

# NTF3055L108, NVF3055L108

## MOSFET – Power, N-Channel, Logic Level, SOT-223 3.0 A, 60 V

Designed for low voltage, high speed switching applications in power supplies, converters and power motor controls and bridge circuits.

### Features

- NVF Prefix for Automotive and Other Applications Requiring Unique Site and Control Change Requirements; AEC-Q101 Qualified and PPAP Capable
- These Devices are Pb-Free and are RoHS Compliant

### Applications

- Power Supplies
- Converters
- Power Motor Controls
- Bridge Circuits

### MAXIMUM RATINGS ( $T_C = 25^\circ\text{C}$ unless otherwise noted)

| Rating                                                                                                                                                                                                                           | Symbol                             | Value                | Unit                                  |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------|----------------------|---------------------------------------|
| Drain-to-Source Voltage                                                                                                                                                                                                          | $V_{DS}$                           | 60                   | Vdc                                   |
| Drain-to-Gate Voltage ( $R_{GS} = 1.0\text{ M}\Omega$ )                                                                                                                                                                          | $V_{DGR}$                          | 60                   | Vdc                                   |
| Gate-to-Source Voltage<br>– Continuous<br>– Non-repetitive ( $t_p \leq 10\text{ ms}$ )                                                                                                                                           | $V_{GS}$                           | $\pm 15$<br>$\pm 20$ | Vdc<br>Vpk                            |
| Drain Current<br>– Continuous @ $T_A = 25^\circ\text{C}$ (Note 1)<br>– Continuous @ $T_A = 100^\circ\text{C}$ (Note 2)<br>– Single Pulse ( $t_p \leq 10\text{ }\mu\text{s}$ )                                                    | $I_D$<br>$I_D$<br>$I_{DM}$         | 3.0<br>1.4<br>9.0    | Adc<br>Apk                            |
| Total Power Dissipation @ $T_A = 25^\circ\text{C}$ (Note 1)<br>Total Power Dissipation @ $T_A = 25^\circ\text{C}$ (Note 2)<br>Derate above $25^\circ\text{C}$                                                                    | $P_D$                              | 2.1<br>1.3<br>0.014  | Watts<br>Watts<br>W/ $^\circ\text{C}$ |
| Operating and Storage Temperature Range                                                                                                                                                                                          | $T_J, T_{stg}$                     | $-55$<br>to $175$    | $^\circ\text{C}$                      |
| Single Pulse Drain-to-Source Avalanche Energy – Starting $T_J = 25^\circ\text{C}$<br>( $V_{DD} = 25\text{ Vdc}$ , $V_{GS} = 5.0\text{ Vdc}$ ,<br>$I_{L(pk)} = 7.0\text{ Apk}$ , $L = 3.0\text{ mH}$ , $V_{DS} = 60\text{ Vdc}$ ) | $E_{AS}$                           | 74                   | mJ                                    |
| Thermal Resistance<br>– Junction-to-Ambient (Note 1)<br>– Junction-to-Ambient (Note 2)                                                                                                                                           | $R_{\theta JA}$<br>$R_{\theta JA}$ | 72.3<br>114          | $^\circ\text{C/W}$                    |
| Maximum Lead Temperature for Soldering Purposes, $1/8"$ from case for 10 seconds                                                                                                                                                 | $T_L$                              | 260                  | $^\circ\text{C}$                      |



Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.



ON Semiconductor®

[www.onsemi.com](http://www.onsemi.com)


3.0 A, 60 V  
 $R_{DS(on)} = 120\text{ m}\Omega$




SOT-223  
CASE 318E  
STYLE 3

### MARKING DIAGRAM

3055L = Device Code  
A = Assembly Location  
Y = Year  
W = Work Week  
■ = Pb-Free Package  
(Note: Microdot may be in either location)



### PIN ASSIGNMENT



### ORDERING INFORMATION

See detailed ordering and shipping information in the package dimensions section on page 6 of this data sheet.

## NTF3055L108, NVF3055L108

1. When surface mounted to an FR4 board using 1" pad size, 1 oz. (Cu. Area 1 in<sup>2</sup>).
2. When surface mounted to an FR4 board using minimum recommended pad size, 2 oz. (Cu. Area 0.272 in<sup>2</sup>).

# NTF3055L108, NVF3055L108

## ELECTRICAL CHARACTERISTICS ( $T_A = 25^\circ\text{C}$ unless otherwise noted)

| Characteristic | Symbol | Min | Typ | Max | Unit |
|----------------|--------|-----|-----|-----|------|
|----------------|--------|-----|-----|-----|------|

### OFF CHARACTERISTICS

|                                                                                                                                                                                 |               |         |          |           |                             |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|---------|----------|-----------|-----------------------------|
| Drain-to-Source Breakdown Voltage (Note 3)<br>( $V_{GS} = 0\text{ Vdc}$ , $I_D = 250\text{ }\mu\text{Adc}$ )<br>Temperature Coefficient (Positive)                              | $V_{(BR)DSS}$ | 60<br>– | 68<br>68 | –<br>–    | Vdc<br>mV/ $^\circ\text{C}$ |
| Zero Gate Voltage Drain Current<br>( $V_{DS} = 60\text{ Vdc}$ , $V_{GS} = 0\text{ Vdc}$ )<br>( $V_{DS} = 60\text{ Vdc}$ , $V_{GS} = 0\text{ Vdc}$ , $T_J = 150^\circ\text{C}$ ) | $I_{DSS}$     | –<br>–  | –<br>–   | 1.0<br>10 | $\mu\text{Adc}$             |
| Gate-Body Leakage Current ( $V_{GS} = \pm 15\text{ Vdc}$ , $V_{DS} = 0\text{ Vdc}$ )                                                                                            | $I_{GSS}$     | –       | –        | $\pm 100$ | nAdc                        |

### ON CHARACTERISTICS (Note 3)

|                                                                                                                                                                                               |              |          |                |           |                             |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------|----------|----------------|-----------|-----------------------------|
| Gate Threshold Voltage (Note 3)<br>( $V_{DS} = V_{GS}$ , $I_D = 250\text{ }\mu\text{Adc}$ )<br>Threshold Temperature Coefficient (Negative)                                                   | $V_{GS(th)}$ | 1.0<br>– | 1.68<br>4.6    | 2.0<br>–  | Vdc<br>mV/ $^\circ\text{C}$ |
| Static Drain-to-Source On-Resistance (Note 3)<br>( $V_{GS} = 5.0\text{ Vdc}$ , $I_D = 1.5\text{ Adc}$ )                                                                                       | $R_{DS(on)}$ | –        | 92             | 120       | m $\Omega$                  |
| Static Drain-to-Source On-Resistance (Note 3)<br>( $V_{GS} = 5.0\text{ Vdc}$ , $I_D = 3.0\text{ Adc}$ )<br>( $V_{GS} = 5.0\text{ Vdc}$ , $I_D = 1.5\text{ Adc}$ , $T_J = 150^\circ\text{C}$ ) | $V_{DS(on)}$ | –        | 0.290<br>0.250 | 0.43<br>– | Vdc                         |
| Forward Transconductance (Note 3) ( $V_{DS} = 7.0\text{ Vdc}$ , $I_D = 3.0\text{ Adc}$ )                                                                                                      | $g_{fs}$     | –        | 5.7            | –         | Mhos                        |

### DYNAMIC CHARACTERISTICS

|                      |                                                                               |           |   |     |     |    |
|----------------------|-------------------------------------------------------------------------------|-----------|---|-----|-----|----|
| Input Capacitance    | $(V_{DS} = 25\text{ Vdc}$ , $V_{GS} = 0\text{ V}$ ,<br>$f = 1.0\text{ MHz}$ ) | $C_{iss}$ | – | 313 | 440 | pF |
| Output Capacitance   |                                                                               | $C_{oss}$ | – | 112 | 160 |    |
| Transfer Capacitance |                                                                               | $C_{rss}$ | – | 40  | 60  |    |

### SWITCHING CHARACTERISTICS (Note 4)

|                     |                                                                                                                             |              |   |     |    |    |
|---------------------|-----------------------------------------------------------------------------------------------------------------------------|--------------|---|-----|----|----|
| Turn-On Delay Time  | $(V_{DD} = 30\text{ Vdc}$ , $I_D = 3.0\text{ Adc}$ ,<br>$V_{GS} = 5.0\text{ Vdc}$ ,<br>$R_G = 9.1\text{ }\Omega$ ) (Note 3) | $t_{d(on)}$  | – | 11  | 25 | ns |
| Rise Time           |                                                                                                                             | $t_r$        | – | 35  | 70 |    |
| Turn-Off Delay Time |                                                                                                                             | $t_{d(off)}$ | – | 22  | 45 |    |
| Fall Time           |                                                                                                                             | $t_f$        | – | 27  | 60 |    |
| Gate Charge         | $(V_{DS} = 48\text{ Vdc}$ , $I_D = 3.0\text{ Adc}$ ,<br>$V_{GS} = 5.0\text{ Vdc}$ ) (Note 3)                                | $Q_T$        | – | 7.6 | 15 | nC |
|                     |                                                                                                                             | $Q_1$        | – | 1.4 | –  |    |
|                     |                                                                                                                             | $Q_2$        | – | 4.0 | –  |    |

### SOURCE-DrAIN DIODE CHARACTERISTICS

|                                |                                                                                                                                                        |          |        |              |          |               |
|--------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------|----------|--------|--------------|----------|---------------|
| Forward On-Voltage             | ( $I_S = 3.0\text{ Adc}$ , $V_{GS} = 0\text{ Vdc}$ )<br>( $I_S = 3.0\text{ Adc}$ , $V_{GS} = 0\text{ Vdc}$ ,<br>$T_J = 150^{\circ}\text{C}$ ) (Note 3) | $V_{SD}$ | –<br>– | 0.87<br>0.72 | 1.0<br>– | Vdc           |
| Reverse Recovery Time          | ( $I_S = 3.0\text{ Adc}$ , $V_{GS} = 0\text{ Vdc}$ ,<br>$dI_S/dt = 100\text{ A}/\mu\text{s}$ ) (Note 3)                                                | $t_{rr}$ | –      | 35           | –        | ns            |
|                                |                                                                                                                                                        | $t_a$    | –      | 21           | –        |               |
|                                |                                                                                                                                                        | $t_b$    | –      | 14           | –        |               |
| Reverse Recovery Stored Charge |                                                                                                                                                        | $Q_{RR}$ | –      | 0.044        | –        | $\mu\text{C}$ |

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

3. Pulse Test: Pulse Width  $\leq 300\text{ }\mu\text{s}$ , Duty Cycle  $\leq 2.0\%$ .

4. Switching characteristics are independent of operating junction temperatures.

TYPICAL ELECTRICAL CHARACTERISTICS




Figure 1. On-Region Characteristics




Figure 2. Transfer Characteristics




Figure 3. On-Resistance vs. Gate-to-Source Voltage




Figure 4. On-Resistance vs. Drain Current and Gate Voltage




Figure 5. On-Resistance Variation with Temperature




Figure 6. Drain-to-Source Leakage Current vs. Voltage

TYPICAL ELECTRICAL CHARACTERISTICS




Figure 7. Capacitance Variation




Figure 8. Gate-to-Source and Drain-to-Source Voltage vs. Total Charge




Figure 9. Resistive Switching Time Variation vs. Gate Resistance




Figure 10. Diode Forward Voltage vs. Current




Figure 11. Maximum Rated Forward Biased Safe Operating Area




Figure 12. Maximum Avalanche Energy vs. Starting Junction Temperature

# NTF3055L108, NVF3055L108

## TYPICAL ELECTRICAL CHARACTERISTICS




Figure 13. Thermal Response

### ORDERING INFORMATION

| Device         | Package                       | Shipping <sup>†</sup> |
|----------------|-------------------------------|-----------------------|
| NTF3055L108T1G | SOT-223 (TO-261)<br>(Pb-Free) | 1000 / Tape & Reel    |
| NVF3055L108T1G | SOT-223 (TO-261)<br>(Pb-Free) | 1000 / Tape & Reel    |

<sup>†</sup>For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.





SCALE 1:1

SOT-223 (TO-261)  
CASE 318E-04  
ISSUE R


DATE 02 OCT 2018




TOP VIEW



SIDE VIEW



FRONT VIEW




DETAIL A

NOTES:

1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 1994.
2. CONTROLLING DIMENSION: MILLIMETERS
3. DIMENSIONS D & E DO NOT INCLUDE MOLD FLASH, PROTRUSIONS OR GATE BURRS. MOLD FLASH, PROTRUSIONS OR GATE BURRS SHALL NOT EXCEED 0.200MM PER SIDE.
4. DATUMS A AND B ARE DETERMINED AT DATUM H.
5. A1 IS DEFINED AS THE VERTICAL DISTANCE FROM THE SEATING PLANE TO THE LOWEST POINT OF THE PACKAGE BODY.
6. POSITIONAL TOLERANCE APPLIES TO DIMENSIONS b AND b1.

| MILLIMETERS |          |      |      |
|-------------|----------|------|------|
| DIM         | MIN.     | NOM. | MAX. |
| A           | 1.50     | 1.63 | 1.75 |
| A1          | 0.02     | 0.06 | 0.10 |
| b           | 0.60     | 0.75 | 0.89 |
| b1          | 2.90     | 3.06 | 3.20 |
| c           | 0.24     | 0.29 | 0.35 |
| D           | 6.30     | 6.50 | 6.70 |
| E           | 3.30     | 3.50 | 3.70 |
| e           | 2.30 BSC |      |      |
| L           | 0.20     | ---  | ---  |
| L1          | 1.50     | 1.75 | 2.00 |
| He          | 6.70     | 7.00 | 7.30 |
| θ           | 0°       | ---  | 10°  |



RECOMMENDED MOUNTING  
FOOTPRINT

|                  |                  |                                                                                                                                                                                     |
|------------------|------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| DOCUMENT NUMBER: | 98ASB42680B      | Electronic versions are uncontrolled except when accessed directly from the Document Repository.<br>Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red. |
| DESCRIPTION:     | SOT-223 (TO-261) | PAGE 1 OF 2                                                                                                                                                                         |

onsemi and onsemi are trademarks of Semiconductor Components Industries, LLC dba onsemi or its subsidiaries in the United States and/or other countries. onsemi reserves the right to make changes without further notice to any products herein. onsemi makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does onsemi assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. onsemi does not convey any license under its patent rights nor the rights of others.

**SOT-223 (TO-261)**  
**CASE 318E-04**  
**ISSUE R**

DATE 02 OCT 2018

|                                                                              |                                                                             |                                                                               |                                                                       |                                                                       |
|------------------------------------------------------------------------------|-----------------------------------------------------------------------------|-------------------------------------------------------------------------------|-----------------------------------------------------------------------|-----------------------------------------------------------------------|
| <b>STYLE 1:</b><br>PIN 1. BASE<br>2. COLLECTOR<br>3. EMITTER<br>4. COLLECTOR | <b>STYLE 2:</b><br>PIN 1. ANODE<br>2. CATHODE<br>3. NC<br>4. CATHODE        | <b>STYLE 3:</b><br>PIN 1. GATE<br>2. DRAIN<br>3. SOURCE<br>4. DRAIN           | <b>STYLE 4:</b><br>PIN 1. SOURCE<br>2. DRAIN<br>3. GATE<br>4. DRAIN   | <b>STYLE 5:</b><br>PIN 1. DRAIN<br>2. GATE<br>3. SOURCE<br>4. GATE    |
| <b>STYLE 6:</b><br>PIN 1. RETURN<br>2. INPUT<br>3. OUTPUT<br>4. INPUT        | <b>STYLE 7:</b><br>PIN 1. ANODE 1<br>2. CATHODE<br>3. ANODE 2<br>4. CATHODE | <b>STYLE 8:</b><br>CANCELLED                                                  | <b>STYLE 9:</b><br>PIN 1. INPUT<br>2. GROUND<br>3. LOGIC<br>4. GROUND | <b>STYLE 10:</b><br>PIN 1. CATHODE<br>2. ANODE<br>3. GATE<br>4. ANODE |
| <b>STYLE 11:</b><br>PIN 1. MT 1<br>2. MT 2<br>3. GATE<br>4. MT 2             | <b>STYLE 12:</b><br>PIN 1. INPUT<br>2. OUTPUT<br>3. NC<br>4. OUTPUT         | <b>STYLE 13:</b><br>PIN 1. GATE<br>2. COLLECTOR<br>3. EMITTER<br>4. COLLECTOR |                                                                       |                                                                       |

**GENERIC  
MARKING DIAGRAM\***



A = Assembly Location  
 Y = Year  
 W = Work Week  
 XXXXX = Specific Device Code  
 ▪ = Pb-Free Package

(Note: Microdot may be in either location)

\*This information is generic. Please refer to device data sheet for actual part marking. Pb-Free indicator, "G" or microdot "▪", may or may not be present. Some products may not follow the Generic Marking.

|                         |                         |                                                                                                                                                                                     |
|-------------------------|-------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>DOCUMENT NUMBER:</b> | <b>98ASB42680B</b>      | Electronic versions are uncontrolled except when accessed directly from the Document Repository.<br>Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red. |
| <b>DESCRIPTION:</b>     | <b>SOT-223 (TO-261)</b> | <b>PAGE 2 OF 2</b>                                                                                                                                                                  |

**onsemi** and **Onsemi** are trademarks of Semiconductor Components Industries, LLC dba **onsemi** or its subsidiaries in the United States and/or other countries. **onsemi** reserves the right to make changes without further notice to any products herein. **onsemi** makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. **onsemi** does not convey any license under its patent rights nor the rights of others.

**onsemi**, **Onsemi**, and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at [www.onsemi.com/site/pdf/Patent-Marking.pdf](http://www.onsemi.com/site/pdf/Patent-Marking.pdf). **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as-is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

## ADDITIONAL INFORMATION

### TECHNICAL PUBLICATIONS:

Technical Library: [www.onsemi.com/design/resources/technical-documentation](http://www.onsemi.com/design/resources/technical-documentation)  
onsemi Website: [www.onsemi.com](http://www.onsemi.com)

### ONLINE SUPPORT: [www.onsemi.com/support](http://www.onsemi.com/support)

For additional information, please contact your local Sales Representative at  
[www.onsemi.com/support/sales](http://www.onsemi.com/support/sales)