

# N-Channel JFET

## MMBFJ110

### Features

- This Device is Designed for Digital Switching Applications where Very Low On Resistance is Mandatory
- Sourced from Process 58
- This is a Pb-Free Device

### MAXIMUM RATINGS ( $T_A = 25^\circ\text{C}$ unless otherwise specified) (Notes 1, 2)

| Symbol         | Parameter                 | Value      | Unit             |
|----------------|---------------------------|------------|------------------|
| $V_{DG}$       | Drain-Source Voltage      | 25         | V                |
| $V_{GS}$       | Gate-Source Voltage       | -25        | V                |
| $I_{GF}$       | Forward Gate Current      | 10         | mA               |
| $T_J$          | Junction Temperature      | 150        | $^\circ\text{C}$ |
| $T_J, T_{STG}$ | Storage Temperature Range | -55 to 150 | $^\circ\text{C}$ |


Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

1. These ratings are based on a maximum junction temperature of  $150^\circ\text{C}$ .
2. These are steady-state limits. onsemi should be consulted on applications involving pulsed or low-duty-cycle operations.

### THERMAL CHARACTERISTICS ( $T_A = 25^\circ\text{C}$ unless otherwise specified) (Note 3)

| Symbol          | Parameter                               | Max  | Unit                      |
|-----------------|-----------------------------------------|------|---------------------------|
| $P_D$           | Total Device Dissipation                | 460  | mW                        |
|                 | Derate Above $25^\circ\text{C}$         | 3.68 | mW/ $^\circ\text{C}$      |
| $R_{\theta JA}$ | Thermal Resistance, Junction-to-Ambient | 270  | $^\circ\text{C}/\text{W}$ |


3. Device mounted on FR-4 PCB 36 mm x 18 mm x 1.5 mm; mounting pad for the collector lead minimum 6  $\text{cm}^2$ .



SOT-23/SUPERSOT™ -23,  
3 LEAD, 1.4x2.9  
CASE 527AG

1. Drain, 2. Source, 3. Gate

### MARKING DIAGRAM



110 = Specific Device Code  
&Y = Year Coding  
&G = Weekly Date Code

### ORDERING INFORMATION

See detailed ordering and shipping information on page 4 of this data sheet.

# MMBFJ110

## ELECTRICAL CHARACTERISTICS ( $T_J = 25^\circ\text{C}$ unless otherwise noted)

| Symbol                     | Parameter                     | Test Condition                                                      | Min  | Max  | Unit |
|----------------------------|-------------------------------|---------------------------------------------------------------------|------|------|------|
| <b>OFF CHARACTERISTICS</b> |                               |                                                                     |      |      |      |
| $V_{(BR)GSS}$              | Gate-Source Breakdown Voltage | $I_G = -10\ \mu\text{A}$ , $V_{DS} = 0$                             | -25  | -    | V    |
| $I_{GSS}$                  | Gate Reverse Current          | $V_{GS} = -15\ \text{V}$ , $V_{DS} = 0$                             | -    | -3.0 | nA   |
|                            |                               | $V_{GS} = -15\ \text{V}$ , $V_{DS} = 0$ , $T_A = 100^\circ\text{C}$ | -    | -200 |      |
| $V_{GS(off)}$              | Gate-Source Cut-Off Voltage   | $V_{DS} = 15\ \text{V}$ , $I_D = 10\ \text{nA}$                     | -0.5 | -4.0 | V    |

## ON CHARACTERISTICS

|              |                                          |                                            |    |    |          |
|--------------|------------------------------------------|--------------------------------------------|----|----|----------|
| $I_{DSS}$    | Zero-Gate Voltage Drain Current (Note 4) | $V_{DS} = 15\ \text{V}$ , $V_{GS} = 0$     | 10 | -  | mA       |
| $r_{DS(on)}$ | Drain-Source On Resistance               | $V_{DS} \leq 0.1\ \text{V}$ , $V_{GS} = 0$ | -  | 18 | $\Omega$ |

## SMALL SIGNAL CHARACTERISTICS

|                                |                                          |                                                                 |   |    |    |
|--------------------------------|------------------------------------------|-----------------------------------------------------------------|---|----|----|
| $C_{dg(on)}$<br>$C_{sg(on)}$   | Drain-Gate & Source-Gate On Capacitance  | $V_{DS} = 0$ , $V_{GS} = 0$ , $f = 1.0\ \text{MHz}$             | - | 85 | pF |
| $C_{dg(off)}$<br>$C_{sg(off)}$ | Drain-Gate & Source-Gate Off Capacitance | $V_{DS} = 0$ , $V_{GS} = -10\ \text{V}$ , $f = 1.0\ \text{MHz}$ | - | 15 | pF |

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

4. Pulse test: pulse width  $\leq 300\ \mu\text{s}$ , duty cycle  $\leq 2\%$ .

## TYPICAL PERFORMANCE CHARACTERISTICS




Figure 1. Common Drain-Source

TYPICAL PERFORMANCE CHARACTERISTICS (continued)




Figure 2. Drain ON Resistance




Figure 3. Drain Current vs. Gate-Source Cut-Off Voltage




Figure 4. Noise Voltage vs. Frequency




Figure 5. Switching Turn-On Time vs. Gate-Source Cut-Off Voltage




Figure 6. Switching Turn-On Time vs. Drain Current




Figure 7. On Resistance vs. Drain Current

# MMBFJ110

## TYPICAL PERFORMANCE CHARACTERISTICS (continued)




Figure 8. Output Conductance vs. Drain Current




Figure 9. Output Conductance vs. Drain Current




Figure 10. Power Dissipation vs. Ambient Temperature

### ORDERING INFORMATION



| Part Number | Top Mark | Package              | Shipping <sup>†</sup> |
|-------------|----------|----------------------|-----------------------|
| MMBFJ110    | 110      | SSOT 3L<br>(Pb-Free) | 3000 / Tape & Reel    |

<sup>†</sup>For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.


SUPERSOT is a trademark of Semiconductor Components Industries, LLC dba "onsemi" or its affiliates and/or subsidiaries in the United States and/or other countries.


**SOT-23/SUPERSOT™ –23, 3 LEAD, 1.4x2.9**  
**CASE 527AG**  
**ISSUE A**

DATE 09 DEC 2019


**LAND PATTERN RECOMMENDATION\***

\*FOR ADDITIONAL INFORMATION ON OUR Pb-FREE STRATEGY AND SOLDERING DETAILS, PLEASE DOWNLOAD THE ON SEMICONDUCTOR SOLDERING AND MOUNTING TECHNIQUES REFERENCE MANUAL, SOLDERRM/D.

**GENERIC MARKING DIAGRAM\***


XXX = Specific Device Code  
M = Month Code  
▪ = Pb-Free Package

(Note: Microdot may be in either location)

\*This information is generic. Please refer to device data sheet for actual part marking. Pb-Free indicator, "G" or microdot "▪", may or may not be present. Some products may not follow the Generic Marking.

|                         |                                            |                                                                                                                                                                                  |
|-------------------------|--------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>DOCUMENT NUMBER:</b> | <b>98AON34319E</b>                         | Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red. |
| <b>DESCRIPTION:</b>     | <b>SOT-23/SUPERSOT-23, 3 LEAD, 1.4X2.9</b> | <b>PAGE 1 OF 1</b>                                                                                                                                                               |

onsemi and onsemi are trademarks of Semiconductor Components Industries, LLC dba onsemi or its subsidiaries in the United States and/or other countries. onsemi reserves the right to make changes without further notice to any products herein. onsemi makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does onsemi assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. onsemi does not convey any license under its patent rights nor the rights of others.

**onsemi**, **Onsemi**, and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at [www.onsemi.com/site/pdf/Patent-Marking.pdf](http://www.onsemi.com/site/pdf/Patent-Marking.pdf). **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as-is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

## ADDITIONAL INFORMATION

### TECHNICAL PUBLICATIONS:

Technical Library: [www.onsemi.com/design/resources/technical-documentation](http://www.onsemi.com/design/resources/technical-documentation)  
onsemi Website: [www.onsemi.com](http://www.onsemi.com)

### ONLINE SUPPORT: [www.onsemi.com/support](http://www.onsemi.com/support)

For additional information, please contact your local Sales Representative at  
[www.onsemi.com/support/sales](http://www.onsemi.com/support/sales)