

# TTC-6-3-HF-M-12DC-PT-I - Surge protection device



2906732

<https://www.phoenixcontact.com/us/products/2906732>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Surge protection with integrated status indicator and knife disconnection for three signal wires with common reference potential. For HF applications and telecommunications interfaces without supply voltage (up to 90 Mbps). Can be used in safety-related circuits up to SIL 3.

## Your advantages

- Space-saving and cost-saving with a narrow overall width of just 6 mm
- Continuous monitoring of protective devices, plus mechanical status indicator with optional remote signaling
- Finding the right product for all possible requirements in MCR applications is easy, thanks to the complete range of products with customized features
- Signal circuits easily interrupted for maintenance work, thanks to vertical knife disconnection

## Commercial data

|                                      |               |
|--------------------------------------|---------------|
| Item number                          | 2906732       |
| Packing unit                         | 1 pc          |
| Minimum order quantity               | 1 pc          |
| Sales key                            | CL23          |
| Product key                          | CL2262        |
| GTIN                                 | 4055626134659 |
| Weight per piece (including packing) | 37 g          |
| Weight per piece (excluding packing) | 37 g          |
| Customs tariff number                | 85363010      |
| Country of origin                    | DE            |

# TTC-6-3-HF-M-12DC-PT-I - Surge protection device



2906732

<https://www.phoenixcontact.com/us/products/2906732>

## Technical data

### Product properties

|                         |   |
|-------------------------|---|
| Product type            | Surge protection for information technology |
| Product family          | TERMITRAB complete                          |
| IEC test classification | C1  |
|                         | C2  |
|                         | C3  |
|                         | D1  |
| Type                    | DIN rail module, one-piece                  |

### Insulation characteristics

|                      |     |
|----------------------|-----|
| Overvoltage category | III |
| Pollution degree     | 2   |


### Electrical properties

|                       |         |
|-----------------------|---------|
| Nominal voltage $U_N$ | 12 V DC |
|-----------------------|---------|

### Connection data

|                                  |   |
|----------------------------------|---|
| Connection method                | Push-in connection                          |
| Conductor cross section flexible | 0.2 mm <sup>2</sup> ... 2.5 mm <sup>2</sup> |
| Conductor cross section rigid    | 0.2 mm <sup>2</sup> ... 4 mm <sup>2</sup>   |
| Conductor cross section AWG      | 24 ... 12                                   |

### Dimensions

|                     |  |
|---------------------|--|
| Dimensional drawing |  |
| Width               | 6.2 mm +0.1 mm   |
| Height              | 105.8 mm   |
| Depth               | 83.5 mm (incl. DIN rail 7.5 mm)  |

### Material specifications

|  |                 |
|--|-----------------|
| Color                                  | gray (RAL 7042) |
| Flammability rating according to UL 94 | V-0             |
| Insulating material                    | PBT             |
| Housing material                       | PBT             |

### Mechanical properties

#### Mechanical data

|                 |    |
|-----------------|----|
| Open side panel | No |
|-----------------|----|

# TTC-6-3-HF-M-12DC-PT-I - Surge protection device



2906732

<https://www.phoenixcontact.com/us/products/2906732>

## Protective circuit

| Direction of action   | Line-Line & Line-Signal Ground/Shield & optional Signal Ground/Shield-Earth Ground |
|---|--|
| Maximum continuous operating voltage $U_C$                            | 15 V DC  |
|   | 10 V AC  |
| Rated current   | 600 mA (40 °C)   |
| Operating effective current $I_C$ at $U_C$                            | $\leq 100 \mu\text{A}$   |
| Protective conductor current $I_{PE}$                                 | $\leq 200 \mu\text{A}$   |
| Nominal discharge current $I_n$ (8/20) $\mu\text{s}$ (line-line)      | 5 kA   |
| Nominal discharge current $I_n$ (8/20) $\mu\text{s}$ (line-ground)    | 5 kA   |
| Pulse discharge current $I_{imp}$ (10/350) $\mu\text{s}$ (line-earth) | 0.5 kA   |
| Total discharge current $I_{Total}$ (8/20) $\mu\text{s}$              | 10 kA  |
| Voltage protection level $U_p$ (line-line)                            | $\leq 145 \text{ V}$ (C1 - 1 kV / 500 A)   |
|   | $\leq 120 \text{ V}$ (C2 - 10 kV / 5 kA)   |
|   | $\leq 25 \text{ V}$ (C3 - 25 A)  |
|   | $\leq 30 \text{ V}$ (C3 - 100 A)   |
| Voltage protection level $U_p$ (line-earth)                           | $\leq 80 \text{ V}$ (C1 - 1 kV / 500 A)  |
|   | $\leq 80 \text{ V}$ (C2 - 10 kV / 5 kA)  |
|   | $\leq 25 \text{ V}$ (C3 - 25 A)  |
|   | $\leq 30 \text{ V}$ (C3 - 100 A)   |
| Voltage protection level $U_p$ static (line-line)                     | $\leq 40 \text{ V}$ (C1 - 1 kV / 500 A)  |
|   | $\leq 95 \text{ V}$ (C2 - 10 kV / 5 kA)  |
| Voltage protection level $U_p$ static (line-earth)                    | $\leq 40 \text{ V}$ (C1 - 1 kV / 500 A)  |
|   | $\leq 95 \text{ V}$ (C2 - 10 kV / 5 kA)  |
| Response time $t_A$ (line-line)                                       | $\leq 1 \text{ ns}$  |
| Response time $t_A$ (line-earth)                                      | $\leq 1 \text{ ns}$  |
| Input attenuation aE, sym.  | typ. 0.3 dB ( $\leq 8.7 \text{ MHz}/150 \Omega$ )                                  |
| Input attenuation aE, asym.   | typ. 0.3 dB ( $\leq 10.5 \text{ MHz}/150 \Omega$ )                                 |
| Cut-off frequency $f_g$ (3 dB), sym. in 150 $\Omega$ system           | typ. 60 MHz  |
| Cut-off frequency $f_g$ (3 dB), asym. (PE) in 150 $\Omega$ system     | typ. 60 MHz  |
| Capacity (Core-Core)  | typ. 32 pF   |
| Capacity (Core-Earth)   | typ. 32 pF   |
| Resistance per path   | 1.65 $\Omega \pm 20 \%$  |
| Surge protection fault message  | optical  |
| Max. required back-up fuse  | 630 mA (FF)  |
| Impulse durability (line-line)  | C1 - 1 kV / 500 A  |
|   | C2 - 10 kV / 5 kA  |
|   | C3 - 100 A   |
| Impulse durability (line-earth)                                       | C1 - 1 kV / 500 A  |
|   | C2 - 10 kV / 5 kA  |
|   | C3 - 100 A   |
|   | D1 - 500 A   |
| Pulse reset time (line-line)  | $\leq 30 \text{ ms}$   |

# TTC-6-3-HF-M-12DC-PT-I - Surge protection device



2906732

<https://www.phoenixcontact.com/us/products/2906732>

|                               |         |
|-------------------------------|---------|
| Pulse reset time (line-earth) | ≤ 30 ms |
|-------------------------------|---------|

## Additional technical data

|  |            |
|--|------------|
| Max. total discharge current $I_{\text{total max}} (8/20) \mu\text{s}$ | 20 kA (1x) |
|--|------------|

## Environmental and real-life conditions

### Ambient conditions

|   |                  |
|---|------------------|
| Degree of protection                    | IP20             |
| Ambient temperature (operation)         | -40 °C ... 85 °C |
| Ambient temperature (storage/transport) | -40 °C ... 85 °C |
| Altitude                                | ≤ 4000 m (amsl)  |
| Permissible humidity (operation)        | 5 % ... 95 %     |

## Standards and regulations

|                          |   |
|--------------------------|---|
| Standards/specifications | IEC 61643-21  |
| Note                     | 2000 + corrigendum 2001 + A1:2008, modified + A2:2012 |

### EN 61643-21

|                          |                          |
|--------------------------|--------------------------|
| Standards/specifications | EN 61643-21              |
| Note                     | 2001 + A1:2009 + A2:2013 |

## Mounting

|               |                          |
|---------------|--------------------------|
| Mounting type | DIN rail: TH 35 - 7.5 mm |
|---------------|--------------------------|

# TTC-6-3-HF-M-12DC-PT-I - Surge protection device




2906732

<https://www.phoenixcontact.com/us/products/2906732>

## Drawings

Dimensional drawing




Schematic diagram


| TTC-6-3-HF-M-...-I   |                          |                           |                          |       |                          |                           |      |                          |       |
|--|--------------------------|---------------------------|--------------------------|-------|--------------------------|---------------------------|------|--------------------------|-------|
| Category   | 1001 architecture, HFT=0 |                           |                          |       | 1002 architecture, HFT=1 |                           |      |                          |       |
|  | PFD <sub>AVG</sub>       | PFH                       | Used budget of SIL 2 SIF |       | PFD <sub>AVG</sub>       | PFH                       | CCF  | Used budget of SIL 3 SIF |       |
|  |                          |                           | PFD <sub>AVG</sub>       | PFH   |                          |                           |      | PFD <sub>AVG</sub>       | PFH   |
|  | 1.21·10 <sup>-5</sup>    | 2.16·10 <sup>-8</sup> 1/h | 1.2 %                    | 2.2 % | 6.09·10 <sup>-6</sup>    | 1.08·10 <sup>-9</sup> 1/h | 5 %  | 0.6 %                    | 1.1 % |
|  |                          |                           |                          |       | 1.22·10 <sup>-5</sup>    | 2.16·10 <sup>-9</sup> 1/h | 10 % | 1.2 %                    | 2.2 % |
| Calculation based on exida report, Phoenix Contact 16/06-072 R023 V3R1<br>exida Profile 1, FMEDA Analysis 2, T <sub>proof</sub> : 1 year, MT: 10 years, MTTR: 24 hours, PTC: 99%<br>Used standards<br>IEC/EN 61508, edition 2010 (device specific)<br>IEC/EN 61511, edition 2016 + COR1:2016 + A1:2017 (system specific) |                          |                           |                          |       |                          |                           |      |                          |       |

## Functional safety scenarios

Diagram



Circuit diagram



2906732

<https://www.phoenixcontact.com/us/products/2906732>

## Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/2906732>



**CSA**

Approval ID: 70136717



**DNV GL**

Approval ID: TAE000027G



**UL Listed**

Approval ID: FILE E 138168



**CSAus**

Approval ID: 70136717

**UAE-RoHS**

Approval ID: 22-06-16191

**Functional Safety**

Approval ID: 16-06-072 R023 V3R1

# TTC-6-3-HF-M-12DC-PT-I - Surge protection device



2906732

<https://www.phoenixcontact.com/us/products/2906732>

## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-13.0 | 27171503 |
| ECLASS-15.0 | 27171503 |

### ETIM

|          |          |
|----------|----------|
| ETIM 9.0 | EC000943 |
|----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 39121600 |
|-------------|----------|

2906732

<https://www.phoenixcontact.com/us/products/2906732>

## Environmental product compliance

### EU RoHS

|   |              |
|---|--------------|
| Fulfills EU RoHS substance requirements | Yes          |
| Exemption                               | 7(a), 7(c)-I |

### China RoHS

|  |   |
|--|---|
| Environment friendly use period (EFUP) | EFUP-50   |
|  | An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required. |

### EU REACH SVHC

|                                     |                                      |
|-------------------------------------|--------------------------------------|
| REACH candidate substance (CAS No.) | Lead(CAS: 7439-92-1)                 |
| SCIP                                | 0b70abea-4fac-458b-8626-7bc1021db673 |

Phoenix Contact 2025 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)