

Product data sheet

Specifications



Auxiliary contact block, Easy TeSys GP2E, 1NO+1NC

GPEFC11

Main

Range	Easy TeSys
Device short name	GPEFC
Product or component type	Auxiliary contact block
Mounting location	Front side
Pole contact composition	1 NO + 1 NC
Connections - terminals	Screw clamp terminals1 0.002...0.004 in ² (1...2.5 mm ²) - solid Screw clamp terminals2 0.002...0.004 in ² (1...2.5 mm ²) - solid Screw clamp terminals1 0.001...0.004 in ² (0.75...2.5 mm ²) - flexible without cable end Screw clamp terminals2 0.001...0.004 in ² (0.75...2.5 mm ²) - flexible without cable end Screw clamp terminals1 0.001...0.002 in ² (0.75...1.5 mm ²) - flexible with cable end
Quantity per set	Set of 10

Complementary

[Ui] rated insulation voltage	300 V UL 60947-4-1 300 V cUL 250 V IEC 60947-1
[Ue] rated operational voltage	24...240 V AC 24...60 V DC
[Ith] conventional free air thermal current	2.5 A
Mechanical durability	100000 cycles
Minimum switching current	5 mA
Minimum switching voltage	17 V
Protection type	GG fuse 10 A GB2CB06 circuit breaker 10 A
Rated operational power in VA	120 VA 110...120 V AC-15 100000 cycles 120 VA 230...240 V AC-15 100000 cycles 48 VA 24 V AC-15 100000 cycles 60 VA 48 V AC-15 100000 cycles
Rated operational power in W	15 W 48 V DC-13 100000 cycles 24 W 24 V DC-13 100000 cycles 9 W 60 V DC-13 100000 cycles
Tightening torque	12.4 lbf.in (1.4 N.m) screw clamp terminals
Height	0.4 in (11 mm) 0.6 in (15.5 mm)
Width	1.8 in (45 mm) 1.8 in (45 mm)
Depth	1.1 in (29 mm) 1.6 in (41 mm)

Net weight	0.04 lb(US) (0.02 kg) 0.057 lb(US) (0.026 kg)
-------------------	--

Colour	Dark grey
---------------	-----------

Environment

Environmental characteristic	Normal environment
-------------------------------------	--------------------

Packing Units

Unit Type of Package 1	PCE
-------------------------------	-----

Number of Units in Package 1	1
-------------------------------------	---

Package 1 Height	0.50 in (1.27 cm)
-------------------------	-------------------

Package 1 Width	1.30 in (3.3 cm)
------------------------	------------------

Package 1 Length	1.80 in (4.57 cm)
-------------------------	-------------------

Package 1 Weight	0.04 lb(US) (0.02 kg)
-------------------------	-----------------------

Unit Type of Package 2	S02
-------------------------------	-----

Number of Units in Package 2	220
-------------------------------------	-----

Package 2 Height	5.91 in (15 cm)
-------------------------	-----------------

Package 2 Width	11.81 in (30 cm)
------------------------	------------------

Package 2 Length	15.75 in (40 cm)
-------------------------	------------------

Package 2 Weight	10.752 lb(US) (4.877 kg)
-------------------------	--------------------------

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

Carbon footprint (kg CO2 eq, Total Life cycle) 1

Environmental Disclosure [Product Environmental Profile](#)

Use Better

Materials and Substances

Packaging made with recycled cardboard Yes

Packaging without single use plastic No

[EU RoHS Directive](#) Compliant

REACH Regulation [REACH Declaration](#)

Use Again

Repack and remanufacture

Circularity Profile [End of Life Information](#)

Take-back No

Image of product / Alternate images

Alternative



