

1400N series

Momentary pushbutton switches •
snap-in mounting • square plunger



DISTINCTIVE FEATURES

Butt action contacts, double break

Solder lug, straight PC and quick-connect terminals



ELECTRICAL SPECIFICATIONS

- Max. current/voltage rating with resistive load :
- silver contacts (A) : 6 A 12 VDC
- silver plated copper contacts (C) : 3 A 12 VDC
- Initial contact resistance : 10 mΩ
- Insulation resistance : 1,000 MΩ min. at 500 VDC
- Dielectric strength :
1,500 Vrms 50 Hz min. between terminals
2,000 Vrms 50 Hz min. between terminals and metal panel
- Electrical life : 10,000 cycles at full load



GENERAL SPECIFICATIONS

- Panel thickness : 2 mm (.078) max.
- Operating temperature : -20 °C to +55 °C (-4 °F to +131 °F)



MATERIALS

- Case : polyamide
- Plunger : polyamide
- Contacts :
A : silver
C : gold plated silver

APEM products may be recycled at end-of-life for the re-claiming of valuable metal components.

The company reserves the right to change specifications without notice.




1400N series


Momentary pushbutton switches •
snap-in mounting • square plunger




PANEL CUT-OUT




TERMINALS



Solder lug




Straight PC



Quick-connect



ELECTRICAL FUNCTIONS




1400N series

Momentary pushbutton switches •
snap-in mounting • square plunger



BUILD YOUR PART NUMBER



ABOUT THIS SERIES

On the following pages, you will find successively basic part numbers of switches and options in the same order as in above chart.



Notice : please note that not all combinations of above numbers are available. Refer to following pages for further information.

1400N series

Momentary pushbutton switches •
snap-in mounting • square plunger

SOLDER LUG TERMINALS



1412N		Normally Closed
1413N		Normally Open
1415N		Changeover

STRAIGHT PC TERMINALS






1442N		Normally Closed
1443N		Normally Open
1445N		Changeover

QUICK-CONNECT TERMINALS 4.7 X 0.8 (.185 X .031)



1412N/8		Normally Closed
1413N/8		Normally Open
1415N/8		Changeover



CONTACT MATERIALS



- A Silver
- C Copper, silver plated

1400N series

Momentary pushbutton switches •
snap-in mounting • square plunger

PLUNGER COLORS

BASIC P/N

- | | |
|---|------------------|
| 2 | Black (standard) |
| 3 | Green |
| 6 | Red |
| 7 | Ivory |

ⓘ Switch frame supplied in black.