

Product data sheet

Specifications

SQUARE D



Switch, reversing drum, 2 HP at 230 VAC single phase, 2 HP at 575 VAC polyphase, handle operated, NEMA 4 enclosure

2601AW2

Product availability: Stock - Normally stocked in distribution facility

Main

Product	Reversing Drum Switch
Enclosure Rating	NEMA 4
Horsepower	1.5 hp 115 V AC, 1 phase 2 hp 230 V AC, 1 phase 2 hp 200 V AC, 3 phase 2 hp 230 V AC, 3 phase 2 hp 460 V AC, 3 phase 2 hp 575 V AC, 3 phase 0.25 hp 115 V DC 0.25 hp 230 V DC
Maximum Rated Voltage	600 V AC 250 V DC
Number of Poles	3P

Complementary

Certifications	CSA UL Listed
Electrical Connection	Screw-clamp terminals
Type	A

Ordering and shipping details

Category	US10CP121116
Discount Schedule	0CP1
GTIN	785901784432
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	4.60 in (11.684 cm)
Package 1 Width	5.60 in (14.224 cm)
Package 1 Length	7.90 in (20.066 cm)
Package weight(Lbs)	2.650 lb(US) (1.202 kg)

Contractual warranty

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Warranty

18 months

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

 Materials and Substances	
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Not compliant
REACH Regulation	REACH Declaration
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Use Again

 Repack and remanufacture	
Take-back	No