

35-210-041-S ✓ ACTIVE

KISSLING | KISSLING Series 35

TE Internal #: K1151411

250 A Battery Disconnect Switch, 32 VDC, 1 Pole, Double Wing Handle, 0 Auxillary Positions, Round Flange, KISSLING Series 35

[View on TE.com >](#)



Switches > Battery Disconnect Switches > Battery Disconnect, 200A, 1 Pole



Operating Voltage: **32 VDC**

Switch Main Contact Current Rating: **250 A**

Number of Poles: **1**

Operating Handle Type: **Double Wing Handle**

Termination Thread Size: **M8**

[All Battery Disconnect, 200A, 1 Pole \(30\)](#)

## Features

### Product Type Features

Sealed Device	Yes
---------------	-----

### Configuration Features

Number of Poles	1
Number of Auxiliary Contacts	0
Switch Keying Option	Not Removable

### Electrical Characteristics

Operating Voltage	32 VDC
Switch Main Contact Current Rating	250 A

### Body Features

Operating Handle Color	Black
------------------------	-------

### Mechanical Attachment

Operating Handle Type	Double Wing Handle
Termination Thread Size	M8
Switch Mounting Option	Round Flange

### Dimensions

Screw Hole Diameter	7 mm [.276 in]
---------------------	----------------

Centerline Between Flange Screw Holes

38 mm[1.5 in]

### Usage Conditions

Operating Temperature Range

-40 – 85 °C[-40 – 185 °F]

### Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU

Not Compliant

EU ELV Directive 2000/53/EC

Compliant

China RoHS 2 Directive MIIT Order No 32, 2016

Restricted Materials Above Threshold

EU REACH Regulation (EC) No. 1907/2006

Current ECHA Candidate List: JUNE 2025 (250)  
Candidate List Declared Against: JAN 2025 (247)  
SVHC > Threshold:  
Pb (3.5% in Component Part)

**Article Safe Usage Statements:**

Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.

Halogen Content

Not Yet Reviewed for halogen content

Solder Process Capability

Not reviewed for solder process capability

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

### Compatible Parts



## Also in the Series | KISSLING Series 35



Battery Disconnect Switches(175)



Rotary Switches(6)

## Customers Also Bought

TE Part #0462-209-16141  
SOC, SOLID, SIZE 16, 14AWG, NITE Part #DRC22-40PB  
40P RECP ASMTE Part #CAT-J41-DDRC  
DEUTSCH DT Receptacle ConnectorsTE Part #CAT-D487-W416  
Wedgelocks: DEUTSCH DTTE Part #DT06-4S  
PLG, 4P, GRY, NTE Part #HDP24-24-47PE  
REC, 47P, BLK, E, 16/20, PTE Part #282104-1  
AMP SUPERSEAL 1.5 SERIES 2P CATE Part #8-1676123-0  
1/2W SM M/OX 5% 1K6

## Documents

### Product Drawings

#### Battery Disconnecter 35-210-041-S

English

### CAD Files

3D PDF

3D

#### Customer View Model

[ENG\\_CVM\\_CVM\\_35-210-041-S\\_A.2d\\_dxf.zip](#)

English

#### Customer View Model

[ENG\\_CVM\\_CVM\\_35-210-041-S\\_A.3d\\_igs.zip](#)

English

#### Customer View Model

[ENG\\_CVM\\_CVM\\_35-210-041-S\\_A.3d\\_stp.zip](#)



English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

### Datasheets & Catalog Pages

[KISSLING SINGLE POLE BI-STABLE RELAYS Series 30 / 300A](#)

English

[KISSLING BATTERY DISCONNECTOR Series 35 / 200A](#)

English