

Product data sheet

Specifications



Disconnect switch, TeSys VLS, additional pole, 63A, for 30A and 63A switch, size 2, door mount

VLS1P063D2S

Main

| | |
|-------------------------------|----------------------------|
| Range | TeSys |
| Device short name | VLS1P |
| Product or component type | Additional pole |
| Performance level | High performance |
| Poles description | 1P |
| Contacts type and composition | 1 NO |
| Contact operation | Simultaneous |
| Range compatibility | TeSys TeSys VARIO LS VLS3P |
| Network type | AC |
| Network frequency | 50/60 Hz |
| Suitability for isolation | Yes |

Complementary

| | |
|--|--|
| Mounting location | Right Left |
| Mounting support | Door |
| [Ue] rated operational voltage | 690 V AC 50/60 Hz |
| [Uimp] rated impulse withstand voltage | 8 kV |
| [Ith] conventional free air thermal current | 63 A (at 131 °F (55 °C)) |
| [Ithe] conventional enclosed thermal current | 63 A |
| [Ie] rated operational current | 60 A Ue: 600 V UL98 63 A AC-21A Ue: 400 V 63 A AC-21A Ue: 500 V 63 A AC-21A Ue: 690 V 63 A AC-22A Ue: 400 V 63 A AC-22A Ue: 500 V 63 A AC-22A Ue: 690 V 63 A AC-23A Ue: 400 V 63 A AC-23A Ue: 500 V 47 A AC-23A Ue: 690 V |
| Rated operational power in W | 30 kW 400 V AC-23A) 45 kW 500 V AC-23A) 45 kW 690 V AC-23A) |
| Intermittent duty class | Class 120 - 60 % |
| Making capacity (I Rms) | 94.5 A 690 V AC-21A 189 A 690 V AC-22A 630 A 690 V AC-23A |
| [Icm] rated short-circuit making capacity | 3550 A 690 V |

| | |
|--|--|
| [I_{cw}] rated short-time withstand Rms current | 2500 A 690 V 1 s |
| Rated conditional short-circuit current | 50 kA 400 V 63 A gG |
| Breaking capacity | 94.5 A 690 V AC-21A) 189 A 690 V AC-22A) 504 A 690 V AC-23A) |
| Mechanical durability | 30000 cycles |
| Electrical durability | 30000 cycles AC-21 |
| Connections - terminals | Power circuit screw clamp terminals 0.08 in ² (50 mm ²) solid Power circuit screw clamp terminals 0.1 in ² (70 mm ²) flexible - without cable end |
| Tightening torque | Power circuit 44.3...53.1 lbf.in (5...6 N.m) screw clamp terminals |
| Height | 3.9 in (100 mm) |
| Width | 0.9 in (23 mm) |
| Depth | 1.9 in (48.6 mm) |
| Net weight | 0.24 lb(US) (0.11 kg) |
| Colour | Grey |

Environment

| | |
|--|--|
| Standards | UL98 CSA C22.2 No 4 IEC 60947-3 |
| Product certifications | cULus GL |
| IP degree of protection | IP20 conforming to IEC 60529 |
| Mechanical robustness | Vibrations 2...100 Hz Fc 0.7 g) IEC 60068-2-6 Shocks 11 ms Ea 15 gn) IEC 60068-2-27 |
| Ambient air temperature for operation | -13...131 °F (-25...55 °C) |
| Fire resistance | 1760 °F (960 °C) IEC 60695-2-11 |

Packing Units

| | |
|-------------------------------------|--------------------------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 2.56 in (6.500 cm) |
| Package 1 Width | 2.80 in (7.100 cm) |
| Package 1 Length | 4.45 in (11.300 cm) |
| Package 1 Weight | 4.691 oz (133.000 g) |
| Unit Type of Package 2 | S03 |
| Number of Units in Package 2 | 36 |
| Package 2 Height | 11.81 in (30.000 cm) |
| Package 2 Width | 11.81 in (30.000 cm) |
| Package 2 Length | 15.75 in (40.000 cm) |
| Package 2 Weight | 11.669 lb(US) (5.293 kg) |

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

|  Materials and Substances | |
|---|-----------|
| Packaging made with recycled cardboard | Yes |
| Packaging without single use plastic | No |
| EU RoHS Directive | Compliant |

Use Again

|  Repack and remanufacture | |
|---|---|
| Take-back | No |
| WEEE Label |  The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |