

# Product data sheet

Specifications



Disconnect switch, TeSys VLS,  
body switch, 80A, 40HP at 480VAC,  
UL98, three phase, 100kA SCCR,  
size 2, DIN rail mount

VLS3P080R2

## Main

Range	TeSys
Product Name	TeSys VARIO LS
Device Short Name	VLS3P
Product Type	Switch body

## Complementary

Device Composition	Handle Switch
Mounting Support	Back DIN rail
Mounting Method	By clips back
Performance Level	High performance
Number of Poles	3P
Contact Type and Composition	3 NO
Color	Grey
[Ue] UL Rated Operational Voltage	600 V AC 50/60 Hz UL 508
[Ue] IEC Rated Operational Voltage	690 V AC 50/60 Hz
UL Maxium Horsepower Ratings	25 hp 200/208 V AC 25 hp 240 V AC 40 hp 480 V AC 40 hp 600 V AC 3 hp 120 V AC 10 hp 240 V AC
IEC Rated Operational Power in W	45 kW 400 V AC-23A) 45 kW 500 V AC-23A) 45 kW 690 V AC-23A)
[Ie] Rated Operational Current	100 A Ue: 600 V UL98 80 A AC-21A Ue: 400 V 80 A AC-21A Ue: 500 V 80 A AC-21A Ue: 690 V 80 A AC-22A Ue: 400 V 80 A AC-22A Ue: 500 V 80 A AC-22A Ue: 690 V 80 A AC-23A Ue: 400 V 63 A AC-23A Ue: 500 V 47 A AC-23A Ue: 690 V
[Ith] Conventional Free Air Thermal Current	80 A (at 131 °F (55 °C))
[Ithe] Conventional Enclosed Thermal Current	80 A
Making Capacity ( I Rms)	120 A 690 V AC-21A 240 A 690 V AC-22A 800 A 690 V AC-23A

<b>Breaking Capacity</b>	120 A 690 V AC-21A) 240 A 690 V AC-22A) 640 A 690 V AC-23A)
<b>SCCR</b>	Circuit-breaker 200 A maximum: 100 kA at 480 V AC Fuse CC 200 A maximum: 100 kA at 480 V AC Fuse J 200 A maximum: 100 kA at 480 V AC Fuse T 200 A maximum: 100 kA at 480 V AC Fuse CC 100 A maximum: 50 kA at 600 V AC Fuse J 100 A maximum: 50 kA at 600 V AC Fuse T 100 A maximum: 50 kA at 600 V AC
<b>Rated Conditional Short Circuit Current</b>	50 kA 400 V 80 A gG
<b>[Icm] Rated Short Circuit Making Capacity</b>	3550 A 690 V
<b>[Icw] Rated Short Time Withstand Current</b>	2500 A 690 V 1 s
<b>[Uimp] Rated Impulse Withstand Voltage</b>	8 kV
<b>Suitability for Isolation</b>	Yes
<b>Network Type</b>	AC
<b>Network Frequency</b>	50/60 Hz
<b>Intermittent Duty Class</b>	Class 120 - 60 %
<b>Control Type</b>	Rotary handle
<b>Rotary Handle Mounting Style</b>	Direct
<b>Handle Color</b>	Black
<b>Handle Front Plate Color</b>	Grey
<b>Rotary Handle Padlocking</b>	1 padlock 0.2 in (4 mm)
<b>Marking</b>	0 - 1
<b>Mechanical Durability</b>	30000 cycles
<b>Electrical Durability</b>	30000 cycles AC-21
<b>UL Wire Size</b>	AWG 12...AWG 1 copper
<b>IEC Terminal Connection</b>	Power circuit screw clamp terminals 0.08 in <sup>2</sup> (50 mm <sup>2</sup> ) solid Power circuit screw clamp terminals 0.1 in <sup>2</sup> (70 mm <sup>2</sup> ) flexible - without cable end
<b>Tightening Torque</b>	Power circuit 44.3...53.1 lbf.in (5...6 N.m) screw clamp terminals
<b>Height</b>	3.0 in (75 mm)
<b>Width</b>	2.8 in (70 mm)
<b>Depth</b>	3.9 in (100 mm)
<b>Product Weight</b>	0.805 lb(US) (0.365 kg)

## Environment

<b>Standards</b>	UL98 CSA C22.2 No 4 IEC 60947-3
<b>Product Certifications</b>	cULus GL
<b>Degree of Protection</b>	IP20 conforming to IEC 60529
<b>Mechanical Robustness</b>	Vibrations 2...100 Hz Fc 0.7 g) IEC 60068-2-6 Shocks 11 ms Ea 15 gn) IEC 60068-2-27
<b>Ambient Air Temperature for Operation</b>	-13...131 °F (-25...55 °C)
<b>Fire Resistance</b>	1760 °F (960 °C) IEC 60695-2-11

---

Compatibility Code	VLS
--------------------	-----

## Packing Units

---

Unit Type of Package 1	PCE
------------------------	-----

---

Number of Units in Package 1	1
------------------------------	---

---

Package 1 Height	3.11 in (7.900 cm)
------------------	--------------------

---

Package 1 Width	3.35 in (8.500 cm)
-----------------	--------------------

---

Package 1 Length	4.72 in (12.000 cm)
------------------	---------------------

---

Package 1 Weight	14.427 oz (409.000 g)
------------------	-----------------------

---

Unit Type of Package 2	S03
------------------------	-----

---

Number of Units in Package 2	27
------------------------------	----

---

Package 2 Height	11.81 in (30.000 cm)
------------------	----------------------

---

Package 2 Width	11.81 in (30.000 cm)
-----------------	----------------------

---

Package 2 Length	15.75 in (40.000 cm)
------------------	----------------------

---

Package 2 Weight	25.499 lb(US) (11.566 kg)
------------------	---------------------------

## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Use Better

 <b>Materials and Substances</b>	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
<a href="#">EU RoHS Directive</a>	Compliant

### Use Again

 <b>Repack and remanufacture</b>	
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins