

TL3301 SERIES TACT SWITCH

ANTI-VANDAL SWITCHES
 DETECTOR SWITCHES
 DIP SWITCHES
 KEYLOCK SWITCHES
 NAVIGATION SWITCHES
 PUSHBUTTON SWITCHES
 ROCKER SWITCHES
 ROTARY SWITCHES
 SLIDE SWITCHES
 SNAP ACTION SWITCHES
TACTILE SWITCHES
 TOGGLE SWITCHES
 CAP OPTIONS



APPLICATIONS / MARKETS



Audio / Visual



Computer Peripherals



Consumer Electronics



Instrumentation



Telecommunication



Medical Devices

RoHS

SPECIFICATIONS

Contact Rating: 50mA @ 12VDC
Electrical Life: 100,000 cycles
Contact Resistance: 100mΩ Max
Insulation Resistance: 100MΩ Min @ 500VDC
Dielectric Strength: 250VAC for 1 Minute
Operating Temperature: -40°C to 85°C
Storage Temperature: -40°C to 85°C
Travel: 0.25mm
Contact Arrangement: SPST
Actuation Force: 100gf; 160gf; 260gf

FEATURES & BENEFITS

- Single pole single throw
- Surface mount
- 6mm x 6mm
- Cap options
- Multiple actuator options
- Silver or gold contacts
- Gull wing or J-lead termination
- Tape & reel packaging

PART NUMBER CONFIGURATOR

Series

TL3301

Actuator Options

A - 5.0mm
 B - 9.5mm
 C - 8.0mm
 D - 13.0mm
 E - 7.3mm
 F - 7.0mm
 N - 4.3mm
 P - 8.5mm
 SP - 2.8mm square (with cap option)
 T - 2.4mm square

Actuation Force

F100 - 100 gf
 F160 - 160 gf
 F260 - 260 gf

Contact Material

Q - Silver
 R - Gold

Termination

G - Gull wing
 J - J-lead

Cap Options

Order Caps Separately (SP Actuator only)
 1C
 1D
 1R
 1S

Specifications subject to change without notice 7.25.2025



E-SWITCH®


www.e-switch.com

800.867.2717



1

TL3301 SERIES TACT SWITCH



Termination Options



ACTUATOR OPTION	"L" DIMENSION
N	4.3mm
A	5.0mm
E	7.3mm
F	7.0mm
C	8.0mm
P	8.5mm
B	9.5mm
D	13.0mm



GULLWING TERMINATION




ANTI-VANDAL SWITCHES
 DETECTOR SWITCHES
 DIP SWITCHES
 KEYLOCK SWITCHES
 NAVIGATION SWITCHES
 PUSHBUTTON SWITCHES
 ROCKER SWITCHES
 ROTARY SWITCHES
 SLIDE SWITCHES
 SNAP ACTION SWITCHES
 TACTILE SWITCHES
 TOGGLE SWITCHES
 CAP OPTIONS





TL3301 SERIES TACT SWITCH



Termination Options



ACTUATOR OPTION	"L" DIMENSION
N	4.3mm
A	5.0mm
E	7.3mm
F	7.0mm
C	8.0mm
P	8.5mm
B	9.5mm
D	13.0mm






J-LEAD TERMINATION





TL3301 SERIES TACT SWITCH

Actuator Options






SP ACTUATOR (GULLWING TERMINATION SHOWN)



TL3301 SERIES TACT SWITCH

Termination Options



T ACTUATOR
(GULLWING TERMINATION SHOWN)

