

2-1904058-7 ✓ ACTIVE

[EVC | Mini K HV Precharge Relay](#)

TE Internal #: 2-1904058-7

High Voltage Relay, DC, Monostable, 1 Form X SPST-NO-DM, 20 A  
Contact Rating, 12 VDC Coil Voltage, 400 VDC Contact Voltage,  
Mini K HV Precharge Relay

[View on TE.com >](#)



Relays & Contactors > Electromechanical Relays



Relay & Contactor Type: **High Voltage Relay**

Coil Magnetic System: **Monostable**

Contact Arrangement: **1 Form X SPST-NO-DM**

Current Type: **DC**

Contact Current Rating: **20 A**

## Features

### Product Type Features

Relay & Contactor Type	High Voltage Relay
------------------------	--------------------

### Configuration Features

Coil Special Features	Resistor in Parallel
Contact Arrangement	1 Form X SPST-NO-DM

### Electrical Characteristics

Contact Limiting Making Current	20 A
Contact Limiting Breaking Current	20 A
Insulation Initial Dielectric Between Open Contacts	2000 Vrms
Contact Current Rating	20 A
Coil Voltage Rating	12 VDC
Contact Switching Voltage (Max)	450 VDC
Contact Voltage Rating	400 VDC
Coil Resistance	41.6 $\Omega$
Coil Power Rating DC	3.5 W
Insulation Initial Dielectric Between Contacts & Coil	2000 Vrms

### Body Features

Product Weight	39 g[1.376 oz]
----------------	----------------



Enclosure Type	Flux Resistant Automatic Solder Capable & Washable
----------------	--

### Contact Features

Contact Material	Silver Alloy
------------------	--------------

### Termination Features

Main Termination & Connection Type	Quick Connect Terminals
------------------------------------	-------------------------

Coil Termination & Connection Type	Quick Connect Terminals
------------------------------------	-------------------------

### Mechanical Attachment

Product Mount Type	Socket Mount
--------------------	--------------

### Dimensions

Product Width	36.6 mm[1.441 in]
---------------	-------------------

Product Length	29.9 mm[1.177 in]
----------------	-------------------

Product Height	29.9 mm[1.177 in]
----------------	-------------------

### Usage Conditions

Operating Temperature Range	-40 – 85 °C[-40 – 185 °F]
-----------------------------	---------------------------

Environmental Category of Protection	RTIII
--------------------------------------	-------

Environmental Ambient Temperature (Max)	85 °C[185 °F]
---	---------------

### Operation/Application

Coil Magnetic System	Monostable
----------------------	------------

Current Type	DC
--------------	----

### Other

Contact Current Class	>16 – ≤25 A
-----------------------	-------------

Coil Power Rating Class	>3 – ≤10 W
-------------------------	------------

Height Class (Mechanical)	>27 – ≤33 mm[>1.063 – ≤1.299 in]
---------------------------	----------------------------------

Length Class (Mechanical)	>22 – ≤33 mm[>.866 – ≤1.299 in]
---------------------------	---------------------------------

Width Class (Mechanical)	>33 mm[>1.299 in]
--------------------------	-------------------

### Product Compliance

[For compliance documentation, visit the product page on TE.com>](#)

EU RoHS Directive 2011/65/EU	Compliant
------------------------------	-----------

EU ELV Directive 2000/53/EC	Compliant with Exemptions
-----------------------------	---------------------------

China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
---	---



EU REACH Regulation (EC) No. 1907/2006

Current ECHA Candidate List: JAN 2025 (247)

Candidate List Declared Against: JUNE 2022 (224)

Does not contain REACH SVHC

Halogen Content

BFR/CFR/PVC Free, but Br/Cl >900 ppm in other sources.

Solder Process Capability

Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

### Compatible Parts




### Also in the Series | Mini K HV Precharge Relay



### Customers Also Bought



TE Part #YHV280-2PM-S-4MM-A  
HVA280-2PHM,SHUNTED,4SQMM,  
KEY A



TE Part #966871-1  
MOD2 ST-WANNE 2X10P



TE Part #1-1393779-8  
V23101D 7A201



TE Part #1564411-6  
SLIDE,TAB HSG GROUP E



TE Part #4-1625890-3  
2W SM M/OX 5% 33R



TE Part #2-1625971-0  
HSA25 1R2 5%



TE Part #1703806-1  
ADAPTER,SEALED,ASSY



TE Part #2112166-2  
SLIDE,FOR 21POS.



TE Part #1-2394804-1  
4POS,TAB0.5X0.4,HDR ASSY,180DEG,  
COD A



TE Part #1-2395006-1  
12POS,TAB0.5X0.4,HDR ASSY,  
180DEG,COD A

## Documents

### Product Drawings

[V23700F0002A408-EV-CBOX](#)

English

### CAD Files

[3D PDF](#)

3D

Customer View Model

[ENG\\_CVM\\_CVM\\_2-1904058-7\\_A.2d\\_dxf.zip](#)

English

Customer View Model

[ENG\\_CVM\\_CVM\\_2-1904058-7\\_A.3d\\_igs.zip](#)

English

Customer View Model

[ENG\\_CVM\\_CVM\\_2-1904058-7\\_A.3d\\_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

## Datasheets & Catalog Pages



### [Automotive Relay Application Notes](#)

English

### [High Voltage Relays & Contactors, High Voltage Relay, Mini K HV Precharge Relay](#)

English

---

### [Product Specifications](#)

#### [Definitions General Purpose Relays](#)

English