

# Product data sheet

Specifications

SQUARE D



## Overload Relay, Motor Logic, solid state, isolated alarm contacts

9999AC04

Product availability: Stock - Normally stocked in distribution facility

### Main

Range of Product	Accessory
Product destination	Overload relay
Thermal overload type	Solid state

### Complementary

Product or Component Type	Auxiliary contact
Contacts type and composition	1 NO
[Ue] rated operational voltage	600 V AC

### Ordering and shipping details

Category	US10CP121761
Discount Schedule	0CP1
GTIN	785901070719
Returnability	Yes
Country of origin	MX

### Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	1.30 in (3.302 cm)
Package 1 Width	2.30 in (5.842 cm)
Package 1 Length	3.10 in (7.874 cm)
Package weight(Lbs)	0.800 oz (22.680 g)

### Contractual warranty

Warranty	18 months
----------	-----------

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Use Better

 <b>Materials and Substances</b>	
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Under investigation

### Use Again

 <b>Repack and remanufacture</b>	
Circularity Profile	No need of specific recycling operations
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.