



## IR Receiver Modules for Remote Control Systems



### DESCRIPTION

This IR receiver series is optimized for long burst remote control systems in different environments. The customer can choose between different IC settings (AGC variants), to find the optimum solution for his application. The higher the AGC, the better noise is suppressed, but the lower the code compatibility.

The devices contain a PIN diode and a preamplifier assembled on a lead frame. The epoxy package contains an IR filter. The demodulated output signal can be directly connected to a microprocessor for decoding. These components have not been qualified to automotive specifications.

### LINKS TO ADDITIONAL RESOURCES



Product Page



Marking



Packages



Holders



Bends and Cuts

### FEATURES

- Individual IC settings to reach maximum performance
- Immunity against noise (lamps, LCD TV, Wi-Fi)
- Low supply current
- Photo detector and preamplifier in one package
- Supply voltage: 2.0 V to 5.5 V
- Material categorization:  
for definitions of compliance please see [www.vishay.com/doc?99912](http://www.vishay.com/doc?99912)



**RoHS**  
COMPLIANT  
HALOGEN  
**FREE**  
**GREEN**  
(5-2008)


### APPLICATIONS

- Infrared remote control systems

### DESIGN SUPPORT TOOLS

- [3D models](#)
- [Window size calculator](#)

### BLOCK DIAGRAM



16833-22


## MECHANICAL DATA

### Pinning for TSOP44..., TSOP48...:

1 = OUT, 2 = GND, 3 =  $V_S$

### Pinning for TSOP22..., TSOP24...:

1 = OUT, 2 =  $V_S$ , 3 = GND




23198

## ORDERING CODE

TSOP2..., TSOP4... - 2160 pieces in tubes

## APPLICATION CIRCUIT



$R_1$  and  $C_1$  recommended in case there are strong ripple or spikes on the supply line.

## PARTS TABLE

| AGC               |        | LEGACY, FOR<br>LONG BURST REMOTE CONTROLS (AGC2)                                                                                                                                                                                                     |                              | RECOMMENDED FOR<br>LONG BURST CODES (AGC4) |                              |
|-------------------|--------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------|--------------------------------------------|------------------------------|
| Carrier frequency | 30 kHz | TSOP4830                                                                                                                                                                                                                                             | TSOP2230                     | TSOP4430                                   | TSOP2430                     |
|                   | 33 kHz | TSOP4833                                                                                                                                                                                                                                             | TSOP2233                     | TSOP4433                                   | TSOP2433                     |
|                   | 36 kHz | TSOP4836                                                                                                                                                                                                                                             | TSOP2236                     | TSOP4436 (1)(2)(3)                         | TSOP2436 (1)(2)(3)           |
|                   | 38 kHz | TSOP4838                                                                                                                                                                                                                                             | TSOP2238                     | TSOP4438 (4)(5)(6)(9)(10)                  | TSOP2438 (4)(5)(6)(9)(10)    |
|                   | 40 kHz | TSOP4840 (8)                                                                                                                                                                                                                                         | TSOP2240 (8)                 | TSOP4440                                   | TSOP2440                     |
|                   | 56 kHz | TSOP4856 (11)                                                                                                                                                                                                                                        | TSOP2256 (11)                | TSOP4456 (6)(7)                            | TSOP2456 (6)(7)              |
| Package           |        | Mold                                                                                                                                                                                                                                                 |                              |                                            |                              |
| Pinning           |        | 1 = OUT, 2 = GND, 3 = $V_S$                                                                                                                                                                                                                          | 1 = OUT, 2 = $V_S$ , 3 = GND | 1 = OUT, 2 = GND, 3 = $V_S$                | 1 = OUT, 2 = $V_S$ , 3 = GND |
| Dimensions (mm)   |        | 6.0 W x 6.95 H x 5.6 D                                                                                                                                                                                                                               |                              |                                            |                              |
| Mounting          |        | Leaded                                                                                                                                                                                                                                               |                              |                                            |                              |
| Application       |        | Remote control                                                                                                                                                                                                                                       |                              |                                            |                              |
| Best choice for   |        | (1) RC-5 (2) RC-6 (3) Panasonic (4) NEC (5) Sharp (6) r-step (7) Thomson RCA<br>(8) Sony (9) Mitsubishi (10) Sejin 4PPM (11) Cisco                                                                                                                   |                              |                                            |                              |
| Special options   |        | <ul style="list-style-type: none"> <li>Narrow optical filter: <a href="http://www.vishay.com/doc?81590">www.vishay.com/doc?81590</a></li> <li>Wide optical filter: <a href="http://www.vishay.com/doc?82726">www.vishay.com/doc?82726</a></li> </ul> |                              |                                            |                              |

## ABSOLUTE MAXIMUM RATINGS

| PARAMETER                   | TEST CONDITION                | SYMBOL      | VALUE                   | UNIT |
|-----------------------------|-------------------------------|-------------|-------------------------|------|
| Supply voltage              |                               | $V_S$       | -0.3 to +6              | V    |
| Supply current              |                               | $I_S$       | 5                       | mA   |
| Output voltage              |                               | $V_O$       | -0.3 to 5.5             | V    |
| Voltage at output to supply |                               | $V_S - V_O$ | -0.3 to ( $V_S + 0.3$ ) | V    |
| Output current              |                               | $I_O$       | 5                       | mA   |
| Junction temperature        |                               | $T_j$       | 100                     | °C   |
| Storage temperature range   |                               | $T_{stg}$   | -25 to +85              | °C   |
| Operating temperature range |                               | $T_{amb}$   | -25 to +85              | °C   |
| Power consumption           | $T_{amb} \leq 85$ °C          | $P_{tot}$   | 10                      | mW   |
| Soldering temperature       | $t \leq 10$ s, 1 mm from case | $T_{sd}$    | 260                     | °C   |

### Note

- Stresses beyond those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. This is a stress rating only and functional operation of the device at these or any other conditions beyond those indicated in the operational sections of this specification is not implied. Exposure to absolute maximum rating conditions for extended periods may affect the device reliability

| <b>ELECTRICAL AND OPTICAL CHARACTERISTICS</b> ( $T_{amb} = 25\text{ }^{\circ}\text{C}$ , unless otherwise specified) |                                                                                |                   |      |          |      |                 |
|----------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------|-------------------|------|----------|------|-----------------|
| PARAMETER                                                                                                            | TEST CONDITION                                                                 | SYMBOL            | MIN. | TYP.     | MAX. | UNIT            |
| Supply current                                                                                                       | $E_v = 0, V_s = 3.3\text{ V}$                                                  | $I_{SD}$          | 0.25 | 0.35     | 0.45 | mA              |
|                                                                                                                      | $E_v = 40\text{ klx, sunlight}$                                                | $I_{SH}$          | -    | 0.45     | -    | mA              |
| Supply voltage                                                                                                       |                                                                                | $V_s$             | 2.0  | -        | 5.5  | V               |
| Transmission distance                                                                                                | $E_v = 0$ , test signal see Fig. 1, IR diode TSAL6200, $I_F = 50\text{ mA}$    | $d$               | -    | 24       | -    | m               |
| Output voltage low                                                                                                   | $I_{OSL} = 0.5\text{ mA}$ , $E_e = 0.7\text{ mW/m}^2$ , test signal see Fig. 1 | $V_{OSL}$         | -    | -        | 100  | mV              |
| Minimum irradiance                                                                                                   | Test signal: RC5 code                                                          | $E_e\text{ min.}$ | -    | 0.12     | 0.25 | $\text{mW/m}^2$ |
|                                                                                                                      | Test signal: NEC code                                                          | $E_e\text{ min.}$ | -    | 0.16     | 0.35 | $\text{mW/m}^2$ |
| Maximum irradiance                                                                                                   | $t_{pi} - 4/f_0 < t_{po} < t_{pi} + 4/f_0$ , test signal see Fig. 1            | $E_e\text{ max.}$ | 30   | -        | -    | $\text{W/m}^2$  |
| Directivity                                                                                                          | Angle of half transmission distance                                            | $\phi_{1/2}$      | -    | $\pm 45$ | -    | deg             |


**TYPICAL CHARACTERISTICS** ( $T_{amb} = 25\text{ }^{\circ}\text{C}$ , unless otherwise specified)


Fig. 1 - Output Active Low




Fig. 3 - Output Function




Fig. 2 - Pulse Length and Sensitivity in Dark Ambient




Fig. 4 - Output Pulse Diagram




Fig. 5 - Frequency Dependence of Responsivity




Fig. 8 - Max. Envelope Duty Cycle vs. Burst Length




Fig. 6 - Sensitivity in Bright Ambient




Fig. 9 - Sensitivity vs. Ambient Temperature




Fig. 7 - Sensitivity vs. Supply Voltage Disturbances




Fig. 10 - Relative Spectral Sensitivity vs. Wavelength




Fig. 11 - Horizontal Directivity




Fig. 12 - Sensitivity vs. Supply Voltage

**SUITABLE DATA FORMAT**

This series is designed to suppress spurious output pulses due to noise or disturbance signals. The devices can distinguish data signals from noise due to differences in frequency, burst length, and envelope duty cycle. The data signal should be close to the device's band-pass center frequency (e.g. 38 kHz) and fulfill the conditions in the table below.

When a data signal is applied to the product in the presence of a disturbance, the sensitivity of the receiver is automatically reduced by the AGC to insure that no spurious pulses are present at the receiver's output. Some examples which are suppressed are:

- DC light (e.g. from tungsten bulbs sunlight)
- Continuous signals at any frequency
- Strongly or weakly modulated patterns from fluorescent lamps with electronic ballasts (see Fig. 13 or Fig. 14).
- 2.4 GHz and 5 GHz Wi-Fi




Fig. 13 - IR Disturbance from Fluorescent Lamp With Low Modulation




Fig. 14 - IR Disturbance from Fluorescent Lamp With High Modulation


|                                                                               | <b>TSOP22..., TSOP48..</b>                                                          | <b>TSOP24..., TSOP44..</b>                                                                                                |
|-------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------|
| Minimum burst length                                                          | 10 cycles/burst                                                                     | 10 cycles/burst                                                                                                           |
| After each burst of length<br>a minimum gap time is required of               | 10 to 72 cycles<br>≥ 10 cycles                                                      | 10 to 40 cycles<br>≥ 10 cycles                                                                                            |
| For bursts greater than<br>a minimum gap time in the data stream is needed of | 72 cycles<br>> 3 x burst length                                                     | 40 cycles<br>> 10 x burst length                                                                                          |
| Maximum number of continuous short bursts/second                              | 950                                                                                 | 1500                                                                                                                      |
| NEC code                                                                      | Yes                                                                                 | Preferred                                                                                                                 |
| RC5/RC6 code                                                                  | Yes                                                                                 | Preferred                                                                                                                 |
| Thomson RCA 56 kHz code                                                       | Yes                                                                                 | Preferred                                                                                                                 |
| Sharp code                                                                    | Yes                                                                                 | Preferred                                                                                                                 |
| Sony code                                                                     | Preferred                                                                           | No                                                                                                                        |
| r-step code                                                                   | Yes                                                                                 | Preferred                                                                                                                 |
| Suppression of interference from fluorescent lamps                            | Mild disturbance patterns<br>are suppressed (example:<br>signal pattern of Fig. 13) | Complex and critical disturbance patterns<br>are suppressed (example: signal pattern<br>of Fig. 14 or highly dimmed LCDs) |

**Note**

- For data formats with short bursts please see the datasheet of TSOP23..., TSOP43..



## PACKAGE DIMENSIONS in millimeters



Drawing-No.: 6.550-5169.01-4

Issue: 9; 03.11.10

13655



## Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Hyperlinks included in this datasheet may direct users to third-party websites. These links are provided as a convenience and for informational purposes only. Inclusion of these hyperlinks does not constitute an endorsement or an approval by Vishay of any of the products, services or opinions of the corporation, organization or individual associated with the third-party website. Vishay disclaims any and all liability and bears no responsibility for the accuracy, legality or content of the third-party website or for that of subsequent links.

Vishay products are not designed for use in life-saving or life-sustaining applications or any application in which the failure of the Vishay product could result in personal injury or death unless specifically qualified in writing by Vishay. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.