



Sensors > Force Sensors > Compact Compression Load Cell



Force Sensor Type: OEM Compression Load Cells

Force Direction: Compression

Full Scale Range: 10 lbf

Operating Temperature Range: 0 – 50 °C [32 – 122 °F]

Supply Voltage Range: 5 VDC

[All Compact Compression Load Cell \(46\)](#)

Features

Product Type Features

Force Sensor Type	OEM Compression Load Cells
-------------------	----------------------------

Electrical Characteristics

Full Scale Range	10 lbf
Supply Voltage Range	5 VDC

Usage Conditions

Operating Temperature Range	0 – 50 °C[32 – 122 °F]
Accuracy	±1 % of FS

Operation/Application

Output Signal Type	4V
--------------------	----

Other

Force Direction	Compression
Zero Shift in CTR	±.05 %FS/°C
Sensitivity Shift	±.05 %FS/°C

Product Compliance

[For compliance documentation, visit the product page on TE.com>](#)



EU RoHS Directive 2011/65/EU	Compliant with Exemptions
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2025 (250) Candidate List Declared Against: JAN 2025 (247) Does not contain REACH SVHC
Halogen Content	Not Yet Reviewed for halogen content
Solder Process Capability	Not reviewed for solder process capability


Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulations, TE’s information on SVHC in articles for this part number is still based on the European Chemical Agency (ECHA) ‘Guidance on requirements for substances in articles’(Version: 2, April 2011), applying the 0.1% weight on weight concentration threshold at the finished product level. TE is aware of the European Court of Justice ruling of September 10th, 2015 also known as O5A (Once An Article Always An Article) stating that, in case of ‘complex object’, the threshold for a SVHC must be applied to both the product as a whole and simultaneously to each of the articles forming part of its composition. TE has evaluated this ruling based on the new ECHA “Guidance on requirements for substances in articles” (June 2017, version 4.0) and will be updating its statements accordingly.

Compatible Parts



Also in the Series | MEAS FX29




Force Sensors(46)

Customers Also Bought




TE Part #CONBNC004
BNC Jack 50 Ohm Panel Mount



TE Part #42318-2
SPADE TERMINAL TERMINAL 20-16 AWG TPBR



TE Part #208487-1
CMC RECEPTACLE ASSY,SIZE 22



TE Part #211903-1
CMC DUST CAP ASSM SIZE 22



TE Part #1-794610-1
MICRO MNL RPT CNT,LS PC 15AU L




TE Part #794617-4
4POS,MICRO MNL,RCPT HSG



TE Part #794617-8
8POS,MICRO MNL,RCPT HSG



TE Part #1658527-2
622-0630LF FEM SOCKET,LEAD FREE



TE Part #1-2232892-8
8P MONOPLUG 2.5



TE Part #5205817-3
FEMALE SCREWLOCK KIT

Documents

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_20009605-08_D.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_20009605-08_D.3d_igs.zip



English

Customer View Model

[ENG_CVM_CVM_20009605-08_D.3d_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

[FX29 COMPRESSION LOAD CELL](#)

English