



Connectors > Connector Accessories > Connector Backshells > AMPSEAL Backshells



Connector Backshell Product Type: Potting Shell/Strain Relief

Primary Product Material: PBT GF15

Sealable: No

Operating Temperature Range: -40 – 125 °C [-40 – 257 °F]

[All AMPSEAL Backshells \(4\)](#)

Features

Product Type Features

Connector Backshell Product Type	Potting Shell/Strain Relief
Sealable	No

Body Features

Cable Exit Angle	180°
Primary Product Color	Black
Primary Product Material	PBT GF15

Usage Conditions

Operating Temperature (Max)	105 °C[221 °F]
Operating Temperature Range	-40 – 125 °C[-40 – 257 °F]

Industry Standards

IP Rating	IP69
UL Flammability Rating	UL 94HB

Other

Serviceable	Yes
-------------	-----



Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2025 (250) Candidate List Declared Against: JUNE 2025 (250) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts




TE Part # CAT-AM78-CH8172
AMPSEAL Receptacle Housings



TE Part # 58529-1
PRO-CRIMPER III TOOL AMPSEAL

Also in the Series | AMPSEAL



Automotive Connector Locks & Position Assurance(1)



Automotive Housings(34)



Automotive Seals & Cavity Plugs(2)



Connector Caps & Covers(1)



Other Automotive Connector Accessories(2)

Customers Also Bought



TE Part #456409-2
CRIMPER WIRE .120 F



TE Part #770678-1
SEAL PLUG, AMPSEAL



TE Part #CAT-AM78-CH8172
AMPSEAL Receptacle Housings



TE Part #CAT-AM78-B128
AMPSEAL Backshells



TE Part #2373965-1
CPA,AMPSEAL

Documents

Product Drawings
STRAIN RELIEF,23 POSITION AMPSEAL
English

CAD Files
3D PDF
3D
Customer View Model
ENG_CVM_CVM_2389806-1_A.2d_dxf.zip



English

Customer View Model

[ENG_CVM_CVM_2389806-1_A.3d_igs.zip](#)

English

Customer View Model

[ENG_CVM_CVM_2389806-1_A.3d_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

[AMPSEAL Connector Series](#)

English

Product Specifications

[Application Specification](#)

English