

347874-1 ✓ ACTIVE

Econoseal

TE Internal #: 347874-1

Cable Seal, 1.1 mm [.043 in] Cavity Diameter, -40 – 125 °C [-40 – 257 °F], Green, Silicone Rubber, 1.6 – 2.4 mm [.062 – .094 in] Insulation Diameter

[View on TE.com >](#)



Connectors > Connector Accessories > Connector Seals & Cavity Plugs



Connector Seal & Plug Type: **Cable Seal**

Cavity Diameter: **1.1 mm [.043 in]**

Operating Temperature Range: **-40 – 125 °C [-40 – 257 °F]**

Primary Product Color: **Green**

Primary Product Material: **Silicone Rubber**

Features

Product Type Features

Connector Seal & Plug Type	Cable Seal
----------------------------	------------

Body Features

Primary Product Color	Green
Primary Product Material	Silicone Rubber

Dimensions

Cavity Diameter	1.1 mm[.043 in]
Compatible Insulation Diameter Range	1.6 – 2.4 mm[.062 – .094 in]

Usage Conditions

Operating Temperature Range	-40 – 125 °C[-40 – 257 °F]
Operating Temperature (Max)	125 °C[257 °F]

Packaging Features

Packaging Method	Bag
Packaging Quantity	10000

Other

Resistance to Hydrocarbons	Poor
Shore A Hardness	40
Contains Lubricant	Yes



Product Compliance

[For compliance documentation, visit the product page on TE.com>](#)

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2025 (250) Candidate List Declared Against: JUNE 2025 (250) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>


Compatible Parts




Customers Also Bought




TE Part #344111-1
36W EMS.REC. HSG.ASSY




TE Part #344267-1
6 WAY REC. HSG. SIL. SEALECONO




TE Part #344273-1
3 WAY REC. HSG. SIL. SEALECONO




TE Part #344276-1
2 WAY REC HSG. SIL SEAL ECONO



TE Part #345806-1
ECONO CONTACT REC




TE Part #345808-1
.070" RECEPTACLE ECON.3



TE Part #152455
ALTERNATOR CONN SERVICING
PACK



TE Part #344261-1
13 WAY TAB ANTI-BACKOUT



TE Part #344274-1
2 WAY TAB HOUSING BLACK ECONO



TE Part #345254-1
ANTI-BACKOUT 2WAY REC
HSGECONO

Documents

Product Drawings

CABLE SEAL LC SILICON 0.5 T

English

CAD Files

Customer View Model

[ENG_CVM_347874-1_C.3d_igs.zip](#)

English

Customer View Model

[ENG_CVM_347874-1_C.3d_stp.zip](#)

English

Customer View Model

[ENG_CVM_347874-1_C.2d_dxf.zip](#)

English

3D PDF

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

347874-1

Cable Seal, 1.1 mm [.043 in] Cavity Diameter, -40 – 125 °C [-40 – 257 °F], Green,
Silicone Rubber, 1.6 – 2.4 mm [.062 – .094 in] Insulation Diameter



Product Datasheet

English