

D369-MR33-NS1 ✓ ACTIVE

DEUTSCH | DEUTSCH 369 Shielded Connector

TE Internal #: YD369-MR33-NS10000

3 Position, Receptacle, Connector Assembly, Crimp, Wire-to-Wire, Shielded, Gold (Au), Normal, DEUTSCH 369 Shielded Connector

[View on TE.com >](#)



Connectors > Rectangular Connectors > Standard Rectangular Connectors > Rectangular Connectors: 3-Way Shielded Receptacle



Connector Product Type: **Connector Assembly**

Connector & Housing Type: **Receptacle**

Mating Alignment: **With**

Mating Alignment Type: **Keyed**

Mating Retention: **With**

[All Rectangular Connectors: 3-Way Shielded Receptacle \(2\)](#)

Features

Product Type Features

Connector Seal & Plug Type	Triple-Seal
Connector Shell Size	03
Connector Product Type	Connector Assembly
Connector & Housing Type	Receptacle
Connector System	Wire-to-Wire
Insertion Force Type	Normal
Sealable	Yes
Connector & Contact Terminates To	Wire & Cable

Configuration Features

Number of Columns	3
Number of Cavities	3
Contacts Preloaded	Yes
Number of Positions	3
Number of Rows	1
Number of Power Positions	3
Number of Signal Positions	3

Electrical Characteristics



Operating Voltage	500 VDC
-------------------	---------

Body Features

Connector & Keying Code	N
Connector Seal Color	Natural
Seal Material	Fluorosilicone
Shell Plating Material	Nickel
Seal Type	Grommet Seal, Interfacial Seal
Primary Product Color	Black
Cable Exit Angle	180°

Contact Features

Contact Size	Size 22
Contact Mating Area Plating Material	Gold (Au)
Contact Retention Within Housing	With
Contact Current Rating (Max)	5 A
Contact Type	Socket
Wire Contact Termination Area Plating Material	Gold

Termination Features

Termination Method to Wire & Cable	Crimp
------------------------------------	-------

Mechanical Attachment

Mating Alignment	With
Mating Alignment Type	Keyed
Mating Retention	With
Mating Retention Type	Button Latch

Housing Features

Shell Material	Composite
Centerline (Pitch)	2.54 mm[.1 in]
Housing Material	Composite

Dimensions

Row-to-Row Spacing	2.54 mm[.1 in]
Compatible Insulation Diameter Range	.71 – 1.37 mm[.028 – .054 in]

Usage Conditions

Operating Temperature Range	-55 – 175 °C[-67 – 347 °F]
-----------------------------	----------------------------



Operation/Application

Shielded	Yes
Circuit Application	Power & Signal

Product Compliance

[For compliance documentation, visit the product page on TE.com>](#)

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Not Yet Reviewed
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	<p>Current ECHA Candidate List: JUNE 2025 (250) Candidate List Declared Against: JAN 2025 (247) SVHC > Threshold: Dodecamethylcyclhexasiloxane (D6) (1% in Component Part) Decamethylcyclopentasiloxane (D5) (1% in Component Part) Octamethylcyclotetrasiloxane (D4) (.43% in Component Part)</p> <p>Article Safe Usage Statements: Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.</p>
Halogen Content	Low Halogen - Br, Cl, F < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Reflow solder capable to 245°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts



TE Part # YD369-MP33-NP10000
369 3 WAY SHIELDED PLUG, CRIMP,
PIN

Also in the Series | DEUTSCH 369 Shielded Connector



Rectangular Power Connectors(15)



Standard Rectangular Connectors(15)

Customers Also Bought



TE Part #YCTJ122E01CC015000
ELEC MODULE



TE Part #T4162214002-001
RPC-M12-2MR-0.5SH-M12-2FR-PVC



TE Part #218673-001
22759/41-8-9



TE Part #632785-000
202D142-100/180-0



TE Part #D369-R66-NS1
369 6 WAY REC, CRIMP, SKT



TE Part #EM7499-000
X4-0.8-0-SP-SM



TE Part #1410946-2
MULTI-GIG SOC. CAP SCREW,
CUSTOMIZED HDW



TE Part #5-1437567-0
MPG106F=(MSPG) SWITCH
PUSHBUTT



TE Part #2309413-1
DDR4 SODIMM 260P 9.2H STD



TE Part #ES1250403AT
ES1250403AT=RELAY



Documents

Product Drawings

[369 3 WAY SHIELDED REC, CRIMPT, SKT](#)

English

CAD Files

[3D PDF](#)

3D

Customer View Model

[ENG_CVM_CVM_YD369-MR33-NS10000_AA.2d_dxf.zip](#)

English

Customer View Model

[ENG_CVM_CVM_YD369-MR33-NS10000_AA.3d_igs.zip](#)

English

Customer View Model

[ENG_CVM_CVM_YD369-MR33-NS10000_AA.3d_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.