



Automotive Parts > Automotive Connector Accessories > Automotive Connector Locks & Position Assurance > Wedgelocks: DEUTSCH DT



Number of Positions: 2

Primary Product Color: Gray

Connector & Contact Retention Accessory Type: Secondary Lock

Primary Product Material: PBT

Operating Temperature Range: -55 – 125 °C [-67 – 257 °F]

[All Wedgelocks: DEUTSCH DT \(58\)](#)

Features

Product Type Features

Sealable	No
Connector & Contact Retention Accessory Type	Secondary Lock

Configuration Features

Number of Positions	2
---------------------	---

Body Features

Primary Product Color	Gray
Primary Product Material	PBT

Usage Conditions

Operating Temperature Range	-55 – 125 °C[-67 – 257 °F]
-----------------------------	----------------------------

Industry Standards

UL Flammability Rating	UL 94HB
------------------------	---------

Packaging Features

--	--



Packaging Method	Box
Other	
Serviceable	Yes

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2025 (250) Candidate List Declared Against: JUNE 2025 (250) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts



TE Part # 2441202-1
DT06-2S-TE01, PLG, 2S, GRY, E




TE Part # CAT-J41-DDPC
DEUTSCH DT Plug Connectors



TE Part # CAT-D487-W416
Wedgelocks: DEUTSCH DT



TE Part # CAT-J41-DDCC
DEUTSCH DT Color Connectors



TE Part # DT06-2S-CE02
PLG, 2P, BLK, E




TE Part # CAT-J41-DDSCC
DEUTSCH DT Connectors with snap cap



TE Part # DT-RT1
EXT TOOL, FRONT RELEASE

Also in the Series | **DEUTSCH DT**



Automotive Housings(767)



Connector Caps & Covers(1)



Connector Strain Relief(35)



Infotainment & Multimedia Cable Assemblies(1)



Rectangular Backshells & Clamps(3)

Customers Also Bought



TE Part #CAT-D487-W416
Wedgelocks: DEUTSCH DT



TE Part #DT06-2S-CE01
PLG, 2P, GRY, E, CAP



TE Part #NB07516001
HTAT-16/4-0-55MM

Documents

- Product Drawings

WEDGE LOCK, 2P, PLG, GRY, STD, DT, A

English
- CAD Files

3D PDF

3D

Customer View Model

[ENG_CVM_CVM_W2SA_99_c-w2sa-99.2d_dxf.zip](#)

English

Customer View Model

[ENG_CVM_CVM_W2SA_99_c-w2sa-99.3d_igs.zip](#)

English

Customer View Model

[ENG_CVM_CVM_W2SA_99_c-w2sa-99.3d_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

TERMINALS AND CONNECTORS

English

CONNECTOR SELECTOR

English

Product Specifications

Application Specification

English

Agency Approvals

UL Report

English