

# SAC-5P-MINT/2XMIN DN US - T distributor



1351107

<https://www.phoenixcontact.com/us/products/1351107>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

T-distributor, 5-pos., 7/8"-16UNF socket to 7/8"-16UNF socket and 7/8"-16UNF plug



## Commercial data

Item number	1351107
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	BF37
Product key	AF2ICC
GTIN	4063151670382
Weight per piece (including packing)	80 g
Weight per piece (excluding packing)	22.22 g
Country of origin	CN

## Technical data

### Notes

#### Trade restriction

CE note	The products are offered exclusively for export outside the EU and the European Economic Area.
---------	--

### Product properties

Product type	T-distributor
Sensor type	DeviceNet™
Number of positions	5
No. of cable outlets	2
Shielded	no
Thread type	7/8"

### Electrical properties

Nominal voltage $U_N$	300 V
Nominal current $I_N$	8 A (at 25 °C)

### Interfaces

Bus system	DeviceNet™
Signal type/category	DeviceNet™

### Signaling

Status display	no
Status display present	no

### Material specifications

Flammability rating according to UL 94	HB
Material of grip body	PVC
Contact material	Copper alloy
Contact surface material	Ni/Au
Contact carrier material	PVC
Material for screw connection	Aluminum

### Connector

#### Connection 1

Type	Plug straight 7/8"-16UNF
------	--------------------------

#### Connection 2

Type	Socket straight 7/8"-16UNF
------	----------------------------

#### Connection 3

Type	Socket straight 7/8"-16UNF
------	----------------------------

# SAC-5P-MINT/2XMIN DN US - T distributor



1351107

<https://www.phoenixcontact.com/us/products/1351107>

## Cable/line

Signal type/category	DeviceNet™
----------------------	------------

## Mechanical properties

### Mechanical data

Insertion/withdrawal cycles	max. 500
-----------------------------	----------

## Environmental and real-life conditions

### Ambient conditions

Degree of protection	IP67
	IP67
Enclosure rating (NEMA)	6P (NEMA)
Ambient temperature (operation)	-20 °C ... 70 °C (Plug / socket)

# SAC-5P-MINT/2XMIN DN US - T distributor




1351107

<https://www.phoenixcontact.com/us/products/1351107>

## Drawings

Dimensional drawing



T-distributor 7/8"


# SAC-5P-MINT/2XMIN DN US - T distributor



1351107


<https://www.phoenixcontact.com/us/products/1351107>

Schematic diagram



Pin assignment, plug, 7/8"-16UNF, 5-pos., view of male side

Schematic diagram




Pin assignment, socket, 7/8"-16UNF, 5-pos., view of female side

# SAC-5P-MINT/2XMIN DN US - T distributor



1351107

<https://www.phoenixcontact.com/us/products/1351107>



Contact assignment of the 7/8" T-distributor

# SAC-5P-MINT/2XMIN DN US - T distributor



1351107

<https://www.phoenixcontact.com/us/products/1351107>

## Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1351107>

 <b>UL Listed</b> Approval ID: E221474				
	Nominal voltage $U_N$	Nominal current $I_N$	Cross section AWG	Cross section $\text{mm}^2$
keine				
	300 V	8 A	-	-

 <b>cUL Listed</b> Approval ID: E221474				
	Nominal voltage $U_N$	Nominal current $I_N$	Cross section AWG	Cross section $\text{mm}^2$
keine				
	300 V	8 A	-	-

# SAC-5P-MINT/2XMIN DN US - T distributor



1351107

<https://www.phoenixcontact.com/us/products/1351107>

## Classifications

### ECLASS

ECLASS-13.0	27440106
ECLASS-15.0	27440106

### ETIM

ETIM 9.0	EC002925
----------	----------

1351107

<https://www.phoenixcontact.com/us/products/1351107>

## Environmental product compliance

### EU RoHS

Fulfills EU RoHS substance requirements	Yes, No exemptions
---	--------------------

### China RoHS

Environment friendly use period (EFUP)	EFUP-50
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.

### EU REACH SVHC

REACH candidate substance (CAS No.)	No substance above 0.1 wt%
-------------------------------------	----------------------------

# SAC-5P-MINT/2XMIN DN US - T distributor



1351107

<https://www.phoenixcontact.com/us/products/1351107>

## Accessories

### PROT-MINMS-PA-CHAIN - Screw plug

1430925

<https://www.phoenixcontact.com/us/products/1430925>

7/8" sealing cap made of plastic with fixing band, for sensor cables, for 7/8" sockets



---

### PROT-MINFS-PA-CHAIN - Sealing cap

1430912

<https://www.phoenixcontact.com/us/products/1430912>

7/8" sealing cap made of plastic with fixing band, for sensor cables, for 7/8" connectors



# SAC-5P-MINT/2XMIN DN US - T distributor



1351107

<https://www.phoenixcontact.com/us/products/1351107>

## TSD-M 1,2NM - Torque screwdriver

1212224

<https://www.phoenixcontact.com/us/products/1212224>



Torque screw driver, accuracy as per EN ISO 6789 standard, adjustable from 0.3 - 1.2 Nm

---

## TSD-M SAC-BIT ADAPTER - Adapter insert

1212600

<https://www.phoenixcontact.com/us/products/1212600>



Adapter bit for TSD-M...torque tools, E6.3-1/4" drive with 4 mm hexagon to accommodate SAC bits

# SAC-5P-MINT/2XMIN DN US - T distributor



1351107

<https://www.phoenixcontact.com/us/products/1351107>

## SAC BIT MIN-D25 - Tool

1212512

<https://www.phoenixcontact.com/us/products/1212512>

Nut for assembling 7/8" connectors with a knurl diameter of 25 mm, with 4 mm hexagonal drive



---

Phoenix Contact 2025 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)