



Connectors > Lighting Connectors > Street Lighting Controls > Street Lighting Power Management



Lighting Connector Features Included: **Energy Metering Header, Keyed, Not Vented, Zero Cross Tuning**

Fail Mode: **Off**

Operating Frequency Range: **50 Hz**

Compatible With Agency/Standards Products: **CSA, UL**

Number of Positions: **7**

Features

Product Type Features

Lighting Product Type	Connector
Sealable	Yes

Configuration Features

Lighting Connector Features Included	Energy Metering Header, Keyed, Not Vented, Zero Cross Tuning
Number of Positions	7

Electrical Characteristics

Output Voltage (Max)	3.3 V, 5 V, 24 V
Surge Protection	3 kA
Fail Mode	Off

Body Features

Primary Product Color	Black
-----------------------	-------

Contact Features

Contact Mating Area Plating Material	Tin (Sn)
Contact Current Rating (Max)	10 A

Dimensions

Product Diameter	3.19 mm, 81.15 mm[81 in]
------------------	--------------------------



Product Height	70.08 mm
----------------	----------

Usage Conditions

UV Exposure Rated	Yes
Storage Temperature Range	-40 – 105 °C[-40 – 221 °F]
Operating Temperature Range	-40 – 85 °C[-40 – 185 °F]

Operation/Application

Operating Frequency Range	50 Hz
---------------------------	-------

Industry Standards

IP Rating	IP66
UL Flammability Rating	UL 94V-0
Compatible With Approved Standards Products	UL 773
Compatible With Agency/Standards Products	CSA, UL

Product Compliance

[For compliance documentation, visit the product page on TE.com>](#)

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant with Exemptions
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2025 (250) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>



Compatible Parts



TE Part # 2318043-2
CABLE ASSEMBLY, EB, 3 POS MINICT



TE Part # CAT-Z23-DRE
LUMAWISE Endurance N Poke-In:
Streetlight Dimming Receptacles



TE Part # 2-2213362-4
RCPT ASSY, DIMMABLE
PHOTOCONTROL, 105C, 3/4



TE Part # 2318043-1
CABLE ASSEMBLY, EB, 7 POS MINICT

Also in the Series | LUMAWISE Endurance N



Street Lighting Accessories(18)



Street Lighting Base Assemblies(31)



Street Lighting Open & Shorting Caps
(3)



Street Lighting Power Management(6)



Street Lighting Receptacles(24)

Customers Also Bought



TE Part # 2318043-2
CABLE ASSEMBLY, EB, 3 POS MINICT

Documents

Product Drawings

LUMAWISE N ENHANCED BASE, FM OFF, ZC YES

English



CAD Files

Customer View Model

[ENG_CVM_CVM_1-2314786-2_A.3d_igs.zip](#)

English

Customer View Model

[ENG_CVM_CVM_1-2314786-2_A.3d_stp.zip](#)

English

Customer View Model

[ENG_CVM_CVM_1-2314786-2_A.2d_dxf.zip](#)

English

3D PDF

3D

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

[LUMAWISE STREET LIGHT DIMMING AND CONTROL QUICK REFERENCE GUIDE](#)

English

[LUMAWISE Endurance N Enhanced Base](#)

English

Product Specifications

[Application Specification](#)

English