

2343405-1 ✓ ACTIVE

LUMAWISE | LUMAWISE Endurance S

TE Internal #: 2343405-1

Light Controller Base, Gray, 16.5 mm Height, Keyed / Not Vented,
UL, 4 Position, Sealable, Printed Circuit Board, Power, LUMAWISE
Endurance S

[View on TE.com >](#)



Connectors > Lighting Connectors > Street Lighting Controls > Street Lighting Connectors



Lighting Product Type: **Light Controller Base**

Primary Product Color: **Gray**

Product Height: **16.5 mm**

Lighting Connector Features Included: **Keyed, Not Vented**

Compatible With Agency/Standards Products: **UL**

Features

Product Type Features

Lighting Product Type	Light Controller Base
Sealable	Yes
Connector & Contact Terminates To	Printed Circuit Board

Configuration Features

Lighting Connector Features Included	Keyed, Not Vented
Number of Positions	4

Body Features

Primary Product Color	Gray
-----------------------	------

Contact Features

Contact Current Rating (Max)	5 A
------------------------------	-----

Dimensions

Product Diameter	43.5 mm
Product Height	16.5 mm



Usage Conditions

Operating Temperature Range	-40 – 90 °C[-40 – 194 °F]
-----------------------------	---------------------------

Operation/Application

Circuit Application	Power
---------------------	-------

Industry Standards

Compatible With Agency/Standards Products	UL
---	----

Product Compliance

[For compliance documentation, visit the product page on TE.com>](#)

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2025 (250) Candidate List Declared Against: JUNE 2022 (224) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Reflow solder capable to 245°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts




TE Part # 2363638-2
Recept, LUMAWISE Endurance S2 Kit, KeyA



TE Part # 2343403-1
RECEPTACLE, LUMAWISE ENDURANCE S, KEYED



TE Part # 2-2343403-1
RECEPTACLE, LUMAWISE ENDURANCE S, KEYED



TE Part # 2505632-3
LITE BRACKET ASM, LUMAWISE END. S. KEYED



TE Part # 1-2343403-1
RECEPT ASSY, LUMAWISE ENDURO S, KEYED



TE Part # 1-2329013-1
LUMAWISE 40MM DIA DOME CLEAR LOW



TE Part # 2505632-4
LITE BRKT ASM BASIC, LUMA END. S, KEYED



TE Part # 2363638-6
Recept, LUMAWISE Endurance S2,Key A



TE Part # 1-2363638-6
Rcpt, LUMAWISE Endurance S2,Key A, Dots




TE Part # 1-2329013-2
LUMAWISE 40MM DIA DOME CLEAR TALL



TE Part # 2329013-1
LUMAWISE 40MM DIA DOME SMOKE GRAY LOW



TE Part # 1-2363638-2
Rcpt,LUMAWISE Endurance S2 Kit, KeyA,Dots



TE Part # 2329013-2
LUMAWISE 40MM DIA DOME SMOKE GRAY TALL

Also in the Series | **LUMAWISE Endurance S**



Poke-In Connectors(1)



Street Lighting Connectors(47)



Street Lighting Power Management(5)

Customers Also Bought



Documents

Product Drawings

[MODULE,40MM LUMAWISE ENDURANCE S. KEYED](#)

English

CAD Files

[3D PDF](#)

3D

Customer View Model

[ENG_CVM_CVM_2343405-1_A.2d_dxf.zip](#)

English

Customer View Model

[ENG_CVM_CVM_2343405-1_A.3d_igs.zip](#)

English

Customer View Model

[ENG_CVM_CVM_2343405-1_A.3d_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages



LUMAWISE STREET LIGHT DIMMING AND CONTROL QUICK REFERENCE GUIDE

English

[Datasheet - Lumawise Z10](#)

English

[Lumawise Endurance S Modules](#)

English

[Product Specifications](#)

[Application Specification](#)

English

[Agency Approvals](#)

[CB_CERT_IEC_61984_US_34131_M1_UL_C1](#)

English

[CB_CERT_US_34131_M1_UL_4788988643_TR_C1](#)

English