


[View Product Page](#)

- ⬡ Non-terminated Jam Nut Bulkhead Connector for 4 Multimode patch leads
- ⬡ Designed to MIL-DTL83526D
- ⬡ Compatible with any connector that follows MIL-DTL83526D
- ⬡ Compatible with OM1 & OM3
- ⬡ Dust Cap, Lanyard, and Ferrules (termini) for the Cable Included

- Mates with Plug Connectors (hermaphroditic)
- Operating Temperature -50°C to +80°C
- Available in 2 Channel
- Cable Assembly Available

Product Display Title:	4 Channel Jam Nut Bulkhead Connector
Product Family:	Circular Fiber Connectors
Product Series:	5000 Series Expanded Beam
Max Insertion Loss:	<2dB
Avg Insertion Loss:	<1.5dB
Body Colour:	Dark Grey
Body Material:	Polycarbonate/Polybutylene Terephthalate (PC/PBT)
Body Material Type:	Plastic Body
Contact Type:	Expanded Beam
Coupling Nut Retention Force:	1Nm
Coupling Type:	Screw
Diameter Over Coupling Ring Mm:	30mm
Fibre Mode:	MM
Flamability Rating:	UL94V-0
Function:	EB Jam Nut Bulkhead Connector
Ip Rating:	IP68
Material Finish:	Matt
Max Operating Temperature:	+80°C
Min Operating Temperature:	-50°C
Max Panel Thickness:	4.7mm
Rohs Compliant:	Yes

 5000 Series Expanded Beam Product...

 PXEB5410MM3D CAD Model