



Positive Lock 197

TE Internal #: 142685-3

Quick Disconnect Receptacle, Uninsulated, 20 – 17 AWG, .51 – 1.03 mm<sup>2</sup> Wire, 5.08 mm [.2 in] Tab Width, F-Crimp, Straight, Positive Lock 197

[View on TE.com >](#)

Terminals & Splices > Quick Disconnects



Quick Disconnect Terminal Type: **Receptacle**

Wire Size: **.51 – 1.03 mm<sup>2</sup>**

Mating Tab Width: **5.08 mm [.2 in]**

Mating Tab Thickness: **.81 mm [.032 in]**

**Features**

**Product Type Features**

Insertion Force	Low
-----------------	-----

**Configuration Features**

Compatible With Wire & Cable Type	FLK
Connection Capacity	Single

**Contact Features**

Quick Disconnect Terminal Type	Receptacle
Mating Tab Width	5.08 mm [.2 in]
Mating Tab Thickness	.81 mm [.032 in]
Terminal Orientation	Straight
Contact Base Material	Phosphor Bronze
Terminal Plating Material	Pre-Tin
Crimp Type	F-Crimp
Barrel Type	Open

**Termination Features**

--	--



Product Terminates To	Wire & Cable
-----------------------	--------------

### Mechanical Attachment

Wire Insulation Support	With
-------------------------	------

### Dimensions

Product Length	21 mm [.826 in]
Compatible Insulation Diameter Range	1.3 – 2 mm [.051 – .078 in]
Terminal Material Thickness	.41 mm [.016 in]
Wire Size	.51 – 1.03 mm <sup>2</sup>

### Usage Conditions

Insulation Option	Uninsulated
Operating Temperature Range	-40 – 110 °C [-40 – 230 °F]

### Industry Standards

Compatible With Agency/Standards Products	UL
---	----

### Packaging Features

Packaging Quantity	4000
Packaging Method	Strip/Reel

### Product Compliance

[For compliance documentation, visit the product page on TE.com>](#)

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2025 (250) Candidate List Declared Against: JUNE 2025 (250) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability


#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these




limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

## Compatible Parts



TE Part # 142680-4  
PL MK III 2 POS HOUSING YELLOW  
RAL 1016



**KIT**  
TE Part # 7-2150376-7  
OCEAN\_2.0\_SPARE\_PART\_KIT-  
090F118F



TE Part # 142680-1  
PL MK III 2 POS HOUSING BROEN  
RAL 8016




TE Part # 142681-1  
PL MK III 3 POS HOUSING BROEN  
RAL 8016



TE Part # 2150376-2  
OCEAN-2.0-APPLICATOR-E-  
090F118FA-REA

## Also in the Series | Positive Lock 197



Crimp Terminal Housings(5)



Quick Disconnects(2)

## Customers Also Bought



## Documents

### Product Drawings

[L.I.F PL CONTACT 5MM 0.35-1 MM2 PTPPHBZ](#)

English

### CAD Files

[3D PDF](#)

3D

Customer View Model

[ENG\\_CVM\\_CVM\\_142685-3\\_W.2d\\_dxf.zip](#)

English

Customer View Model

[ENG\\_CVM\\_CVM\\_142685-3\\_W.3d\\_igs.zip](#)

English

Customer View Model

[ENG\\_CVM\\_CVM\\_142685-3\\_W.3d\\_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

### Product Specifications



## Application Specification

French