



Terminals & Splices > Quick Disconnects



Quick Disconnect Terminal Type: **Receptacle**

Wire Size: .51 – 1.65 mm²

Mating Tab Width: 6.35 mm [.25 in]

Mating Tab Thickness: .81 mm [.032 in]

Features

Product Type Features

Insertion Force	Normal
-----------------	--------

Configuration Features

Compatible With Wire & Cable Type	Discrete Wire
Connection Capacity	Single

Contact Features

Quick Disconnect Terminal Type	Receptacle
Mating Tab Width	6.35 mm [.25 in]
Mating Tab Thickness	.81 mm [.032 in]
Terminal Orientation	Straight
Contact Base Material	Brass
Terminal Plating Material	Unplated
Crimp Type	F-Crimp
Barrel Type	Open

Termination Features

--	--



Product Terminates To	Wire & Cable
-----------------------	--------------

Mechanical Attachment

Wire Insulation Support	With
-------------------------	------

Mating Retention Type	Dimple
-----------------------	--------

Extraction Force	8.1 kgf
------------------	---------

Dimensions

Product Length	19.2 mm [.755 in]
----------------	-------------------

Compatible Insulation Diameter Range	2.3 – 3.3 mm [.09 – .13 in]
--------------------------------------	-----------------------------

Terminal Material Thickness	.41 mm [.016 in]
-----------------------------	------------------

Wire Size	.51 – 1.65 mm ²
-----------	----------------------------

Usage Conditions

Insulation Option	Uninsulated
-------------------	-------------

Operating Temperature Range	-40 – 110 °C [-40 – 230 °F]
-----------------------------	-----------------------------

Industry Standards

Compatible With Agency/Standards Products	CSA, UL
---	---------

Packaging Features

Packaging Quantity	6000
--------------------	------

Packaging Method	Strip/Reel
------------------	------------

Other

Line	Premier
------	---------

Product Compliance

[For compliance documentation, visit the product page on TE.com>](#)

EU RoHS Directive 2011/65/EU	Compliant
------------------------------	-----------

EU ELV Directive 2000/53/EC	Compliant
-----------------------------	-----------

China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
---	---

EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2025 (250) Candidate List Declared Against: JUNE 2025 (250) Does not contain REACH SVHC
--	---

Halogen Content	Low Halogen - Br, Cl, F < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
-----------------	--

Solder Process Capability

Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts




TE Part # 2150082-2
OCEAN_2.0_APPLICATOR-E-090F130F-REA



TE Part # 2150082-1
OCEAN_2.0_APPLICATOR-E-090F130F-REM



TE Part # 735209-1
250 FASTON REC 22-18 AWG BR




TE Part # 7-2150082-7
OCEAN_2.0_SPARE_PART_KIT-090F130F



TE Part # 737439-1
250 FASTON REC 22-18 AWG BR



TE Part # 180388-2
250 FASTON,REC.,20-16 AWG,TPBR



TE Part # 42239-4
205 FASTON REC 18-14 AWG PHBZ



TE Part # 63648-1
250 FASTON FLAG REC 20-14 AWG BR



TE Part # 737439-3
250 FASTON REC 22-18 AWG TPBR



TE Part # 190735-7
250 FASTON,FLAG,REC.,20-16 AWG,PTBR



TE Part # 180388-5
250 FASTON,REC.,20-16 AWG,TPPB

Also in the Series | **FASTON 250**



Compression Connectors(4)



Crimp Terminal Housings(115)



Insulation Boots & Sleeves(16)



Magnet Wire Terminals(1)



PCB Terminals(133)



Quick Disconnects(418)



Splices(4)

Customers Also Bought



TE Part #170823-6
250 FASTON SLEEVE,REC.,
TRANSPARENT



TE Part #177907-1
POWER DBL LOCK CAP P/M 3P



TE Part #177916-1
AMP POWER DBL LOCK TAB (S)



TE Part #2-321889-3
SOLIS R HT 22-16COMM22-18MIL6



TE Part #964204-1
STD-POW-TIM KONTAKT



TE Part #1534594-3
MCON 1.2 CB REC SRC AG




TE Part #1-1718806-1
5POS, MCON 1.2 LL REC SEALED



TE Part #1744416-8
8 POS EP II HSG, GLOW WIRE



TE Part #2293255-1
FASTON 187 REC 0.5-1.5MM2 TPBR



TE Part #721420-2
BUTTON-CRIMP SPACER

Documents



Product Drawings

[250 FASTON,REC.,20-16 AWG,BR](#)

English

CAD Files

[3D PDF](#)

3D

Customer View Model

[ENG_CVM_CVM_160807-2_A.2d_dxf.zip](#)

English

Customer View Model

[ENG_CVM_CVM_160807-2_A.3d_igs.zip](#)

English

Customer View Model

[ENG_CVM_CVM_160807-2_A.3d_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Product Specifications

[Application Specification](#)

English