

173722-1 ✓ ACTIVE

[Positive Lock](#) | [Positive Lock 187](#)


TE Internal #: 173722-1

Quick Disconnect Receptacle, Uninsulated, 26 – 20 AWG, .12 – .41 mm<sup>2</sup> Wire, 4.75 mm [.187 in] Tab Width, F-Crimp, Straight, Brass, Positive Lock 187

[View on TE.com >](#)



Terminals & Splices > Quick Disconnects



Quick Disconnect Terminal Type: **Receptacle**

Wire Size: .12 – .41 mm<sup>2</sup>

Mating Tab Width: 4.75 mm [.187 in]

Mating Tab Thickness: .51 mm [.02 in]

## Features

### Configuration Features

Compatible With Wire & Cable Type	Discrete Wire
Connection Capacity	Single

### Electrical Characteristics

Voltage Rating	250 V
----------------	-------

### Contact Features

Quick Disconnect Terminal Type	Receptacle
Mating Tab Width	4.75 mm [.187 in]
Mating Tab Thickness	.51 mm [.02 in]
Terminal Orientation	Straight
Contact Base Material	Brass
Terminal Plating Material	Pre-Tin
Crimp Type	F-Crimp
Barrel Type	Open

### Termination Features

--	--



Product Terminates To	Wire & Cable
-----------------------	--------------

### Mechanical Attachment

Wire Insulation Support	With
-------------------------	------

### Dimensions

Product Length	17.2 mm [.677 in]
Compatible Insulation Diameter Range	1.3 – 3.6 mm [.051 – .141 in]
Terminal Material Thickness	.3 mm [.012 in]
Wire Size	.12 – .41 mm <sup>2</sup>

### Usage Conditions

Insulation Option	Uninsulated
Operating Temperature Range	-40 – 110 °C [-40 – 230 °F]

### Packaging Features

Packaging Quantity	6000
Packaging Method	Strip/Reel

### Product Compliance

[For compliance documentation, visit the product page on TE.com>](#)

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2025 (250) Candidate List Declared Against: JUNE 2025 (250) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits



as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

### Compatible Parts



TE Part # 2150047-2  
OCEAN\_2.0\_Applicator-E-062F140F-REA




TE Part # 2013799-1  
250 HSG. PL EX REC. BLACK



TE Part # 1743221-1  
250 PL EX FLAG REC. 18-12AWG PTBR



TE Part # 1743058-1  
PL 187 REC 22-16 AWG 0.3 X 22.8 PTBR



**KIT**  
REPRESENTATION ONLY

TE Part # 7-2150047-7  
OCEAN\_2.0\_SPARE\_PART\_KIT-062F140F



TE Part # 2391853-2  
187 sleeve PL BLUE transparent




TE Part # 2391853-1  
187 sleeve PL BLUE transparent



TE Part # 2232342-1  
187 PL EX FLAG REC. 22-16AWG PTBR

### Also in the Series | Positive Lock 187



Crimp Terminal Housings(82)



Insertion & Extraction Tools(2)



Insulation Boots & Sleeves(7)



Quick Disconnects(56)

### Customers Also Bought




TE Part #CAT-HST-VERSAFITV2  
Versafit-V2 Heat Shrink Tubing



TE Part #177902-1  
AMP POWER DBL LOCK PLUG HSG 8P



TE Part #177913-1  
POWER DBL LOCK CAP HSG P/M 12P



TE Part #316088-1  
2.5 SIGNAL D/LOCK CAP HSG 4P



TE Part #353537-2  
040-3 UNSEALED CONT.TAB(S)GOLD



TE Part #521204-2  
HSG RCPT POSI MK 111 250 2POS



TE Part #CAT-SI261-P729  
STD Temp Signal Double Lock Plug



TE Part #2825888-1  
Housing - Magnet Wire to PCB

## Documents

### Product Drawings

187 PL EX REC. 26-20AWG PTBR

English

### CAD Files

3D PDF

3D

Customer View Model

[ENG\\_CVM\\_CVM\\_173722-1\\_E.2d\\_dxf.zip](#)

English

Customer View Model

[ENG\\_CVM\\_CVM\\_173722-1\\_E.3d\\_igs.zip](#)

English

Customer View Model

[ENG\\_CVM\\_CVM\\_173722-1\\_E.3d\\_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

### Product Specifications

Application Specification

English

### Instruction Sheets

Instruction Sheet (non U.S.)

English

POSITIVE LOCK EX CONTACT

English

### Agency Approvals

UL Report

English