



Terminals & Splices > Quick Disconnects



Quick Disconnect Terminal Type: **Receptacle**

Wire Size: **.32 – .82 mm²**

Mating Tab Width: **2.8 mm [.11 in]**

Mating Tab Thickness: **.51 mm [.02 in]**

Features

Configuration Features

Compatible With Wire & Cable Type	Discrete Wire
Connection Capacity	Single

Contact Features

Quick Disconnect Terminal Type	Receptacle
Mating Tab Width	2.8 mm[.11 in]
Mating Tab Thickness	.51 mm[.02 in]
Terminal Orientation	Straight
Contact Base Material	Brass
Terminal Plating Material	Tin
Crimp Type	F-Crimp
Barrel Type	Open

Termination Features

Product Terminates To	Wire & Cable
-----------------------	--------------

Mechanical Attachment

--	--



Wire Insulation Support	With
Mating Retention Type	Dimple

Dimensions

Product Length	16.13 mm[.635 in]
Compatible Insulation Diameter Range	1.52 – 2.54 mm[.06 – .1 in]
Terminal Material Thickness	.25 mm[.01 in]
Wire Size	.32 – .82 mm ²

Usage Conditions

Insulation Option	Uninsulated
Operating Temperature Range	-40 – 110 °C[-40 – 230 °F]

Industry Standards

Compatible With Agency/Standards Products	CSA, UL
---	---------

Packaging Features

Packaging Quantity	15000
Packaging Method	Strip/Reel

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2025 (250) Candidate List Declared Against: JUNE 2025 (250) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part



numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

 TE Part # 2150636-1 OCEAN-2.0-APPLICATOR-E-062F090OV-REM	 TE Part # 2150049-1 OCEAN-2.0-APPLICATOR-E-062F090F-REM	 TE Part # 7-2150049-7 OCEAN_2.0_SPARE_PART_KIT-062F090F	 TE Part # 2063846-1 CCII 110 FASTON REC 24-18 ASSY
 TE Part # 2150049-2 OCEAN-2.0-APPLICATOR-E-062F090FA-REA	 TE Part # 7-2150636-7 OCEAN_2.0_SPARE_PART_KIT-062F090OV	 TE Part # 2150636-2 OCEAN-2.0-APPLICATOR-E-062F090OV-REA	

Also in the Series | FASTON 110

 Crimp Terminal Housings(13)	 Insertion & Extraction Tools(1)	 PCB Terminals(22)	 Quick Disconnects(164)
---------------------------------	-------------------------------------	-----------------------	----------------------------

Customers Also Bought

 TE Part #OTX-433-HH-KF2-MS Remote MS 433MHz OOK AM 2Btn KF TX EU	 TE Part #BAT-HLD-002-THM-TR Battery Holder 2016 THM T&R Pack	 TE Part #61408-1 110 FASTON REC 20-16 AWG TPBR	 TE Part #2-321026-1 SPLICE,PG BUTT 26-22
---	---	---	---



TE Part #1565088-1
GRACE INERTIA CONNECTOR 3.5 6P

TE Part #3-2005820-9
CLUSTER BLOCK 3P SLIM HSG(GWT)

TE Part #6-2176091-2
RP 2A 0.25W 255R 0.1% 25PPM 1K RL

TE Part #CAT-L489-CH8172
LEAVYSEAL Connector Housings

TE Part #2344956-1
COVER

Documents

Product Drawings

110 FASTON REC 22-18 AWG TPBR

English

CAD Files

Customer View Model

ENG_CVM_CVM_42068-1_CT.2d_dxf.zip

English

3D PDF

3D

Customer View Model

ENG_CVM_CVM_42068-1_CT.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_42068-1_CT.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

FASTIN_FASTON_Product_Line

English

82004 FASTON Terminals (Insulated and Uninsulated) Catalog - FASTON Receptacles Section

English

Product Specifications

Application Specification

English



Agency Approvals

UL Report

English

UL Report

English