



Terminals & Splices > Quick Disconnects



Quick Disconnect Terminal Type: **Tab**

Wire Size: **404 – 1022 CMA**

Mating Tab Width: **2.8 mm [.11 in]**

Features

Configuration Features

Compatible With Wire & Cable Type

Discrete Wire

Connection Capacity

Single

Contact Features

Quick Disconnect Terminal Type

Tab

Mating Tab Width

2.8 mm [.11 in]

Mating Tab Thickness

.79 mm [.031 in]

Terminal Orientation

Straight

Contact Base Material

Copper Zinc Alloy

Terminal Plating Material

Tin

Crimp Type

F-Crimp

Barrel Type

Open

Termination Features

Product Terminates To

Wire & Cable

Mechanical Attachment

Locking Lance Height

1.2 mm [.047 in]



Mating Retention Type

Locking Lance

Dimensions

Product Length

22.5 mm [.886 in]

Compatible Insulation Diameter Range

1.15 – 1.6 mm [.045 – .062 in]

Wire Size

404 – 1022 CMA

Usage Conditions

Insulation Option

Uninsulated

Operating Temperature Range

-40 – 130 °C [-40 – 266 °F]

Packaging Features

Packaging Quantity

5000

Packaging Method

Reel

Product Compliance

For compliance documentation, visit the product page on [TE.com](https://www.te.com)>

EU RoHS Directive 2011/65/EU

Compliant

EU ELV Directive 2000/53/EC

Compliant

China RoHS 2 Directive MIIT Order No 32, 2016

No Restricted Materials Above Threshold

EU REACH Regulation (EC) No. 1907/2006

Current ECHA Candidate List: JUNE 2025 (250)
 Candidate List Declared Against: JUNE 2025 (250)
 Does not contain REACH SVHC

Halogen Content

Low Halogen - Br, Cl, F < 900 ppm per homogenous material. Also BFR/CFR/PVC Free

Solder Process Capability

Not applicable for solder process capability





Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts



Also in the Series | FASTIN-FASTON 110



Customers Also Bought



Documents

Product Drawings

[FF 110 TAB 0.2-0.5MM2 .070 F PTP CUZN30](#)

English

[FF 110 TAB 0.2-0.5MM2 .070 F PTP CUZN30](#)

English

CAD Files

[3D PDF](#)

3D

Customer View Model

[ENG_CVM_CVM_963961-2_D.2d_dxf.zip](#)

English

Customer View Model

[ENG_CVM_CVM_963961-2_D.3d_igs.zip](#)

English

Customer View Model

[ENG_CVM_CVM_963961-2_D.3d_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.



Product Specifications

2,8 mm Flachstecker

English

Application Specification

English

Application Specification

German

Application Specification

English