

PF0011/15/63 Datasheet



Product Name // IEC Connector Snap Fit To Panel Fused
Inlet PF0011 Series 1.5mm Panel Black 6.3mm Tab
Termination EN60 320-1 Standard Sheet C14 Class I

View Product Page

List No.	Dim A
PF0011/xx/28	27.0
PF0011/xx/48	26.5
PF0011/xx/63	28.6

BULGIN PF0011/Panel/Termination

Panel Thickness	
/10	1.0-1.14
/15	1.5-1.65
/20	2.0-2.15
/30	3.0-3.15

// Product Description:

- Snap Fit Panel Mount Fused IEC Inlets
- EN60 320-1 Standard Sheet C14 Class I
- Cold Condition
- Single 5mm x 20mm fuse with spare fuse facility
- Choice of panel thickness depending on part code: /10 - 1mm, /15 - 1.5mm, /20 - 2mm, /30 - 3mm

- Choice of Termination depending on part code: /28 - 2.8mm Solder Tag, /48 - 4.8mm Tab, /63 - 6.3mm Tab, /PC - PCB Spills
- Choice of colour depending on part code: /WH - White, /GY - Grey, no suffix - Black (some approvals apply to specific colours only - see data for details)
- Insulation Boot for rear of connector available separately (part code 11987) for all versions except PCB Mount
- Mate with PX0587, PX0587/SE, PX0588

// General Information:

Product Display Title:

Product Family:

Product Series:

Approvals:

Body Material:

Current Max:

Flamability Rating:

Function:

Iec Connector Colour:

Iec Connector Mates With:

Iec En60620 Type:

Max Operating Temperature:

Min Operating Temperature:

Max Panel Thickness:

Min Panel Thickness:

Number Of Contacts:

Rohs Compliant:

Voltage Max:

Snap Fit Panel Mount Fused IEC Inlets

IEC Connectors

IEC60320 Main Inlets and Outlets

CSA, ENEC, UL, VDE, CCC

Nylon 66

10A

UL94V-0

Panel Mount Fused Connector

Black

PX0587,PX0587/SE,PX0588

EN60 320-1 Standard Sheet C14 Class I

+70°C

-40°C

1.5mm

1.5mm

3 Contacts

Yes

250V

// Product PDF Links

IEC Connectors product data

// Product 3D CAD Model Links

PF0011/15/633D CAD Model