



- 注)
NOTES:
- 材質
MATERIAL
黄銅 (板厚: 0.3)
BRASS (THICKNESS: 0.3)
 - メッキ仕様
TERMINAL PLATING
接点部 : 金メッキ 0.25 μm MIN.
CONTACT AREA : GOLD 0.25 MICROMETER MIN.
圧着部 : 錫メッキ 1.0 μm MIN.
CRIMP AREA : TIN 1.0 MICROMETER MIN.
下地メッキ : ニッケルメッキ 2.0 μm MIN.
UNDER PLATE : NICKEL 2.0 MICROMETER MIN.
 - 適用電線範囲 : UL 2517 , AWG #16
APPLICABLE WIRE RANGE : UL2517 , AWG #16
 - 被覆外径 : φ2.2 ~ φ2.7
INSULATION EXTERNAL DIA : φ2.2 ~ φ2.7
 - 適用ハウジングアッセンブリ : 51194 シリーズ
APPLICABLE HOUSING ASS'Y : 51194 SERIES
 - 本製品は59320-**-90の鉛フリー品である。
THIS PRODUCT IS LEAD FREE OF 59320-**-90.

連鎖状 CHAIN	59320-9028	59320-**-28
端子形状 TERMINAL CONFIGURATION	MATERIAL No.	MODEL NO.

GENERAL TOLERANCES:
(UNLESS SPECIFIED)
一般公差

10 UNDER 未満	±0.2
10 OVER 以上 30 UNDER 未満	±0.25
30 OVER 以上	±0.3
ANGLE 角度	± 3°

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION

DIMENSION UNITS	SCALE
mm	1:1
GENERAL TOLERANCES (UNLESS SPECIFIED)	
4 PLACES ±	MM INCH
3 PLACES ±	
2 PLACES ±	
1 PLACE ±	
0 PLACES ±	
ANGULAR TOL ± °	

CURRENT REV DESC: RETRACTED AS PER THE REQUEST CASE #01114726

EC NO: 831459
DRWN: VISHAH2
CHKD: GB
APPR: GB

INITIAL REVISION:
DRWN: Y.WADA
APPR: M.SASAO

molex

POWER PLUG CRIMP TERM
-LEAD FREE-

PRODUCT CUSTOMER DRAWING

DOCUMENT NUMBER	DOC TYPE	DOC PART	REVISION
SD-59320-002	PSD	001	C
MATERIAL NUMBER	CUSTOMER	SHEET NUMBER	
SEE TABLE	GENERAL MARKET	1 OF 1	