

CUC-V14-C1ZNI-S/R4IE10G8 - RJ45 connector



1149841

<https://www.phoenixcontact.com/us/products/1149841>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



RJ45 connector, degree of protection: IP65/IP67, number of positions: 8, 10 Gbps, CAT6_A, connection method: IDC fast connection, connection cross section: AWG 26- 24, cable outlet: straight, Ethernet

Your advantages

- Easy and time-saving assembly with IDC fast connection technology
- Future-proof due to CAT6_A with 10 Gbps
- 360° shielding ensures reliable transmission, even in industrial applications
- Ideal companion for servicing or repairs in the field: no special tools required for mounting
- Locking system to prevent inadvertent release

Commercial data

| | |
|--------------------------------------|---------------|
| Item number | 1149841 |
| Packing unit | 1 pc |
| Minimum order quantity | 1 pc |
| Sales key | AB17 |
| Product key | ABNOAA |
| GTIN | 4063151145842 |
| Weight per piece (including packing) | 102.1 g |
| Weight per piece (excluding packing) | 88.612 g |
| Customs tariff number | 85366990 |
| Country of origin | PL |

1149841

<https://www.phoenixcontact.com/us/products/1149841>

Technical data

Product properties

| | |
|----------------------|-----------------------------|
| Product type | Data connector (cable side) |
| Type | Version 14 |
| Sensor type | Ethernet |
| Number of positions | 8 |
| Connection profile | Variant 14 |
| No. of cable outlets | 1 |
| Shielded | yes |
| Cable outlet | straight |

Insulation characteristics

| | |
|----------------------|---|
| Overvoltage category | I |
| Degree of pollution | 2 |

Electrical properties

| | |
|---|--|
| Rated current | 1.75 A |
| Insulation resistance | > 500 MΩ |
| Nominal voltage U_N | 48 V |
| Transmission medium | Copper |
| Transmission speed | 10 Gbps |
| Transmission characteristics (category) | CAT6 _A |
| Transmission speed | 10 Gbps |
| Power transmission | PoE++ in accordance with: IEEE 802.3bt |
| Wave impedance | 100 Ω |

Connection data

Connection technology

| | |
|------------------------------|----------------------|
| Connection method | IDC fast connection |
| Connection cross section AWG | 26 ... 24 (solid) |
| | 26 ... 24 (flexible) |

Dimensions

| | |
|--------|---------|
| Width | 22.4 mm |
| Height | 34 mm |
| Length | 95 mm |

Material specifications

| | |
|--|-----|
| Flammability rating according to UL 94 | V0 |
| Seal material, O-ring | NBR |
| Seal material cable seal | CR |
| Seal material | NBR |
| Seal material, pin connector pattern | NBR |

CUC-V14-C1ZNI-S/R4IE10G8 - RJ45 connector



1149841

<https://www.phoenixcontact.com/us/products/1149841>

| | |
|-------------------------------|-------|
| Contact material | Cu/Sn |
| Contact surface material | Au/Ni |
| Contact carrier material | PC |
| Material for screw connection | CuZn |

Cable/line

| | |
|-------------------------|----------------------|
| External cable diameter | 5.5 mm ... 10 mm |
| External cable diameter | 5.5 mm ... 10 mm |
| Cable cross section | 0.14 mm ² |
| Wave impedance | 100 Ω |

Environmental and real-life conditions

Ambient conditions

| | |
|---|------------------|
| Degree of protection | IP65/IP67 |
| Ambient temperature (operation) | -40 °C ... 85 °C |
| Ambient temperature (storage/transport) | -40 °C ... 70 °C |
| Ambient temperature (assembly) | -10 °C ... 40 °C |

Standards and regulations

| | |
|--------------------------|-----------------|
| Standards/specifications | IEC 61076-3-117 |
|--------------------------|-----------------|

CUC-V14-C1ZNI-S/R4IE10G8 - RJ45 connector



1149841

<https://www.phoenixcontact.com/us/products/1149841>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1149841>

|  cULus Recognized Approval ID: E335024-20170228 | | | | |
|--|-----------------------|-----------------------|-------------------|-----------------------------|
| | Nominal voltage U_N | Nominal current I_N | Cross section AWG | Cross section mm^2 |
| keine | | | | |
| | 56.5 V | 1.75 A | - | - |

CUC-V14-C1ZNI-S/R4IE10G8 - RJ45 connector



1149841

<https://www.phoenixcontact.com/us/products/1149841>

Classifications

ECLASS

| | |
|-------------|----------|
| ECLASS-13.0 | 27440290 |
| ECLASS-15.0 | 27440290 |

ETIM

| | |
|----------|----------|
| ETIM 9.0 | EC002943 |
|----------|----------|

UNSPSC

| | |
|-------------|----------|
| UNSPSC 21.0 | 39121400 |
|-------------|----------|

1149841

<https://www.phoenixcontact.com/us/products/1149841>

Environmental product compliance

EU RoHS

| | |
|---|------|
| Fulfills EU RoHS substance requirements | Yes |
| Exemption | 6(c) |

China RoHS

| | |
|--|---|
| Environment friendly use period (EFUP) | EFUP-50 |
| | An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required. |

EU REACH SVHC

| | |
|-------------------------------------|--------------------------------------|
| REACH candidate substance (CAS No.) | Lead(CAS: 7439-92-1) |
| SCIP | 528ae429-2bed-42b7-962d-e626ca800bba |

Phoenix Contact 2025 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com