

# PCIe® M.2 Gen 5 Card Edge Connectors

## HIGH-DENSITY HIGH PERFORMANCE CONNECTOR

Amphenol's PCIe® M.2 Gen 5 Connectors provide 67 contacts on 0.50 mm pitch. It occupies less board space, offers more connector height options and supports higher data rates compared to PCIe® Mini Card connector. It is designed for PCIe® Gen 5, making it suitable for tablets, laptops and low profile storage and server applications. PCIe® M.2 connectors also support higher data rate transmission with both single and double-sided modules.

- Various connector height and keying options
- Accepts angled insertion of add-in module cards
- The product support angled insertion
- Provides both right angle and vertical orientation for M.2 Connectors. Right angle option is available, the design of vertical option is ongoing



### TARGET MARKETS



### FEATURES

- Card edge connector with 67 contacts on a 0.50 mm pitch
- 75 positions with 8 connector key options
- Available in various connector heights
- Supports both single and double-sided modules
- Upgradeable to Gen 5 (32 Gb/s)
- Provides both right-angle and vertical orientations

### BENEFITS

- Fully compliant with PCI-SIG PCIe® M.2 specification
- Design flexibility
- Options to reduce overall height
- Enables higher data rates
- Supports higher speeds with backward compatibility to Gen 3 and Gen 4
- Allows for application flexibility

# TECHNICAL INFORMATION

## MATERIAL

- Contact: Copper Alloy with Gold plating sufficient to meet all mechanical and environmental requirements
- Contact Finish: Must be compatible with Lead-free soldering process
- Housing: Complies with UL 94 V-0. Must be compatible with Lead-free soldering process

## ELECTRICAL PERFORMANCE

- Low Level Contact Resistance: EIA-364-23, 55 mΩ max. (initial) per contact, \*20 mΩ max. change allowed
- Insulation Resistance: EIA-364-21, \* $>5 \times 10^8 \Omega$  at 500 VDC
- Dielectric Withstanding Voltage: EIA-364-20, \* $>300$  VAC (RMS) at sea level
- Current Rating: \*0.75 A/Power contact (continuous), \* The temperature rise above ambient shall not exceed 30 °C, \* The ambient condition is still air at 25 °C, \* EIA-364-70 Method 2
- Voltage Rating: 50 VAC per contact

## MECHANICAL PERFORMANCE

- Durability:
  - Normal M.2: 25-60 mating cycles

## ENVIRONMENTAL

- Durability: EIA-364-9; \*Option 1 – 25 Cycles, \*Option 2 – 60 Cycles, Upon completion of cycles the sample must meet all visual and electrical performance requirements
- Insertion Force: 20 N (2.04KgF, 1 Newton = 1Kg\* m/s<sup>2</sup>) max., EIA-364-13, Method A
- Shock: \* 250G (notebook) and 285G (tablet), \*at 2 ms half sine, \*on all six (6) axis
- Vibration: EIA-364-1000 Test group 3, EIA-364-28
- Operating Temperature Range: -40 °C to +80 °C
- Environmental Test Methodology: EIA-364-1000 Test group 1, 2, 3, 4
- Useful Field Life: Three (3) years

## SPECIFICATIONS

- Amphenol Product Specification:
  - GS-12-1142
  - GS-12-1195
  - GS-12-1248

## PACKAGING

- Tape & Reel

## TOOLING INFORMATION

- Tooled Up

## TARGET MARKETS/APPLICATIONS



Wireless



Laptop  
Tablet



Storage



Industrial PC

## PART NUMBERS

Description	Height (mm)	Data rate	Orientation	Key Options	Part Numbers
M.2 Gen 5	4.2	32 Gb/s	Right Angle	M	MDT420M0X501
M.2 Gen 5	6.7	32 Gb/s	Right Angle	M	MDT670M0X501
M.2 Gen 5	8.5	32 Gb/s	Right Angle	M	MDT850M0X501
M.2 Gen 5	3.2	32 Gb/s	Right Angle	M	MDT320M01501
M.2 Gen 5	1.88	32 Gb/s	Right Angle, RVS, Mid-mount	M	10181068-002RLF
M.2 Gen 5	10.85	32 Gb/s	Right Angle, Stack M.2	M	10180257-004RHLF

Find part number details using the search box on [www.amphenol-cs.com](http://www.amphenol-cs.com)

**WHERE INNOVATION CONNECTS**  
Scan to learn more ▶



SS10PCIEM2G50825EA4