


PXP6034/A Datasheet

Product Name // Rewireable Flex Connector PXP6034
Series PUR CAT5e Cable Plastic Body

 [View Product Page](#)



// Product Description:

- Rewireable Flex Cable Connectors
 - Water and dustproof to IP66, IP68, IP69K when mated with compatible connector
 - 30 degree push twist locking, tamperproof lock prevents accidental un-mating
 - Supplied with shielded RJ45 plug
 - Choice of cable acceptance depending on part code:
 - Part codes suffixed /A have cable glands optimised for PUR jacket cable to maintain CAT5e performance
- Part codes suffixed /B accept cable 4mm-10mm diameter
 - Choice of body material depending on part code:
 - Plastic body (part codes prefixed PXP)
 - Metal body (part codes prefixed PXM)
 - PXP6081/PXM6081 Sealing Cap available separately to maintain IP rating of unmated connectors
 - Mate with PXP6033TP, PXP6033TP/E, PXM6033TP Front Panel Mount CAT5e Couplers

// General Information:

Product Display Title:	Rewireable Flex Cable Connectors
Product Family:	Circular Data Connectors
Product Series:	6000 Series - Ethernet Buccaneer
Approvals:	CSA, UL, VDE
Body Material:	Polycarbonate/Polybutylene Terephthalate (PC/PBT)
Body Material Type:	Plastic Body
Contact Type:	Plug Contact
Coupling Type:	Push-Twist
Current Max:	1.5A
Diameter Over Coupling Ring Mm:	32mm
Ethernet Category:	Cat 5e
Flamability Rating:	UL94V-0
Function:	Flex Cable Connector
Ip Rating:	IP66, IP68, IP69K
Max Cable Entry Size:	7mm
Min Cable Entry Size:	5mm
Max Operating Temperature:	+120°C
Min Operating Temperature:	-40°C
Number Of Contacts:	8 Contacts
Voltage Max:	42V

// Product PDF Links

-  6000 Series Ethernet connectors...
-  6000 Series Ethernet connectors...

// Product 3D CAD Model Links

-  PXP6034/A3D CAD Model



Have a question or project enquiry
you'd like to talk to us about?



[Click Here To Contact Us](#)