

Data Sheet | Item Number: 216-144


Ferrule; Sleeve for 1.5 mm² / AWG 16; uninsulated; electro-tin plated; electrolytic copper; gastight crimped; acc. to DIN 46228, Part 1/08.92; silver-colored

<https://www.wago.com/216-144>



Color: ■ silver-colored

Similar to illustration



Dimensions in mm

Connection data	
Cross-section metric	1.5 mm²
Strip length	10 mm / 0.39 inches
Cross-section AWG	16 AWG

Physical data	
Total length	10 mm
Wall thickness crimp sleeve	0.15 mm
Diameter crimp sleeve inside	1.7 mm

Mechanical data	
Plastic collar	No

Material data	
Color	silver-colored
Fire load	0 MJ
Weight	0.1 g

Commercial data	
Product Group	2 (Terminal Block Accessories)
PU (SPU)	5000 (1000) pcs
Packaging type	Box
Country of origin	DE
GTIN	4044918016384
Customs tariff number	85369010000



Product classification		
UNSPSC		39121405
eCl@ss 10.0		27-40-02-01
eCl@ss 9.0		27-40-02-01
ETIM 9.0		EC000005
ETIM 8.0		EC000005
ECCN		NO US CLASSIFICATION

Environmental Product Compliance	
RoHS Compliance Status	Compliant,No Exemption

Downloads

Environmental Product Compliance


Compliance Search

Environmental Product Compliance 216-144

↓

Documentation				
Bid Text				
216-144	19.02.2019	xml	2.87 KB	↓
216-144	13.06.2017	doc	23.00 KB	↓

Installation Notes



A perfect gas-tight crimp – both electrical-ly and mechanically reliable