

# General Purpose Transistors

## NPN Silicon

### MMBT3904TT1G, SMMBT3904TT1G

This transistor is designed for general purpose amplifier applications. It is housed in the SOT-416/SC-75 package which is designed for low power surface mount applications.

#### Features

- S Prefix for Automotive and Other Applications Requiring Unique Site and Control Change Requirements; AEC-Q101 Qualified and PPAP Capable
- These Devices are Pb-Free, Halogen Free/BFR Free and are RoHS Compliant\*

#### MAXIMUM RATINGS ( $T_A = 25^\circ\text{C}$ )

| Rating                         | Symbol    | Value | Unit |
|--------------------------------|-----------|-------|------|
| Collector – Emitter Voltage    | $V_{CEO}$ | 40    | Vdc  |
| Collector – Base Voltage       | $V_{CBO}$ | 60    | Vdc  |
| Emitter – Base Voltage         | $V_{EBO}$ | 6.0   | Vdc  |
| Collector Current – Continuous | $I_C$     | 200   | mAdc |

#### THERMAL CHARACTERISTICS

| Characteristic                                                                                                  | Symbol          | Max         | Unit                       |
|-----------------------------------------------------------------------------------------------------------------|-----------------|-------------|----------------------------|
| Total Device Dissipation,<br>FR-4 Board (Note 1) @ $T_A = 25^\circ\text{C}$<br>Derated above $25^\circ\text{C}$ | $P_D$           | 200<br>1.6  | mW<br>mW/ $^\circ\text{C}$ |
| Thermal Resistance, Junction-to-Ambient<br>(Note 1)                                                             | $R_{\theta JA}$ | 600         | $^\circ\text{C}/\text{W}$  |
| Total Device Dissipation,<br>FR-4 Board (Note 2) @ $T_A = 25^\circ\text{C}$<br>Derated above $25^\circ\text{C}$ | $P_D$           | 300<br>2.4  | mW<br>mW/ $^\circ\text{C}$ |
| Thermal Resistance, Junction-to-Ambient<br>(Note 2)                                                             | $R_{\theta JA}$ | 400         | $^\circ\text{C}/\text{W}$  |
| Junction and Storage Temperature Range                                                                          | $T_J, T_{stg}$  | -65 to +150 | $^\circ\text{C}$           |

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.


1. FR-4 @ Minimum Pad
2. FR-4 @  $1.0 \times 1.0$  Inch Pad

\*For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.


## GENERAL PURPOSE AMPLIFIER TRANSISTORS SURFACE MOUNT



SOT-416/SC-75  
CASE 463  
STYLE 1



#### MARKING DIAGRAM



AM = Device Code  
M = Date Code\*  
▪ = Pb-Free Package

(Note: Microdot may be in either location)

\*Date Code orientation may vary depending upon manufacturing location.

#### ORDERING INFORMATION

| Device        | Package              | Shipping†           |
|---------------|----------------------|---------------------|
| MMBT3904TT1G  | SOT-416<br>(Pb-Free) | 3,000 / Tape & Reel |
| SMMBT3904TT1G | SOT-416<br>(Pb-Free) | 3,000 / Tape & Reel |

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

# MMBT3904TT1G, SMMBT3904TT1G

## ELECTRICAL CHARACTERISTICS (T<sub>A</sub> = 25°C unless otherwise noted)

| Characteristic | Symbol | Min | Max | Unit |
|----------------|--------|-----|-----|------|
|----------------|--------|-----|-----|------|

### OFF CHARACTERISTICS

|                                                                                                 |                      |     |    |      |
|-------------------------------------------------------------------------------------------------|----------------------|-----|----|------|
| Collector – Emitter Breakdown Voltage (Note 3)<br>(I <sub>C</sub> = 1.0 mA, I <sub>B</sub> = 0) | V <sub>(BR)CEO</sub> | 40  | –  | Vdc  |
| Collector – Base Breakdown Voltage<br>(I <sub>C</sub> = 10 μA, I <sub>E</sub> = 0)              | V <sub>(BR)CBO</sub> | 60  | –  | Vdc  |
| Emitter – Base Breakdown Voltage<br>(I <sub>E</sub> = 10 μA, I <sub>C</sub> = 0)                | V <sub>(BR)EBO</sub> | 6.0 | –  | Vdc  |
| Base Cutoff Current<br>(V <sub>CE</sub> = 30 Vdc, V <sub>EB</sub> = 3.0 Vdc)                    | I <sub>BL</sub>      | –   | 50 | nAdc |
| Collector Cutoff Current<br>(V <sub>CE</sub> = 30 Vdc, V <sub>EB</sub> = 3.0 Vdc)               | I <sub>CEX</sub>     | –   | 50 | nAdc |

### ON CHARACTERISTICS (Note 3)

|                                                                                                                                                                                                                                                                                                       |                      |                             |                         |     |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------|-----------------------------|-------------------------|-----|
| DC Current Gain<br>(I <sub>C</sub> = 0.1 mA, V <sub>CE</sub> = 1.0 Vdc)<br>(I <sub>C</sub> = 1.0 mA, V <sub>CE</sub> = 1.0 Vdc)<br>(I <sub>C</sub> = 10 mA, V <sub>CE</sub> = 1.0 Vdc)<br>(I <sub>C</sub> = 50 mA, V <sub>CE</sub> = 1.0 Vdc)<br>(I <sub>C</sub> = 100 mA, V <sub>CE</sub> = 1.0 Vdc) | h <sub>FE</sub>      | 40<br>70<br>100<br>60<br>30 | –<br>–<br>300<br>–<br>– | –   |
| Collector – Emitter Saturation Voltage<br>(I <sub>C</sub> = 10 mA, I <sub>B</sub> = 1.0 mA)<br>(I <sub>C</sub> = 50 mA, I <sub>B</sub> = 5.0 mA)                                                                                                                                                      | V <sub>CE(sat)</sub> | –<br>–                      | 0.2<br>0.3              | Vdc |
| Base – Emitter Saturation Voltage<br>(I <sub>C</sub> = 10 mA, I <sub>B</sub> = 1.0 mA)<br>(I <sub>C</sub> = 50 mA, I <sub>B</sub> = 5.0 mA)                                                                                                                                                           | V <sub>BE(sat)</sub> | 0.65<br>–                   | 0.85<br>0.95            | Vdc |

### SMALL – SIGNAL CHARACTERISTICS

|                                                                                                             |                  |     |     |                    |
|-------------------------------------------------------------------------------------------------------------|------------------|-----|-----|--------------------|
| Current – Gain – Bandwidth Product<br>(I <sub>C</sub> = 10 mA, V <sub>CE</sub> = 20 Vdc, f = 100 MHz)       | f <sub>T</sub>   | 300 | –   | MHz                |
| Output Capacitance<br>(V <sub>CB</sub> = 5.0 Vdc, I <sub>E</sub> = 0, f = 1.0 MHz)                          | C <sub>obo</sub> | –   | 4.0 | pF                 |
| Input Capacitance<br>(V <sub>EB</sub> = 0.5 Vdc, I <sub>C</sub> = 0, f = 1.0 MHz)                           | C <sub>ibo</sub> | –   | 8.0 | pF                 |
| Input Impedance<br>(V <sub>CE</sub> = 10 Vdc, I <sub>C</sub> = 1.0 mA, f = 1.0 kHz)                         | h <sub>ie</sub>  | 1.0 | 10  | k Ω                |
| Voltage Feedback Ratio<br>(V <sub>CE</sub> = 10 Vdc, I <sub>C</sub> = 1.0 mA, f = 1.0 kHz)                  | h <sub>re</sub>  | 0.5 | 8.0 | X 10 <sup>-4</sup> |
| Small – Signal Current Gain<br>(V <sub>CE</sub> = 10 Vdc, I <sub>C</sub> = 1.0 mA, f = 1.0 kHz)             | h <sub>fe</sub>  | 100 | 400 | –                  |
| Output Admittance<br>(V <sub>CE</sub> = 10 Vdc, I <sub>C</sub> = 1.0 mA, f = 1.0 kHz)                       | h <sub>oe</sub>  | 1.0 | 40  | μmhos              |
| Noise Figure<br>(V <sub>CE</sub> = 5.0 Vdc, I <sub>C</sub> = 100 μA, R <sub>S</sub> = 1.0 k Ω, f = 1.0 kHz) | NF               | –   | 5.0 | dB                 |

### SWITCHING CHARACTERISTICS

|              |                                                                                        |                |   |     |    |
|--------------|----------------------------------------------------------------------------------------|----------------|---|-----|----|
| Delay Time   | (V <sub>CC</sub> = 3.0 Vdc, V <sub>BE</sub> = –0.5 Vdc)<br>MMBT3904TT1G, SMMBT3904TT1G | t <sub>d</sub> | – | 35  | ns |
| Rise Time    | (I <sub>C</sub> = 10 mA, I <sub>B1</sub> = 1.0 mA)<br>MMBT3904TT1G, SMMBT3904TT1G      | t <sub>r</sub> | – | 35  |    |
| Storage Time | (V <sub>CC</sub> = 3.0 Vdc, I <sub>C</sub> = 10 mA)<br>MMBT3904TT1G, SMMBT3904TT1G     | t <sub>s</sub> | – | 200 |    |
| Fall Time    | (I <sub>B1</sub> = I <sub>B2</sub> = 1.0 mA)<br>MMBT3904TT1G, SMMBT3904TT1G            | t <sub>f</sub> | – | 50  |    |

3. Pulse Test: Pulse Width ≤ 300 μs, Duty Cycle ≤ 2.0%.

# MMBT3904TT1G, SMMBT3904TT1G




Figure 1. Normalized Thermal Response




Figure 2. Delay and Rise Time Equivalent Test Circuit




Figure 3. Storage and Fall Time Equivalent Test Circuit

\* Total shunt capacitance of test jig and connectors

## TYPICAL TRANSIENT CHARACTERISTICS




Figure 4. Capacitance




Figure 5. Charge Data

# MMBT3904TT1G, SMMBT3904TT1G




Figure 6. Turn-On Time




Figure 7. Rise Time




Figure 8. Storage Time




Figure 9. Fall Time

## TYPICAL AUDIO SMALL-SIGNAL CHARACTERISTICS NOISE FIGURE VARIATIONS

( $V_{CE} = 5.0$  Vdc,  $T_A = 25^\circ\text{C}$ , Bandwidth = 1.0 Hz)




Figure 10. Noise Figure




Figure 11. Noise Figure

# MMBT3904TT1G, SMMBT3904TT1G

## h PARAMETERS

( $V_{CE} = 10 \text{ Vdc}$ ,  $f = 1.0 \text{ kHz}$ ,  $T_A = 25^\circ\text{C}$ )




Figure 12. Current Gain




Figure 13. Output Admittance




Figure 14. Input Impedance




Figure 15. Voltage Feedback Ratio

## TYPICAL STATIC CHARACTERISTICS




Figure 16. DC Current Gain

# MMBT3904TT1G, SMMBT3904TT1G




Figure 17. Collector Saturation Region




Figure 18. "ON" Voltages






Figure 19. Temperature Coefficients

**SC75-3 1.60x0.80x0.80, 1.00P**  
**CASE 463**  
**ISSUE H**


DATE 01 FEB 2024



TOP VIEW




SIDE VIEW



END VIEW

**GENERIC MARKING DIAGRAM\***



XX = Specific Device Code  
M = Date Code  
▪ = Pb-Free Package

\*This information is generic. Please refer to device data sheet for actual part marking. Pb-Free indicator, "G" or microdot "▪", may or may not be present. Some products may not follow the Generic Marking.

STYLE 1:  
PIN 1. BASE  
2. EMITTER  
3. COLLECTOR


STYLE 2:  
PIN 1. ANODE  
2. N/C  
3. CATHODE

STYLE 3:  
PIN 1. ANODE  
2. ANODE  
3. CATHODE

STYLE 4:  
PIN 1. CATHODE  
2. CATHODE  
3. ANODE

STYLE 5:  
PIN 1. GATE  
2. SOURCE  
3. DRAIN

| DIM | MILLIMETERS |      |      |
|-----|-------------|------|------|
|     | MIN.        | NOM. | MAX. |
| A   | 0.70        | 0.80 | 0.90 |
| A1  | 0.00        | 0.05 | 0.10 |
| A2  | 0.80 REF.   |      |      |
| b   | 0.15        | 0.20 | 0.30 |
| c   | 0.10        | 0.15 | 0.25 |
| D   | 1.55        | 1.60 | 1.65 |
| E   | 1.50        | 1.60 | 1.70 |
| E1  | 0.70        | 0.80 | 0.90 |
| e   | 1.00 BSC    |      |      |
| L   | 0.10        | 0.15 | 0.20 |



**RECOMMENDED MOUNTING FOOTPRINT\***

\* FOR ADDITIONAL INFORMATION ON OUR Pb-FREE STRATEGY AND SOLDERING DETAILS, PLEASE DOWNLOAD THE ON SEMICONDUCTOR SOLDERING AND MOUNTING TECHNIQUES REFERENCE MANUAL, SOLDERRM/D.

|                         |                                     |                                                                                                                                                                                  |
|-------------------------|-------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>DOCUMENT NUMBER:</b> | <b>98ASB15184C</b>                  | Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red. |
| <b>DESCRIPTION:</b>     | <b>SC75-3 1.60x0.80x0.80, 1.00P</b> | <b>PAGE 1 OF 1</b>                                                                                                                                                               |

onsemi and onsemi are trademarks of Semiconductor Components Industries, LLC dba onsemi or its subsidiaries in the United States and/or other countries. onsemi reserves the right to make changes without further notice to any products herein. onsemi makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does onsemi assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. onsemi does not convey any license under its patent rights nor the rights of others.

**onsemi**, **Onsemi**, and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at [www.onsemi.com/site/pdf/Patent-Marking.pdf](http://www.onsemi.com/site/pdf/Patent-Marking.pdf). **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as-is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

## ADDITIONAL INFORMATION

### TECHNICAL PUBLICATIONS:

Technical Library: [www.onsemi.com/design/resources/technical-documentation](http://www.onsemi.com/design/resources/technical-documentation)  
onsemi Website: [www.onsemi.com](http://www.onsemi.com)

### ONLINE SUPPORT: [www.onsemi.com/support](http://www.onsemi.com/support)

For additional information, please contact your local Sales Representative at  
[www.onsemi.com/support/sales](http://www.onsemi.com/support/sales)