



features

- Semi-precision metal film resistors
- Meets requirements of MIL-R-22684
- Suitable for automatic machine insertion
- MFS two times the power rating of the standard body type
- Products with lead-free terminations meet EU RoHS requirements
- AEC-Q200 Qualified: MF1/4, MFS1/4, MFS1/2


dimensions and construction



Derating Curve



Surface Temperature Rise



Type	Dimensions inches (mm)				
	L (ref.)	C (max.)	D	d (nom.)	I*
MFS1/4	.126 ±.008 (3.2 ±0.2)	.133 (3.4)	.066 ^{+0.008} _{-.004} (1.7 ^{+0.2} _{-.01})	.018 (0.45)	1.10 ±.118 (28.0 ±3.0)
MF1/4	.248 ±.02 (6.3 ±0.5)	.280 (7.1)	.091 ±.012 (2.3 ±0.3)	.024 (0.6)	
MFS1/2	.248 ±.02 (6.3 ±0.5)	.280 (7.1)	.091 ±.012 (2.3 ±0.3)	.024 (0.6)	1.10 ^{+0.012} _{-.016} (28.0 ^{+3.0} _{-.4.0})
MF1/2C MF1/2D	.354 ±.04 (9.0 ±1.0)	.437 (11.1)	.138 ^{+0.016} _{-.02} (3.5 ^{+0.4} _{-.05})	.024 (0.6)	
MF1/2L	.354 ±.04 (9.0 ±1.0)	.437 (11.1)	.138 ±.016 (3.5 ±0.4)	.024 (0.6)	1.10 ±.118 (28.0 ±3.0)
RK1/4	.248 ±.02 (6.3 ±0.5)	.280 (7.1)	.091 ±.012 (2.3 ±0.3)	.024 (0.6)	0.94 min. (24.0 min.)
RK1/2	.374 ±.04 (9.5 ±1.0)	.437 (11.1)	.138 ±.016 (3.5 ±0.4)	.024 (0.6)	
RK1	.610 ±.04 (15.5 ±1.0)	.720 (18.3)	.217 ±.02 (5.5 ±0.5)	.031 (0.8)	1.50 ±.118 (38.0 ±3.0)

* Lead length changes depending on taping and forming.

ordering information

MF	1/2	D	C	T52	R	1003	F
Type	Power Rating	T.C.R.	Termination Material	Taping and Forming	Packaging	Nominal Resistance	Tolerance
MF MFS RK	1/4: 0.25W 1/2: 0.50W 1: 1W	C: ±50 D: ±100 L: ±200 G: ±250 B: ±350	C: SnCu	1/4: T26, T52, VT, VTP, VTE, L, MT, M, U 1/2: T26, T52, VT, VTP, VTE, M 1: T521	A: Ammo R: Reel	+2%: 2 significant figures + 1 multiplier +0.5%, +1%: 3 significant figures + 1 multiplier "R" indicates decimal on value <100Ω	D: ±0.5% F: ±1% G: ±2% J: ±5%

For further information on packaging, please refer to Appendix C.

Specifications given herein may be changed at any time without prior notice. Please confirm technical specifications before you order and/or use.

10/27/25

applications and ratings

Part Designation	Power Rating @ 70°C	Dielectric Withstanding Voltage	T.C.R. (ppm/°C)	Resistance Range (Ω)				Maximum Working Voltage	Maximum Overload Voltage	Operating Temperature Range	
				(D±0.5%) E-24 E-192	(F±1.0%) E-24 E-96	(G±2.0%) E-24	(J±5.0%) E-24				
MFS1/4C	0.25W	300V	C: ±50	49.9 - 562k	10 - 1M	—	—	250V	500V	-55°C to +155°C	
MFS1/4D			D: ±100								
MF1/4C	0.25W	500V	C: ±50	10 - 2.21M	10 - 2.21M	—	—	250V	500V		
MF1/4D			D: ±100								
MF1/4L			L: ±200								—
MFS1/2C	0.50W	500V	C: ±50	10 - 1M	10 - 2.2M	10 - 2.2M	—	350V	700V		
MFS1/2D			D: ±100								
MF1/2C	0.50W	700V	C: ±50	10 - 5.05M	10 - 4.99M	—	—	350V	700V		
MF1/2D			D: ±100								10 - 5.11M
MF1/2L			L: ±200								—
RK1/4D	0.25W	500V	D: ±100	—	3.09M - 25M	—	—	500V	700V		
RK1/4L			L: ±200	—	—	3.3M - 33M	3.3M - 33M				
RK1/4B			B: ±350	—	100k - 25M	100k - 33M	100k - 33M				
RK1/2D	0.50W	700V	D: ±100	—	5.11M - 33M	—	—	700V	1000V		
RK1/2L			L: ±200	—	—	6.2M - 33M	6.2M - 33M				
RK1/2B			B: ±350	—	100k - 35M	100k - 51M	100k - 51M				
RK1BC	1W	1000V	B: ±350	—	100k - 51M	100k - 100M	100k - 100M	1000V	1500V		
RK1/2G*	0.50W	700V	G: ±250	—	—	—	1M - 12M	350V	700V		

* Discharge path resistor

environmental applications

Performance Characteristics

Parameter	Requirement Δ R ±(% + 0.05Ω)		Test Method
	Limit	Typical	
Resistance	Within specified tolerance	—	25°C
T.C.R.	Within specified T.C.R.	—	+25°C/+125°C
Overload (Short Time)	RK: ±1%, RK1/2G: ±2.5% MF: ±0.5%	RK: ±0.6%, RK1/2G: ±1% MF: ±0.3%	RK, MFS1/4, MF1/4, MF1/2: Rated voltage x 2.5 or max. overload voltage, whichever is lower, for 5 seconds; MFS1/2: Rated voltage x 2 or max. overload voltage for 5 seconds, whichever is less
Resistance to Solder Heat	RK: ±1%; RK1/2G: ±5%; MFS: ±0.75%; MF1/4, MFS1/2, MF1/2: ±0.5%	RK: ±0.5%; RK1/2G: ±1% MFS1/4: ±0.4%; MF1/4, MFS1/2, MF1/2: ±0.25%	260°C ± 5°C, 10 seconds ± 1 second or RK: 350°C ± 10°C, 3.5 seconds ± 0.5 second
Dielectric Withstanding Voltage	No breakdown	—	RK: 1 minute
Insulation Resistance	Not less than 10,000MΩ	—	RK: 100V, 1 minute
Rapid Change of Temperature	RK,MF: ±1%; RK1/2G: ±5%	MF: ±0.3%; RK: ±0.5%, RK1/2G: ±1%	-55°C (30 minutes), +155°C (30 minutes), 5 cycles
Moisture Resistance	RK: ±5%; RK1/2G: ±10%; MFS1/4: ±1.5%; MF1/4, MFS1/2, MF1/2: ±1%	RK: ±2%; RK1/2G: ±5%; MFS1/4: ±1%; MF1/4, MFS1/2, MF1/2: ±0.75%	40°C ± 2°C, 90 - 95% RH, 1000 hours, 1.5 hr ON, 0.5 hr OFF cycle
Endurance at 70°C	RK: ±5%; RK1/2G: ±10%; MFS1/4: ±1.5%; MF1/4, MFS1/2, MF1/2: ±1%	RK: ±2%; RK1/2G: ±5%; MFS1/4: ±1%; MF1/4, MFS1/2, MF1/2: ±0.75%	70°C ± 2°C, 1000 hours, 1.5 hr ON, 0.5 hr OFF cycle
Resistance to Solvent	No abnormality in appearance. Marking shall be easily legible	—	RK: The resistor shall be immersed for 5 seconds in IPA
Impulse	No such abnormalities as short-circuit, burnout, breakdown, etc.	—	RK: Discharge from 1000pF capacitor 50 pulses. Internal 2.5 seconds. Charge voltage: 1.25kV (RK1/4), 2.5kV (RK1/2) and 6kV (RK1)