

## REGULATORY COMPLIANCE




## ITEM DESCRIPTION

Watch Crystal Resonator 1.2mm x 2.0mm x 0.6mm 2 Pad Plastic Surface Mount (SMD) 32.768kHz


## ELECTRICAL SPECIFICATIONS

Nominal Frequency	32.768kHz
Frequency Tolerance (at 25°C)	±20ppm (See Options)
Load Capacitance	12.5pF (See Options)
Operating Temperature Range	-40°C to +85°C (See Options)
Storage Temperature Range	-55°C to +125°C
Turnover Temperature	+25°C±5°C
Mode of Operation	Flexural Mode (Tuning Fork)
Frequency Stability	-0.03ppm/(Change in °C) <sup>2</sup> Typical, -0.04ppm/(Change in °C) <sup>2</sup> Maximum, Parabolic Curve
Equivalent Series Resistance	90,000 Ohms Maximum (-40°C to +85°C Option) 110,000 Ohms Maximum (-40°C to +125°C Option)
Drive Level	0.5µWatt Maximum
Aging (at 25°C)	±2ppm/First Year Maximum
Quality Factor	9000 Minimum
Shunt Capacitance (Co)	0.9 pF ~ 1.2pF Typical
Insulation Resistance	500 Megaohms Minimum (Measured at 100Vdc ±15Vdc)

## PART NUMBERING GUIDE




**MECHANICAL DIMENSIONS**



Note: Due to material availability, the outline and finish color of the component may vary. This variation in no way affects the electrical performance of the product.

**SUGGESTED SOLDER PAD LAYOUT**



PIN	CONNECTION
1	Crystal
2	Crystal

All Tolerances are  $\pm 0.1$


All Dimensions in Millimeters

## TAPE & REEL DIMENSIONS


Quantity per Reel: 3000 Units

All Dimensions in Millimeters

Compliant to EIA-481



RECOMMENDED SOLDER REFLOW METHODS




**LOW TEMPERATURE INFRARED/CONVECTION 240°C**

T <sub>s</sub> MAX to T <sub>L</sub> (Ramp-up Rate)	5°C/Second Maximum
<b>Preheat</b>	
- Temperature Minimum (T <sub>s</sub> MIN)	N/A
- Temperature Typical (T <sub>s</sub> TYP)	150°C
- Temperature Maximum (T <sub>s</sub> MAX)	N/A
- Time (t <sub>s</sub> )	60 - 120 Seconds
Ramp-up Rate (T <sub>L</sub> to T <sub>p</sub> )	5°C/Second Maximum
<b>Time Maintained Above:</b>	
- Temperature (T <sub>L</sub> )	150°C
- Time (t <sub>L</sub> )	200 Seconds Maximum
Peak Temperature (T <sub>p</sub> )	245°C Maximum
Target Peak Temperature (T <sub>p</sub> Target)	245°C Maximum 2 Times / 230°C Maximum 1 Time
Time within 5°C of actual peak (t <sub>p</sub> )	10 Seconds Maximum 2 Times / 80 Seconds Maximum 1 Time
Ramp-down Rate	5°C/Second Maximum
Time 25°C to Peak Temperature (t)	N/A
Moisture Sensitivity Level	Level 1
Additional Notes	Temperatures shown are applied to body of device.

**Low Temperature Manual Soldering**

185°C Maximum for 10 Seconds Maximum, 2 times Maximum. (Temperatures shown are applied to body of device.)

**RECOMMENDED SOLDER REFLOW METHOD**



LOW TEMPERATURE INFRARED/CONVECTION 245°C	
T <sub>s</sub> MAX to T <sub>L</sub> (Ramp-up Rate)	5°C/Second Maximum
<b>Preheat</b>	
- Temperature Minimum (T <sub>s</sub> MIN)	N/A
- Temperature Typical (T <sub>s</sub> TYP)	150°C
- Temperature Maximum(T <sub>s</sub> MAX)	N/A
- Time (t <sub>s</sub> )	30 - 60 Seconds
Ramp-up Rate (T <sub>L</sub> to T <sub>P</sub> )	5°C/Second Maximum
<b>Time Maintained Above:</b>	
- Temperature (T <sub>L</sub> )	150°C
- Time (t <sub>L</sub> )	200 Seconds Maximum
Peak Temperature (T <sub>P</sub> )	245°C Maximum
Target Peak Temperature (T <sub>P</sub> Target)	245°C Maximum 2 Times / 230°C Maximum 1 Time
Time within 5°C of actual peak (t <sub>p</sub> )	10 Seconds Maximum 2 Times / 80 Seconds Maximum 1 Time
Ramp-down Rate	5°C/Second Maximum
Time 25°C to Peak Temperature (t)	N/A
Moisture Sensitivity Level	Level 1
Additional Notes	Temperatures shown are applied to body of device.

**Low Temperature Manual Soldering**

185°C Maximum for 10 Seconds Maximum, 2 times Maximum. (Temperatures shown are applied to body of device.)

**High Temperature Manual Soldering**

260°C Maximum for 5 Seconds Maximum, 2 times Maximum. (Temperatures shown are applied to body of device.)