

MST 1-PHASE CONTROL AND ISOLATION TRANSFORMER



P: 4000VA IN: 208...550VAC OUT: 2x115VAC

Art.No.: 86156
 Weight: 34
 Country of origin: CZ
 Model designation: MST 4000-208...550/2x115

Single-phase - Control and Isolation Transformers
 4000 VA
 Isolation class T 40/B
 Other voltages on request.

[Link to Product](#)

Illustration



Product may differ from Image



Header

Material short text MST 4000-208...550/2x115

Commercial data

URL Webshop	https://shop.murrelektronik.com/86156
GTIN	4048879375542
ECLASS-6.0	27031302
ECLASS-6.1	27031302
ECLASS-7.0	27031302
ECLASS-7.1	27031302
ECLASS-8.0	27031302
ECLASS-8.1	27031302
ECLASS-9.0	27031302
ECLASS-9.1	27031302
ECLASS-10.0.1	27031302
ECLASS-10.1	27031302
ECLASS-11.0	27031302
ECLASS-11.1	27031302
ECLASS-12.0	27031302
ECLASS-13.0	27031302
ECLASS-14.0	27031302
ETIM-5.0	EC002486
ETIM-6.0	EC002486
ETIM-7.0	EC002486
ETIM-8.0	EC002486
customs tariff number	85043200
EAN	4048879375542
Packaging unit	1

Electrical data | Supply

Power frequency	50 ... 60 Hz
-----------------	--------------

Electrical data | Input

Input voltage AC	420, 208, 525, 550, 230, 380, 400, 440, 460, 480, 500
Input voltage 1 AC	208 V
Input voltage 2 AC	550 V
Input current at input voltage 1 AC	20 A
Input current at input voltage 2 AC	77 A
Inrush current at input voltage 1	372 A
Inrush current at input voltage 2	141 A
Short-circuit current at input voltage 1	960 A
Short-circuit current at input voltage 2	367 A

Electrical data | Output

Output voltage adjustable	yes
Output voltage	1 × 230 / 1 × 115 / 2 × 115 V AC
Output voltage AC 1	230 V
Output voltage AC 2	115 V
Power rating AC max.	4,000 VA

Device protection | Electrical

Insulation test voltage input - output	4 kV
--	------

Mechanical data | Mounting data

Height	213 mm
Width	197 mm
Depth	250 mm
Suitable for mounting type	Long-hole mounting
Mounting dimension a	200 mm
Mounting dimension b	174 mm
Mounting dimension c	9 mm

Diameter bore	9 mm
Length bore	14 mm

Environmental characteristics | Climatic

Operating temperature min.	-20 °C
Operating temperature max.	40 °C
Storage temperature min.	-40 °C
Storage temperature max.	80 °C

Conformity

Product standard	EN 61558-1, EN 61558-2-4, EN 62041 category 0
------------------	---