



Switches > Slide Switches



Contact Current Rating: **.3 A**

Configuration (Pole-Throw): **Double Pole - Double Throw**

Product Orientation: **Right Angle**

Contact Base Material: **Copper Alloy**

Number of Actuators: **Single**

Features

Configuration Features

Terminals Connected	2-1, 5-4
Configuration (Pole-Throw)	Double Pole - Double Throw
Number of Actuators	Single
Number of Positions	2
Operating Function	On On On

Electrical Characteristics

Contact Current Rating	.3 A
Operating Voltage	125 VAC

Body Features

Actuator Orientation	Side
Actuator Travel	2 mm[.079 in]
Product Orientation	Right Angle
Actuator Profile	Extended
Actuator Material	POM
Actuator Color	Black

Contact Features

Contact Base Material	Copper Alloy
Switch Contact Plating Material	Silver

Termination Features

Termination Post & Tail Length	3 mm[.118 in]
Termination Method to PCB	Through Hole - Solder

Dimensions

Product Length	16 mm[.63 in]
Actuator Length	9.5 mm[.374 in]

Industry Standards

UL Flammability Rating	UL 94HB
------------------------	---------

Packaging Features

Packaging Method	Tray
------------------	------

Other

Grade	Instrumentation
-------	-----------------

Product Compliance

[For compliance documentation, visit the product page on TE.com>](#)

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	有害物质含量符合标准要求 No Restricted Substance(s) Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2025 (250) Candidate List Declared Against: JUNE 2025 (250) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Wave solder capable to 265°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides

on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts



Also in the Series | ALCOSWITCH MSS



Customers Also Bought





TE Part #5-532955-5
30 MODII 2PC CE RCPT ASSY, RoHS



TE Part #5-532956-4
24 MODII 2PC CE RCPT ASSY, RoHS




TE Part #2-1393243-0
RTE25012



TE Part #2-1437664-0
NC6-P107-14=NC6 ASSEMBLY



TE Part #6609028-9
5VK1 M0=F7139



TE Part #5535512-1
12 MODII HORZ DR CE

Documents

Product Drawings

[MSS2250R04=DPDT SL SW R/A AG](#)

English

CAD Files

Customer View Model

[ENG_CVM_CVM_1571630-2_G.3d_igs.zip](#)

English

Customer View Model

[ENG_CVM_CVM_1571630-2_G.3d_stp.zip](#)

English

Customer View Model

[ENG_CVM_CVM_1571630-2_G.2d_dxf.zip](#)

English

3D PDF

3D

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

[SWITCHES_CORE_PROGRAM_CATALOG](#)

English

[8-1773450-9_SWITCHES_CATALOG_SECTION_B_SLIDE_SWITCHES](#)

English