

# Product data sheet

Specifications



## Plain cap, Harmony XB5, Harmony XB4, black, for flush mounted push button

ZBAF2

**Product availability: Stock - Normally stocked in distribution facility**

### Main

|                                       |                         |
|---------------------------------------|-------------------------|
| Accessory / separate part category    | Marking accessory       |
| Accessory / Separate Part Type        | Blank push-button cap   |
| Product or Component Type             | Antimicrobial plain cap |
| Product Compatibility                 | ZB4FA0<br>ZB5FA0        |
| Accessory / separate part destination | Push-button head        |
| Cap/operator or lens colour           | Black                   |
| Shape of signaling unit head          | Round                   |
| Quantity per Set                      | Set of 1                |
| Sale per indivisible quantity         | 10                      |
| Product Weight                        | 0.002 lb(US) (0.001 kg) |

### Complementary

|                     |   |
|---------------------|---|
| Range Compatibility | Harmony XAL<br>Harmony XB5<br>Harmony XB4 |
| Operator profile    | Flush                                     |
| Main group          | Selector switch<br>Push-button            |

### Environment

|           |                             |
|-----------|-----------------------------|
| Standards | ISO 21702<br>ISO 22196:2011 |
|-----------|-----------------------------|

### Ordering and shipping details

|                   |               |
|-------------------|---------------|
| Category          | US10CS222467  |
| Discount Schedule | 0CS2          |
| GTIN              | 3606481340689 |
| Returnability     | Yes           |
| Country of origin | FR            |

### Packing Units

|                        |     |
|------------------------|-----|
| Unit Type of Package 1 | PCE |
| Nbr. of units in pkg.  | 1   |

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

|                                     |                       |
|-------------------------------------|-----------------------|
| <b>Package 1 Height</b>             | 0.79 in (2.000 cm)    |
| <b>Package 1 Width</b>              | 0.98 in (2.500 cm)    |
| <b>Package 1 Length</b>             | 0.98 in (2.500 cm)    |
| <b>Package weight(Lbs)</b>          | 0.071 oz (2.000 g)    |
| <b>Unit Type of Package 2</b>       | BB1                   |
| <b>Number of Units in Package 2</b> | 10                    |
| <b>Package 2 Height</b>             | 1.57 in (4.000 cm)    |
| <b>Package 2 Width</b>              | 2.17 in (5.500 cm)    |
| <b>Package 2 Length</b>             | 2.17 in (5.500 cm)    |
| <b>Package 2 Weight</b>             | 0.847 oz (24.000 g)   |
| <b>Unit Type of Package 3</b>       | S01                   |
| <b>Number of Units in Package 3</b> | 200                   |
| <b>Package 3 Height</b>             | 5.91 in (15.000 cm)   |
| <b>Package 3 Width</b>              | 5.91 in (15.000 cm)   |
| <b>Package 3 Length</b>             | 15.75 in (40.000 cm)  |
| <b>Package 3 Weight</b>             | 23.986 oz (680.000 g) |



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Environmental footprint

Carbon footprint (kg CO2 eq, Total Life cycle) 1

Environmental Disclosure [Product Environmental Profile](#)

## Use Better

### Materials and Substances

Packaging made with recycled cardboard Yes

Packaging without single use plastic Yes

[EU RoHS Directive](#) Pro-active compliance (Product out of EU RoHS legal scope)

REACH Regulation [REACH Declaration](#)

California proposition 65 **WARNING:** This product can expose you to chemicals including: Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

## Use Again

### Repack and remanufacture

Circularity Profile [End of Life Information](#)

Take-back No

Offer Marketing Illustration

Product benefits / Features

---

## Technical Benefits

Harmony XB5

Conformity with IEC, UL, CSA, CCC EAC, and JIS standards, as well as CE marking and marine approvals

Up to IP66, 67, 69, 69K, and type 4X protection ratings

High vibration resistance with shake-proof terminal screws



Operating temperature from -40°C to 70°C

Shock protection level up to IK06

Secure switching of inductive or heavy DC loads directly – 100 000 operations at 10A, 24V dc

Offer Marketing Illustration

Product benefits / Features

---

### Features Harmony XB5



- 

Quick and easy assembly and disassembly
- 

Excellent mechanical connection with operator head
- 

Various types of connection: screw clamp, connector, Faston connector, spring terminal, or printed circuit board
- 

Robustness to withstand harsh environments
- 

Large set of accessories to customize your panels

Image of product / Alternate images

Alternative

---





