

KSC2 DCT Series

Dual Circuit Technology

Tactile Switch for SMT 6.2mm x 6.2mm



Description

The KSC2 DCT series of sealed tactile switches for SMT are IP67 rated, 3.5mm high momentary action tactile switches, featuring a soft actuator. The switches have an operating force of 4.75N +/-1.25N and a lifespan of 300K cycles. The KSC2 series is designed to give users a positive tactile feeling.

Features & Benefits

- SPDT NC-NO function
- Electrical Height for easier integration due to more precise tolerances
- Soft actuator 3.5mm high
- IP67
- Compatible with JEDEC reflow soldering process of SMT devices
- Low halogen, RoHS and REACH compliant
- J bend terminals

Applications

- Industrial electronics
- Consumer products
- Transportation
- Medical

Specifications

Function	Momentary action
Contact Arrangement	2 contacts = SPDT, NC -NO
Terminals	J bend type for SMT
Sealing	IP67

Note: Specifications listed above are for switches with standard options. For information on specific and custom switches, consult Customer Service Center.


Electrical Characteristics

	Activated Position	Released Position
Dielectric Strength (50Hz, 1 min.)	125 Vrms	250 Vrms
Contact Resistance	0.1 Ohm	0.5 Ohm
Insulation Resistance (100V)	1000 MOhm	1000 MOhm
Bounce Time	3 ms	20 ms
Maximum Power	1 VA	0.5 VA
Maximum Voltage	24 V	12 V
Minimum Voltage	0.02 V	0.04 V
Maximum Current	50 mA	25 mA
Minimum Current	1 mA	2 mA

Environmental Characteristics

Operating Temperature	-40°C to 85°C
Storage Temperature	-55°C to 85°C

Dimensions (mm) J Termination




KSC2 DCT Series

Dual Circuit Technology

Tactile Switch for SMT 6.2mm x 6.2mm

**Mechanical Characteristics**



Part #	Operating Force Fa (Newtons)	Operating Life (operations)	Electrical Height from PCB (mm)
KSC2 DCT	4.75 +/- 1.25	300,000	3.2 +/- 0.3

Soldering Profile

Note: Up to 2 reflow cycles in accordance with the above temperature profile

Soldering process: Depending on the application, this component is suited to the following methods:


- Terminals being silver plated over a nickel barrier, the use of slightly activated flux is suitable.
- JEDEC soldering process in accordance with the definition on the left.

J Terminations (mm)

KSC2 DCT Series

Dual Circuit Technology

Tactile Switch for SMT 6.2mm x 6.2mm

**Tape & Reel**Reeling Direction
Out of Production


Scale 0.25

Detail R
Scale 1

See Detail R

Packaging Details

Type	Tape & reel
Number of Parts in Packaging	2,000
Other Information	Tape and reel per EIA 481
Transport Conditions	According to specification NF H00-060

Packaging (mm)**Coupe B-B****Ordering Number**

Our easy build-a-switch concept allows you to mix and match options to create the switch you need. To order, select desired option from each category. However, please note that not all combinations of these options are feasible. For any part number different from those listed below, please consult your local representative.

KSC2 - xx - x - x - DCT - x

Operating Force
4: 3.5 N (350 grams)

Contact Material
1: Silver

LFS: Lead free compatible, silver plated

Dual Circuit Technology

Termination
J: J Bend

Liability Limitation

This datasheet does not provide enough information for applications that require a certain level of quality or safety such as automotive, medical systems, or safety equipment. Please contact customer service for the contractual specification package.

Disclaimer Notice - Information furnished is believed to be accurate and reliable. However, users should independently evaluate the suitability of and test each product selected for their own applications. Littelfuse products are not designed for, and may not be used in, all applications. Read complete Disclaimer Notice at <http://www.littelfuse.com/disclaimer-electronics>.