

MIRO 6.2 pluggable compl. Module Optocoupler

IN: 24 VDC - OUT: 24 VDC / 6 A

Art.No.: 3000-32512-2100040

Weight: 0.026 kg

Country of origin: CZ

Model designation: MIRO 6,2-Opto-Komplettmodul 24/24VDC 6A

Transistor 6 A



24 V DC

Spring clamp terminals

Complete module

[Link to Product](#)

Illustration



Product may differ from Image



Header

Material short text

MIRO 6,2-Opto-Komplettmodul 24/24VDC 6A

Commercial data

URL Webshop	https://shop.murrelektronik.com/3000-32512-2100040
GTIN	4048879532747
ECLASS-6.0	27371604
ECLASS-6.1	27371604
ECLASS-7.0	27371604
ECLASS-7.1	27371604
ECLASS-8.0	27371604
ECLASS-8.1	27371604
ECLASS-9.0	27371604
ECLASS-9.1	27371604
ECLASS-10.0.1	27371604
ECLASS-10.1	27371604
ECLASS-11.0	27371604
ECLASS-11.1	27371604
ECLASS-12.0	27371604
ECLASS-13.0	27371604
ECLASS-14.0	27371604
ETIM-5.0	EC001504
ETIM-6.0	EC001504
ETIM-7.0	EC001504
ETIM-8.0	EC001504
customs tariff number	85365005
EAN	4048879532747
Packaging unit	1

Electrical data | Input

Input voltage DC	24 V
Input voltage DC min.	18 V
Input voltage DC max.	30 V
Input current	9 mA

Electrical data | Output

Forward voltage max.	240 mV
Switch on delay max.	15 μ s
Switch off delay max.	31 μ s
Voltage switching DC min.	3 V
Switching voltage DC max.	30 V
Switching current min.	10 mA
Switching current max.	6 A
Switching frequency ohmic max.	500 Hz
Switching frequency inductive max.	50 Hz

Diagnostics

Status indication LED	yellow
-----------------------	--------

Device protection | Electrical

Degree of protection (EN IEC 60529)	IP20
Rated surge voltage	2,5 kV
Rated insulation voltage	50 V

Mechanical data | Mounting data

Height	93 mm
Width	6,2 mm
Depth	75,6 mm
Mounting method	inserted

Environmental characteristics | Climatic

Operating temperature min.	-25 °C
----------------------------	--------

Operating temperature max. 50 °C

Connection type 5

Family construction form	terminal
No. of poles	1
Gender	female
Color contact carrier	black
Connection	Spring clamp terminals FK
PIN 1	n.c.
Family construction form	terminal
No. of poles	1
Gender	female
Color contact carrier	black
Connection	Spring clamp terminals FK
PIN 1	13
Family construction form	terminal
No. of poles	1
Gender	female
Color contact carrier	black
Connection	Spring clamp terminals FK
PIN 1	14
Family construction form	terminal
No. of poles	1
Gender	female
Color contact carrier	black
Connection	Spring clamp terminals FK
PIN 1	+ A 1
Family construction form	terminal
No. of poles	1
Gender	female
Color contact carrier	black
Connection	Spring clamp terminals FK
PIN 1	- A 2