

RT33K024

✓ ACTIVE

SCHRACK | SCHRACK Power PCB Relay RT1

TE Internal #: 2-1393240-4

General Purpose Power Relay, DC, Monostable, 1 Form A SPST-NO, 16 A Contact Rating, 24 VDC Coil Voltage, SCHRACK Power PCB Relay RT1

[View on TE.com >](#)



Relays & Contactors > Electromechanical Relays



Relay & Contactor Type: **General Purpose Power Relay**

Coil Magnetic System: **Monostable**

Contact Arrangement: **1 Form A SPST-NO**

Current Type: **DC**

Contact Current Rating: **16 A**

Features

Product Type Features

|                        |                             |
|------------------------|-----------------------------|
| Relay & Contactor Type | General Purpose Power Relay |
|------------------------|-----------------------------|

Configuration Features

|                         |                            |
|-------------------------|----------------------------|
| Contact Number of Poles | 1                          |
| Coil Special Features   | UL Coil Insulation Class F |
| Contact Arrangement     | 1 Form A SPST-NO           |

Electrical Characteristics

|                                                     |           |
|-----------------------------------------------------|-----------|
| Contact Limiting Making Current                     | 30 A      |
| Contact Limiting Continuous Current                 | 16 A      |
| Contact Limiting Breaking Current                   | 16 A      |
| Insulation Initial Dielectric Between Open Contacts | 1000 Vrms |
| Contact Switching Voltage (Max)                     | 400 VAC   |
| Coil Resistance                                     | 1440 Ω    |
| Contact Current Rating                              | 16 A      |
| Coil Voltage Rating                                 | 24 VDC    |



|                                                       |           |
|-------------------------------------------------------|-----------|
| Contact Voltage Rating                                | 250 VAC   |
| Coil Power Rating DC                                  | .4 W      |
| Insulation Initial Dielectric Between Contacts & Coil | 5000 Vrms |

Body Features

|                |                                         |
|----------------|-----------------------------------------|
| Product Weight | 14 g[.494 oz]                           |
| Enclosure Type | Flux Resistant Automatic Solder Capable |

Contact Features

|                  |           |
|------------------|-----------|
| Contact Material | AgNi90/10 |
|------------------|-----------|

Termination Features

|                                    |             |
|------------------------------------|-------------|
| Main Termination & Connection Type | Solder Pins |
| Coil Termination & Connection Type | Solder Pins |

Mechanical Attachment

|                    |             |
|--------------------|-------------|
| Product Mount Type | Board Mount |
|--------------------|-------------|

Dimensions

|                                             |                  |
|---------------------------------------------|------------------|
| Insulation Clearance Between Contact & Coil | 10 mm[.394 in]   |
| Insulation Creepage Between Contact & Coil  | 10 mm[.394 in]   |
| Product Width                               | 12.7 mm[.5 in]   |
| Product Length                              | 29 mm[1.141 in]  |
| Product Height                              | 15.7 mm[.618 in] |

Usage Conditions

|                                         |                           |
|-----------------------------------------|---------------------------|
| Operating Temperature Range             | -40 – 85 °C[-40 – 185 °F] |
| Environmental Category of Protection    | RTII                      |
| Environmental Ambient Temperature (Max) | 85 °C[185 °F]             |

Operation/Application

|                      |                     |
|----------------------|---------------------|
| Solder Process       | Wave Solder Capable |
| Coil Magnetic System | Monostable          |
| Current Type         | DC                  |

Packaging Features

|                  |              |
|------------------|--------------|
| Packaging Method | Carton, Tube |
|------------------|--------------|

Other

|                         |             |
|-------------------------|-------------|
| Coil Power Rating Class | >.3 – ≤.6 W |
|-------------------------|-------------|



|                           |                                 |
|---------------------------|---------------------------------|
| Contact Current Class     | >10 – ≤16 A                     |
| Height Class (Mechanical) | >14 – ≤16 mm[>.551 – ≤.63 in]   |
| Length Class (Mechanical) | >22 – ≤33 mm[>.866 – ≤1.299 in] |
| Width Class (Mechanical)  | >11 – ≤14 mm[>.433 – ≤.551 in]  |

Product Compliance

For compliance documentation, visit the product page on TE.com>

|                                               |                                                                                                                                 |
|-----------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------|
| EU RoHS Directive 2011/65/EU                  | Compliant                                                                                                                       |
| EU ELV Directive 2000/53/EC                   | Compliant                                                                                                                       |
| China RoHS 2 Directive MIIT Order No 32, 2016 | 有害物质含量符合标准要求 No Restricted Substance(s) Above Threshold                                                                         |
| EU REACH Regulation (EC) No. 1907/2006        | Current ECHA Candidate List: JUNE 2025 (250)<br>Candidate List Declared Against: JUNE 2025 (250)<br>Does not contain REACH SVHC |
| Halogen Content                               | Not Low Halogen - contains Br or Cl > 900 ppm.                                                                                  |
| Solder Process Capability                     | Wave solder capable to 265°C                                                                                                    |

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts







Also in the Series | **SCHRACK Power PCB Relay RT1**

AC Relays(31)

DC Relays(158)

Electromechanical Relays(189)

Customers Also Bought

TE Part #6-534267-2  
30 MODIV VRT DR DE 100/125

TE Part #4-1393240-8  
RT334024

TE Part #1-1393258-7  
V23047-A1024-A511

TE Part #3-1419108-5  
RTD34012

TE Part #1734101-8  
Champ050 series,80pos,Au over PdNi

TE Part #2-1825059-3  
ADF05ST04=DIP SWT,FLUSH,SMT-GW

TE Part #9-2176070-1  
3521 56K 1% 2W

TE Part #5-5179180-4  
0.8FH,R09H.5,100,08/Sn,TR,SC

TE Part #7-1423008-3  
T92S7D14-24-03

TE Part #7-1768019-3  
EK820

Documents

- CAD Files
- Customer View Model
- [ENG\\_CVM\\_CVM\\_2-1393240-4\\_F.3d\\_igs.zip](#)
- English
- Customer View Model
- [ENG\\_CVM\\_CVM\\_2-1393240-4\\_F.3d\\_stp.zip](#)
- English



3D PDF

3D

Customer View Model

ENG\_CVM\_CVM\_2-1393240-4\_F.2d\_dxf.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

Power PCB Relay RT1 Inrush

English

Product Specifications

Definitions General Purpose Relays

English

Agency Approvals

VDE Certificate

English