

# LC/UPC-LC/UPC Singlemode Duplex Fiber Optic Patch Cable

## Technical Data Sheet

Length (meters)	Yellow with Blue and White Connectors
0.5 m	CM-105090BSTK
1 m	CM-102792BSTK
1.5 m	CM-102807BSTK
2 m	CM-102793BSTK
3 m	CM-102794BSTK
5 m	CM-102795BSTK
6 m	CM-102809BSTK
7 m	CM-102855BSTK
8 m	CM-102810BSTK
9 m	CM-102925BSTK
10 m	CM-102856BSTK
12 m	CM-102926BSTK
15 m	CM-102906BSTK
20 m	CM-102907BSTK
25 m	CM-102908BSTK
30 m	CM-102909BSTK
35 m	CM-102910BSTK
40 m	CM-102911BSTK
50 m	CM-102912BSTK

## Specifications

- 100% tested. Test report included with each cable.
- 1/2 Markers easily identify the TX and RX connector on each end of the assembly

Connector Type	LC-LC Singlemode
Polishing	UPC
Return Loss	55 dB
Insertion Loss	0.30 dB
Ferrule Material	Ceramic (zirconia)
Ferrule Diameter	1.25 mm / 2.5 mm
Body type	Duplex
Nominal Diameter Core	9/125 $\mu$ m
Jacket Material	OFNR
Operation Temperature Range	-20°C +70°C
Cable Diameter	2.0mm