

www.opledtw.com

Opto Plus LED Corp.
0.39" SMD Type LED Display
OPS-D3920SB-2-STT(R)-1.0-G(B)W
OPS-D3921SB-2-STT(R)-1.0-G(B)W

● **EDIT HISTORY**

Version A: Mar. 24, 2025

Preliminary Spec.



www.opledtw.com

Opto Plus LED Corp.

0.39" SMD Type LED Display

OPS-D3920SB-2-STT(R)-1.0-G(B)W

OPS-D3921SB-2-STT(R)-1.0-G(B)W

● FEATURES

- 0.39 inch (10.0 mm) Digit Height.
- Low current operation.
- Excellent character appearance.
- Super thin SMD type.
- RoHS compliant, Pb Free.

● DESCRIPTION

The device are 0.39 inch (10.00 mm) height dual digit 7-segment displays.

The device is Opto Plus LED Corp standard LED Display.

This device utilizes Super Bright Blue LED chip which are made from InGaN

On a transparent GaN, substrate.

The device has face and segment option, please refer to **PRODUCT APPEARANCE**.

● DEVICE

PART NO.	DESCRIPTION
OPS-D3920SB-2-STT-1.0-GW	Common Anode Gray face White segment Top mount
OPS-D3921SB-2-STT-1.0-GW	Common Cathode Gray face White segment Top mount
OPS-D3920SB-2-STT-1.0-BW	Common Anode Black face White segment Top mount
OPS-D3921SB-2-STT-1.0-BW	Common Cathode Black face White segment Top mount
OPS-D3920SB-2-STR-1.0-GW	Common Anode Gray face White segment Reverse mount
OPS-D3921SB-2-STR-1.0-GW	Common Cathode Gray face White segment Reverse mount
OPS-D3920SB-2-STR-1.0-BW	Common Anode Black face White segment Reverse mount
OPS-D3921SB-2-STR-1.0-BW	Common Cathode Black face White segment Reverse mount

RoHS Compliance



Pb Free.



Opto Plus LED Corp. 7F-3, No.496, Bannan Road, Zhonghe Dist., New Taipei City 235, Taiwan (R.O.C)
Website: www.opledtw.com E-mail: sales@opledtw.com Tel: 886-2-2222-5698 Fax: 886-2-2222-2566


Disclaimer:
Subject to change without notice



www.opledtw.com

Opto Plus LED Corp.
0.39" SMD Type LED Display
OPS-D3920SB-2-STT(R)-1.0-G(B)W
OPS-D3921SB-2-STT(R)-1.0-G(B)W

● **MECHANICAL DIMENSIONS**



NOTES: All dimensions are in millimeters. Tolerances are ± 0.25 mm unless otherwise noted.



www.opledtw.com

Opto Plus LED Corp.



0.39" SMD Type LED Display

OPS-D3920SB-2-STT(R)-1.0-G(B)W


OPS-D3921SB-2-STT(R)-1.0-G(B)W

● TYPICAL INTERNAL EQUIVALENT CIRCUIT


Turn On Color




Recommended
Top Mount
Soldering Pattern




Recommended
Reverse Mount
Soldering Pattern



Reflector
(Mounting Hole)




OPS-D3920SB-2-STT(R)-1.0-G(B)W
(Common Anode)



OPS-D3921SB-2-STT(R)-1.0-G(B)W
(Common Cathode)

※EMITTED COLOR : SUPER BRIGHT BLUE



www.opledtw.com

Opto Plus LED Corp.
0.39" SMD Type LED Display
OPS-D3920SB-2-STT(R)-1.0-G(B)W
OPS-D3921SB-2-STT(R)-1.0-G(B)W

● **PRODUCT APPEARANCE**


The most common reflector color and segment color are show in below diagram.

-GW	-BW
※ REFLECTOR COLOR: Gray ※ SEGMENT COLOR: White	※ REFLECTOR COLOR: Black ※ SEGMENT COLOR: White

Opto Plus can customize reflector and segment colors by customer's request. If you have these request please visit www.opledtw.com or contact sales@opledtw.com for more **Standard Product Customization** information.

Part NO. related to reflector and segment colors show as table below.

PART NO.	DESCRIPTION
OPS-D3920SB-2-STT-1.0-GW	Common Anode Gray face White segment Top mount
OPS-D3921SB-2-STT-1.0-GW	Common Cathode Gray face White segment Top mount
OPS-D3920SB-2-STT-1.0-BW	Common Anode Black face White segment Top mount
OPS-D3921SB-2-STT-1.0-BW	Common Cathode Black face White segment Top mount
OPS-D3920SB-2-STR-1.0-GW	Common Anode Gray face White segment Reverse mount
OPS-D3921SB-2-STR-1.0-GW	Common Cathode Gray face White segment Reverse mount
OPS-D3920SB-2-STR-1.0-BW	Common Anode Black face White segment Reverse mount
OPS-D3921SB-2-STR-1.0-BW	Common Cathode Black face White segment Reverse mount



www.opledtw.com

Opto Plus LED Corp.
0.39" SMD Type LED Display
OPS-D3920SB-2-STT(R)-1.0-G(B)W
OPS-D3921SB-2-STT(R)-1.0-G(B)W


● **SB: SUPER BRIGHT BLUE (InGaN/GaN)**

ABSOLUTE MAXIMUM RATING AT Ta=25°C

Parameter	Symbol	Maximum Rating	Unit
Power dissipation	P _{AD}	90	mW
Continuous forward current	I _{AF}	30	mA
Peak current (duty cycle 1/10, 1kHz)	I _{PF}	60	mA
Reverse voltage	V _R	5	V
Operating temperature	T _{OPR}	-40 to +105	°C
Storage temperature	T _{STG}	-40 to +105	°C

ELECTRICAL - OPTICAL CHARACTERISTICS AT Ta=25°C

Characteristic	Symbol	Condition	Min.	Type.	Max.	Unit
Forward Voltage, (Per Dice)	V _F	I _F = 20mA	-	3.0	3.4	V
Reverse Current, (Per Dice)	I _R	V _R = 5V	-	-	10	μA
Dominant Wavelength	λ _D	I _F = 20mA	464	-	474	nm
Luminous Intensity	I _v	I _F = 20mA	15	-	50	mcd
Spectral Line Half-Bandwidth	Δλ	I _F = 20mA	-	20	-	nm



www.opledtw.com

Opto Plus LED Corp.
0.39" SMD Type LED Display
OPS-D3920SB-2-STT(R)-1.0-G(B)W
OPS-D3921SB-2-STT(R)-1.0-G(B)W

● **SB: BIN GRADE (Unit : mcd) 20mA**

Super Bright Blue	H	I	J
	15.0 – 27.0	27.1 – 38.0	38.1 – 50.0

● **SB: HUE GRADE (λ_D : nm)**

1	2	3
464.0 - 467.0	467.1 - 470.0	470.1 - 474.0

● **AVAILABLE BIN / HUE TABLE**

H1	I1	J1
H2	I2	J2
H3	I3	J3



www.opledtw.com

Opto Plus LED Corp.

0.39" SMD Type LED Display

OPS-D3920SB-2-STT(R)-1.0-G(B)W

OPS-D3921SB-2-STT(R)-1.0-G(B)W

● SB: SUPER BRIGHT BLUE (InGaN/GaN) CURVE

Typical Electro-optical Characteristic Curves
(25 °C Free Air Temperature Unless Otherwise Specified)




Fig.1-Relative Intensity VS. Wavelength




Fig.2-Relative Luminous Intensity vs. Forward Current




Fig.3-Forward Current vs. Forward Voltage




Fig.4-Relative Intensity(@20mA)VS. Ambient Temperature




Fig.5-Forward Voltage(@20mA)VS. Ambient Temperature




Fig.6-Dominant Wavelength(@20mA) VS. Ambient Temperature




Fig.7-Max. Allowable DC Current VS. Ambient Temperature




www.opledtw.com

Opto Plus LED Corp.
0.39" SMD Type LED Display
OPS-D3920SB-2-STT(R)-1.0-G(B)W
OPS-D3921SB-2-STT(R)-1.0-G(B)W

● **SMT REFLOW SOLDERING INSTRUCTIONS**

SMT Soldering Profile

Pb free reflow soldering Profile



- We recommend the reflow temperature 245°C (+/- 5°C).
The maximum soldering temperature should be limited to 260°C.
- Number of reflow process shall be 2 times or less.

● **SOLDERING IRON**

Basic spec is ≤ 4 sec when 260°C. If temperature is higher, time should be shorter (+10°C → 1 sec). Power dissipation of Iron should be smaller than 15W, and temperature should be controllable. Surface temperature of the device should be under 230°C.

● **REWORK**

- Customer must finish rework within 3 sec. under 350°C.
- The head of soldering iron cannot touch copper foil.



www.opledtw.com


Opto Plus LED Corp.

0.39" SMD Type LED Display

OPS-D3920SB-2-STT(R)-1.0-G(B)W

OPS-D3921SB-2-STT(R)-1.0-G(B)W

● REEL DIMENSIONS



● PACKING & LABEL SPECIFICATIONS

OPS-D3920(1)XX-2-STT-1.0-BW Top Mount	OPS-D3920(1)XX-2-STR-1.0-BW Reverse Mount	OPS-D3920(1)XX-2-STT-1.0-BW OPS-D3920(1)XX-2-STR-1.0-BW
<p>Circle</p> <p>Ellipse</p> <p>750PCS / 1REEL</p>	<p>Circle</p> <p>Ellipse</p> <p>750PCS / 1REEL</p>	<p>1REEL / 1 SILVER ESD BAG 450X430 mm</p> <p>OUTSIDE LABEL</p> <p>7REEL / 1BOX 5250PCS / 1BOX BOX SIZE: 430X390X300 mm</p>

● STORAGE CONDITION

In factory original sealed bag package

TEMPERATURE CONDITION	HUMIDITY CONDITION
5°C ~ 30°C	Below 60%RH

After opened and not in factory original sealed bag package

TEMPERATURE CONDITION	HUMIDITY CONDITION	STORAGE TIME
5°C ~ 30°C	Below 60%RH	Within 4 weeks (MSL as level 2a)