



Opto Plus LED Corp.
0.28" SMD Type LED Display
OPS-T2812SB | OPS-T2811SB

● **EDIT HISTORY**

Version A: Nov. 17, 2020

Preliminary Spec.



Opto Plus LED Corp.

0.28" SMD Type LED Display

OPS-T2812SB | OPS-T2811SB

● FEATURES

- 0.28 inch (7.00 mm) Digit Height.
- SMD type.
- Low current operation.
- RoHS Compliant, Pb Free.

● DESCRIPTION

The device are 0.28 inch (7.00 mm) height quadruple digit 7-segment displays.

The device is Opto Plus LED Corp standard LED Display.

This device utilizes Super Bright Blue LED chip which are made from InGaN

On a transparent GaN, substrate.

The device has face and segment option, please refer to **PRODUCT APPEARANCE**.

● DEVICE


PART NO.		DESCRIPTION
	OPS-Q2818SB-GW	Common Anode Gray face White segment
	OPS-Q2817SB-GW	Common Cathode Gray face White segment
	OPS-Q2818SB-BW	Common Anode Black face White segment
	OPS-Q2817SB-BW	Common Cathode Black face White segment

RoHS Compliance




Pb Free.








● TYPICAL INTERNAL EQUIVALENT CIRCUIT


Recommended
Soldering Pattern



Turn On Color



OPS-Q2818 (Common Anode)





OPS-Q2817 (Common Cathode)

※EMITTED COLOR : SUPER BRIGHT BLUE

● PRODUCT APPEARANCE

The most common reflector color and segment color are show in below diagram.

-GW	-BW
	
※ REFLECTOR COLOR: Gray ※ SEGMENT COLOR: White	※ REFLECTOR COLOR: Black ※ SEGMENT COLOR: White

Opto Plus can customize reflector and segment colors by customer's request. If you have these request please visit www.opledtw.com or contact sales@opledtw.com for more **Standard Product Customization** information.

Part NO. related to reflector and segment colors show as table below.

PART NO.	DESCRIPTION
OPS-Q2818SB-GW	Common Anode Gray face White segment
OPS-Q2817SB-GW	Common Cathode Gray face White segment
OPS-Q2818SB-BW	Common Anode Black face White segment
OPS-Q2817SB-BW	Common Cathode Black face White segment



Opto Plus LED Corp.

0.28" SMD Type LED Display

OPS-T2812SB | OPS-T2811SB

● SB: SUPER BRIGHT BLUE (InGaN/GaN)

ABSOLUTE MAXIMUM RATING AT Ta=25°C

Parameter	Symbol	Maximum Rating	Unit
Power dissipation	P _{AD}	90	mW
Continuous forward current	I _{AF}	30	mA
Peak current (duty cycle 1/10, 1kHz)	I _{PF}	60	mA
Reverse voltage	V _R	5	V
Operating temperature	T _{OPR}	-40 to +105	°C
Storage temperature	T _{STG}	-40 to +105	°C

ELECTRICAL - OPTICAL CHARACTERISTICS AT Ta=25°C

Characteristic	Symbol	Condition	Min.	Type.	Max.	Unit
Forward Voltage, (Per Dice)	V _F	I _F =20mA	-	3.0	3.4	V
Reverse Current, (Per Dice)	I _R	V _R =5V	-	-	10	μA
Dominant Wavelength	λ _D	I _F =20mA	464	-	474	nm
Luminous Intensity	I _v	I _F =20mA	25	38	55	mcd
Spectral Line Half-Bandwidth	Δλ	I _F =20mA	-	20	-	nm



Opto Plus LED Corp.

0.28" SMD Type LED Display

OPS-T2812SB | OPS-T2811SB

● SB: BIN GRADE (Unit : mcd) 20mA

	J	K	L
Super Bright Blue	25.0 – 33.0	33.1 – 43.0	43.1 – 55.0

● SB: Hue grade (λ_D : nm)

1	2	3
464.0 - 467.0	467.1 - 470.0	470.1 - 474.0

● AVAILABLE BIN / HUE TABLE

J1	J2	J3
K1	K2	K3
L1	L2	L3

● SB: SUPER BRIGHT BLUE (InGaN/GaN) CURVE

Typical Electro-optical Characteristic Curves
(25 °C Free Air Temperature Unless Otherwise Specified)




Fig.1-Relative Intensity VS. Wavelength




Fig.2-Relative Luminous Intensity vs. Forward Current




Fig.3-Forward Current vs. Forward Voltage




Fig.4-Relative Intensity(@20mA)VS. Ambient Temperature




Fig.5-Forward Voltage(@20mA)VS. Ambient Temperature




Fig.6-Dominant Wavelength(@20mA)
VS. Ambient Temperature





Fig.7-Max. Allowable DC Current
VS. Ambient Temperature

● SMT REFLOW SOLDERING INSTRUCTIONS

SMT Soldering Profile

Pb free reflow soldering Profile



- We recommend the reflow temperature 245°C (+/- 5°C).
 The maximum soldering temperature should be limited to 260°C.
- Number of reflow process shall be 2 times or less.


● SOLDERING IRON

Basic spec is ≤4 sec when 260°C. If temperature is higher, time should be shorter (+10°C→1 sec). Power dissipation of Iron should be smaller Than 15W, and temperature should be controllable. Surface temperature Of the device should be under 230°C.


● REWORK

- Customer must finish rework within 3 sec. under 350°C.
- The head of soldering iron cannot touch copper foil.

● REEL DIMENSIONS



● PACKING & LABEL SPECIFICATIONS



● STORAGE CONDITION

In factory original sealed bag package

TEMPERATURE CONDITION	HUMIDITY CONDITION
5°C ~ 30°C	Below 60%RH

After opened and not in factory original sealed bag package

TEMPERATURE CONDITION	HUMIDITY CONDITION	STORAGE TIME
5°C ~ 30°C	Below 60%RH	Within 4 weeks (MSL as level 2a)