




[www.opledtw.com](http://www.opledtw.com)

**Opto Plus LED Corp.**  
**0.39" SMD Type LED Display**  
**OPS-S3920SPG-STT(R)-1.0-G(B)W**  
**OPS-S3921SPG-STT(R)-1.0-G(B)W**

● **EDIT HISTORY**

Version A: Mar. 24, 2025

Preliminary Spec.



[www.opledtw.com](http://www.opledtw.com)

# Opto Plus LED Corp.

## 0.39" SMD Type LED Display

### OPS-S3920SPG-STT(R)-1.0-G(B)W

### OPS-S3921SPG-STT(R)-1.0-G(B)W

#### ● FEATURES

- 0.39 inch (10.0 mm) Digit Height.
- Low current operation.
- Excellent character appearance.
- Super thin SMD type.
- RoHS compliant, Pb Free.

#### ● DESCRIPTION

The device are 0.39 inch (10.00 mm) height single digit 7-segment displays.

The device is Opto Plus LED Corp standard LED Display.

This device utilizes Pure Green LED chip which are made from InGaN on a Transparent GaN, substrate.

The device has face and segment option, please refer to **PRODUCT APPEARANCE**.

#### ● DEVICE

PART NO.	DESCRIPTION
OPS-S3920SPG-STT-1.0-GW	Common Anode   Gray face   White segment   Top mount
OPS-S3921SPG-STT-1.0-GW	Common Cathode   Gray face   White segment   Top mount
OPS-S3920SPG-STT-1.0-BW	Common Anode   Black face   White segment   Top mount
OPS-S3921SPG-STT-1.0-BW	Common Cathode   Black face   White segment   Top mount
OPS-S3920SPG-STR-1.0-GW	Common Anode   Gray face   White segment   Reverse mount
OPS-S3921SPG-STR-1.0-GW	Common Cathode   Gray face   White segment   Reverse mount
OPS-S3920SPG-STR-1.0-BW	Common Anode   Black face   White segment   Reverse mount
OPS-S3921SPG-STR-1.0-BW	Common Cathode   Black face   White segment   Reverse mount

**RoHS Compliance**



**Pb Free.**



Opto Plus LED Corp. 7F-3, No.496, Bannan Road, Zhonghe Dist., New Taipei City 235, Taiwan (R.O.C)  
Website: [www.opledtw.com](http://www.opledtw.com) E-mail: [sales@opledtw.com](mailto:sales@opledtw.com) Tel: 886-2-2222-5698 Fax: 886-2-2222-2566


Disclaimer:  
Subject to change without notice



[www.opledtw.com](http://www.opledtw.com)

**Opto Plus LED Corp.**  
**0.39" SMD Type LED Display**  
**OPS-S3920SPG-STT(R)-1.0-G(B)W**  
**OPS-S3921SPG-STT(R)-1.0-G(B)W**

● **MECHANICAL DIMENSIONS**



NOTES: All dimensions are in millimeters. Tolerances are  $\pm 0.25$  mm unless otherwise noted.



[www.opledtw.com](http://www.opledtw.com)


# Opto Plus LED Corp.

## 0.39" SMD Type LED Display


### OPS-S3920SPG-STT(R)-1.0-G(B)W

### OPS-S3921SPG-STT(R)-1.0-G(B)W

#### ● TYPICAL INTERNAL EQUIVALENT CIRCUIT



※EMITTED COLOR : PURE GREEN





[www.opledtw.com](http://www.opledtw.com)

**Opto Plus LED Corp.**  
**0.39" SMD Type LED Display**  
**OPS-S3920SPG-STT(R)-1.0-G(B)W**  
**OPS-S3921SPG-STT(R)-1.0-G(B)W**

● **PRODUCT APPEARANCE**


The most common reflector color and segment color are show in below diagram.

-GW	-BW
	
※ REFLECTOR COLOR: Gray ※ SEGMENT COLOR: White	※ REFLECTOR COLOR: Black ※ SEGMENT COLOR: White

Opto Plus can customize reflector and segment colors by customer's request. If you have these request please visit [www.opledtw.com](http://www.opledtw.com) or contact [sales@opledtw.com](mailto:sales@opledtw.com) for more **Standard Product Customization** information.

Part NO. related to reflector and segment colors show as table below.

PART NO.	DESCRIPTION
OPS-S3920SPG-STT-1.0-GW	Common Anode   Gray face   White segment   Top mount
OPS-S3921SPG-STT-1.0-GW	Common Cathode   Gray face   White segment   Top mount
OPS-S3920SPG-STT-1.0-BW	Common Anode   Black face   White segment   Top mount
OPS-S3921SPG-STT-1.0-BW	Common Cathode   Black face   White segment   Top mount
OPS-S3920SPG-STR-1.0-GW	Common Anode   Gray face   White segment   Reverse mount
OPS-S3921SPG-STR-1.0-GW	Common Cathode   Gray face   White segment   Reverse mount
OPS-S3920SPG-STR-1.0-BW	Common Anode   Black face   White segment   Reverse mount
OPS-S3921SPG-STR-1.0-BW	Common Cathode   Black face   White segment   Reverse mount



[www.opledtw.com](http://www.opledtw.com)

**Opto Plus LED Corp.**  
**0.39" SMD Type LED Display**  
**OPS-S3920SPG-STT(R)-1.0-G(B)W**  
**OPS-S3921SPG-STT(R)-1.0-G(B)W**

● **SPG: PURE GREEN (InGaN/GaN)**

ABSOLUTE MAXIMUM RATING AT Ta=25°C

Parameter	Symbol	Maximum Rating	Unit
Power dissipation	P <sub>AD</sub>	90	mW
Continuous forward current	I <sub>AF</sub>	30	mA
Peak current (duty cycle 1/10, 1kHz)	I <sub>PF</sub>	60	mA
Reverse voltage	V <sub>R</sub>	5	V
Operating temperature	T <sub>OPR</sub>	-40 to +105	°C
Storage temperature	T <sub>STG</sub>	-40 to +105	°C

ELECTRICAL - OPTICAL CHARACTERISTICS AT Ta=25°C

Characteristic	Symbol	Condition	Min.	Type.	Max.	Unit
Forward Voltage, (Per Dice)	V <sub>F</sub>	I <sub>F</sub> =20mA	-	3.0	3.4	V
Reverse Current, (Per Dice)	I <sub>R</sub>	V <sub>R</sub> =5V	-	-	10	µA
Dominant Wavelength	λ <sub>D</sub>	I <sub>F</sub> =20mA	515	-	530	nm
Luminous Intensity	I <sub>v</sub>	I <sub>F</sub> =20mA	100	-	400	mcd
Spectral Line Half-Bandwidth	Δλ	I <sub>F</sub> =20mA	-	30	-	nm



[www.opledtw.com](http://www.opledtw.com)

**Opto Plus LED Corp.**  
**0.39" SMD Type LED Display**  
**OPS-S3920SPG-STT(R)-1.0-G(B)W**  
**OPS-S3921SPG-STT(R)-1.0-G(B)W**

● **SPG: BIN GRADE (Unit : mcd ) 20mA**

PURE GREEN	Q	R	S
	100.0 – 200.0	200.1 – 300.0	300.1 – 400.0

● **SPG: HUE GRADE ( $\lambda_D$  : nm)**

1	2	3
515.0 – 520.0	520.1 – 525.0	525.1 – 530.0

● **AVAILABLE BIN / HUE TABLE**

Q1	R1	S1
Q2	R2	S2
Q3	R3	S3



[www.opledtw.com](http://www.opledtw.com)

# Opto Plus LED Corp.

## 0.39" SMD Type LED Display

### OPS-S3920SPG-STT(R)-1.0-G(B)W

### OPS-S3921SPG-STT(R)-1.0-G(B)W

## ● SPG: PURE GREEN (InGaN/GaN) CURVE

Typical Electro-optical Characteristic Curves  
(25 °C Free Air Temperature Unless Otherwise Specified)




Fig.-1 Relative Intensity VS. Wavelength




Fig.2-Relative Luminous Intensity vs. Forward Current




Fig.3-Forward Current vs. Forward Voltage




Fig.4-Relative Intensity(@20mA)VS. Ambient Temperature




Fig.5-Forward Voltage(@20mA)VS. Ambient Temperature




Fig.6-Dominant Wavelength(@20mA)  
VS. Ambient Temperature




Fig.7-Max. Allowable DC Current  
VS. Ambient Temperature



[www.opledtw.com](http://www.opledtw.com)

# Opto Plus LED Corp.

## 0.39" SMD Type LED Display


### OPS-S3920SPG-STT(R)-1.0-G(B)W

### OPS-S3921SPG-STT(R)-1.0-G(B)W

## ● SMT REFLOW SOLDERING INSTRUCTIONS

SMT Soldering Profile

Pb free reflow soldering Profile



- We recommend the reflow temperature 245°C (+/- 5°C).  
The maximum soldering temperature should be limited to 260°C.
- Number of reflow process shall be 2 times or less.

## ● SOLDERING IRON

Basic spec is  $\leq 4$  sec when 260°C. If temperature is higher, time should be shorter (+10°C → 1 sec). Power dissipation of Iron should be smaller than 15W, and temperature should be controllable. Surface temperature of the device should be under 230°C.

## ● REWORK

- Customer must finish rework within 3 sec. under 350°C.
- The head of soldering iron cannot touch copper foil.



[www.opledtw.com](http://www.opledtw.com)


# Opto Plus LED Corp.

## 0.39" SMD Type LED Display

### OPS-S3920SPG-STT(R)-1.0-G(B)W

### OPS-S3921SPG-STT(R)-1.0-G(B)W

### ● REEL DIMENSIONS



### ● PACKING & LABEL SPECIFICATIONS

OPS-S3920(1)XX-STT-1.0-BW Top Mount	OPS-S3920(1)XX-STR-1.0-BW Reverse Mount	OPS-S3920(1)XX-STT-1.0-BW OPS-S3920(1)XX-STR-1.0-BW
<p>Diagram showing the top mount LED display with a label and hot seal.</p>	<p>Diagram showing the reverse mount LED display with a label and hot seal.</p>	<p>Diagram showing the packaging process: 1 REEL / 1 SILVER ESD BAG (450X430 mm) and a box with an OUTSIDE LABEL.</p>
<p>Circle Ellipse 1200PCS / 1REEL</p>	<p>Circle Ellipse 1200PCS / 1REEL</p>	<p>7REEL / 1BOX 8400PCS / 1BOX BOX SIZE: 430X390X300 mm</p>

### ● STORAGE CONDITION

In factory original sealed bag package

TEMPERATURE CONDITION	HUMIDITY CONDITION
5°C ~ 30°C	Below 60%RH

After opened and not in factory original sealed bag package

TEMPERATURE CONDITION	HUMIDITY CONDITION	STORAGE TIME
5°C ~ 30°C	Below 60%RH	Within 4 weeks (MSL as level 2a)