

www.opledtw.com

Opto Plus LED Corp.
0.51" SMD Type LED Display
OPS-T5116SY | OPS-T5117SY

● **EDIT HISTORY**

Version A: Jun. 05, 2024

Preliminary Spec.

Confidential Document



Opto Plus LED Corp.

0.51" SMD Type LED Display

OPS-T5116SY | OPS-T5117SY

● FEATURES

- 0.51 inch (13.00 mm) digit height.
- SMD type.
- Low current operation.
- RoHS Compliant, Pb Free.

● DESCRIPTION

The device are 0.51 inch (13.00 mm) height triple digit 7-segment displays.

The device is Opto Plus LED Corp standard LED Display.

This device utilizes Super Bright Yellow LED chip which are made from AlGaInP
On a transparent GaAs, substrate.

The device has face and segment option, please refer to **PRODUCT APPEARANCE**.

● DEVICE

PART NO.	DESCRIPTION
OPS-T5116SY-GW	Common Anode Gray face White segment
OPS-T5117SY-GW	Common Cathode Gray face White segment
OPS-T5116SY-BW	Common Anode Black face White segment
OPS-T5117SY-BW	Common Cathode Black face White segment

RoHS Compliance



Pb Free.






Opto Plus LED Corp.

0.51" SMD Type LED Display

OPS-T5116SY | OPS-T5117SY



● MECHANICAL DIMENSIONS






NOTES: All dimensions are in millimeters. Tolerances are ± 0.25 mm unless otherwise noted.

● TYPICAL INTERNAL EQUIVALENT CIRCUIT

Turn On Color



Recommended Soldering Pattern





※EMITTED COLOR : SUPER BRIGHT YELLOW



Opto Plus LED Corp. 0.51" SMD Type LED Display OPS-T5116SY | OPS-T5117SY

● PRODUCT APPEARANCE

The most common reflector color and segment color are show in below diagram.

-GW	-BW
	
※ REFLECTOR COLOR: Gray ※ SEGMENT COLOR: White	※ REFLECTOR COLOR: Black ※ SEGMENT COLOR: White

Opto Plus can customize reflector and segment colors by customer's request. If you have these request please visit www.opledtw.com or contact sales@opledtw.com for more **Standard Product Customization** information.

Part NO. related to reflector and segment colors show as table below.

	PART NO.	DESCRIPTION
	OPS-T5116SY-GW	Common Anode Gray face White segment
	OPS-T5117SY-GW	Common Cathode Gray face White segment
	OPS-T5116SY-BW	Common Anode Black face White segment
	OPS-T5117SY-BW	Common Cathode Black face White segment



Opto Plus LED Corp.
0.51" SMD Type LED Display
OPS-T5116SY | OPS-T5117SY

● **SY: SUPER BRIGHT YELLOW (AlGaInP/GaAs)**

ABSOLUTE MAXIMUM RATING AT Ta=25°C

Parameter	Symbol	Maximum Rating	Unit
Power dissipation	P_{AD}	48	mW
Continuous forward current	I_{AF}	20	mA
Peak current (duty cycle 1/10, 1kHz)	I_{PF}	40	mA
Reverse voltage	V_R	5	V
Operating temperature	T_{OPR}	-40 to +105	°C
Storage temperature	T_{STG}	-40 to +105	°C

ELECTRICAL - OPTICAL CHARACTERISTICS AT Ta=25°C

Characteristic	Symbol	Condition	Min.	Type.	Max.	Unit
Forward Voltage, (Per Dice)	V_F	$I_F = 20\text{mA}$	-	2.1	2.4	V
Reverse Current, (Per Dice)	I_R	$V_R = 5\text{V}$	-	-	10	μA
Peak Wavelength	λ_P	$I_F = 20\text{mA}$	-	593	-	nm
Dominant Wavelength	λ_D	$I_F = 20\text{mA}$	585	-	595	nm
Luminous Intensity	I_V	$I_F = 20\text{mA}$	15	-	60	mcd
Spectral Line Half-Bandwidth	$\Delta\lambda$	$I_F = 20\text{mA}$	-	20	-	nm



Opto Plus LED Corp.
0.51" SMD Type LED Display
OPS-T5116SY | OPS-T5117SY

- SY: BIN GRADE (Unit : mcd) 20mA

Super Bright Yellow	I	J	K
	15.0 – 30.0	30.1 – 45.0	45.1 - 60.0

- SY: HUE GRADE (λ_D : nm)

1	2	3
585.0 – 588.0	588.1 – 592.0	592.1 – 595.0

- AVAILABLE BIN / HUE TABLE

I1	I2	I3
J1	J2	J3
K1	K2	K3



Opto Plus LED Corp.

0.51" SMD Type LED Display

OPS-T5116SY | OPS-T5117SY

● SY: SUPER BRIGHT YELLOW (AlGaInP/GaAs) CURVE

Typical Electro-optical Characteristic Curves
(25 °C Free Air Temperature Unless Otherwise Specified)




Fig.1-Relative Intensity VS. Wavelength




Fig.2-Relative Luminous Intensity vs. Forward Current




Fig.3-Forward Current vs. Forward Voltage




Fig.4-Relative Intensity(@20mA) vs. Ambient Temperature




Fig.5-Forward Voltage(@20mA) vs. Ambient Temperature




Fig.6-Dominant Wavelength(@20mA)
VS. Ambient Temperature




Fig.7-Max. Allowable DC Current
VS. Ambient Temperature



www.opledtw.com

Opto Plus LED Corp.


0.51" SMD Type LED Display

OPS-T5116SY | OPS-T5117SY

● SMT REFLOW SOLDERING INSTRUCTIONS

SMT Soldering Profile

Pb free reflow soldering Profile



- We recommend the reflow temperature 245°C (+/- 5°C).
The maximum soldering temperature should be limited to 260°C.
- Number of reflow process shall be 2 times or less.

● SOLDERING IRON

Basic spec is ≤ 4 sec when 260°C. If temperature is higher, time should be shorter (+10°C → 1 sec). Power dissipation of Iron should be smaller than 15W, and temperature should be controllable. Surface temperature of the device should be under 230°C.

● REWORK

- Customer must finish rework within 3 sec. under 350°C.
- The head of soldering iron cannot touch copper foil.




Opto Plus LED Corp.


0.51" SMD Type LED Display

OPS-T5116SY | OPS-T5117SY

● REEL DIMENSIONS



● PACKING & LABEL SPECIFICATIONS



● STORAGE CONDITION

In factory original sealed bag package

TEMPERATURE CONDITION	HUMIDITY CONDITION
5°C ~ 30°C	Below 60%RH

After opened and not in factory original sealed bag package

TEMPERATURE CONDITION	HUMIDITY CONDITION	STORAGE TIME
5°C ~ 30°C	Below 60%RH	Within 4 weeks (MSL as level 2a)