

FL SFP GT - Media module



2989420

<https://www.phoenixcontact.com/us/products/2989420>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Gigabit SFP module for transmission up to 100 m.



Product description

SFP module with a data transmission speed of 1000 Mbps and a maximum transmission length of 100 m.

Your advantages

- MSA compliant

Commercial data

Item number	2989420
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	DN22
Product key	DNN623
GTIN	4046356346122
Weight per piece (including packing)	33 g
Weight per piece (excluding packing)	33 g
Customs tariff number	85176200
Country of origin	TW

FL SFP GT - Media module



2989420

<https://www.phoenixcontact.com/us/products/2989420>

Technical data

Dimensions

Width	13.7 mm
Height	8.95 mm
Length	56.5 mm

Notes

Note on application

Note on application	Only for industrial use
---------------------	-------------------------

Material specifications

Housing material	Metal
------------------	-------

Mounting

Mounting type	Insert in SFP slot
---------------	--------------------

Interfaces

Ethernet (RJ45)

Connection method	RJ45
Transmission speed	1 Gbps
Transmission physics	Copper
Transmission length	100 m (per segment)
Signal LEDs	depending on the Factoryline device
No. of channels	1 (RJ45 port)

Product properties

Product type	SFP module
Type	Factoryline devices with SFP slot
Format	SFP (Small Form-factor Pluggable)
Basic functions	SFP module as copper port

Signaling

Status display	via a Factoryline device
----------------	--------------------------

Electrical properties

Current consumption	375 mA
Maximum power dissipation for nominal condition	1.24 W
Transmission medium	Copper

Supply

Supply voltage	3.3 V (via Factoryline switch)
Power supply connection	via SFP slot
Max. current consumption	375 mA

FL SFP GT - Media module

2989420

<https://www.phoenixcontact.com/us/products/2989420>



Current consumption	375 mA
---------------------	--------

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	-40 °C ... 85 °C (non-condensing)
Ambient temperature (storage/transport)	-40 °C ... 85 °C (non-condensing)
Permissible humidity (operation)	5 % ... 95 %

FL SFP GT - Media module



2989420

<https://www.phoenixcontact.com/us/products/2989420>

Classifications

ECLASS

ECLASS-13.0	19179090
ECLASS-15.0	19179090

ETIM

ETIM 9.0	EC000310
----------	----------

UNSPSC

UNSPSC 21.0	43222600
-------------	----------

FL SFP GT - Media module



2989420

<https://www.phoenixcontact.com/us/products/2989420>

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes, No exemptions
---	--------------------

China RoHS

Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits

EU REACH SVHC

REACH candidate substance (CAS No.)	No substance above 0.1 wt%
-------------------------------------	----------------------------

Phoenix Contact 2025 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com