

Specifications



Photo is representative

Eaton 11155AA14

Eaton Prism series Tubular photoelectric sensor, Photoelectric, 0.71 diameter, Forward Viewing, Sensor distance: 20 Ft., 6.6 Ft. (2m) Cable, 20-132 Vac/15-30 Vdc input, Thru-beam, 6.6 Ft. (2m)

General specifications

PRODUCT NAME	Eaton OEM Prism 18mm tubular photoelectric sensor
CATALOG NUMBER	11155AA14
UPC	782113056524
PRODUCT LENGTH/DEPTH	0.47 in
PRODUCT HEIGHT	2.35 in
PRODUCT WIDTH	0.71 in
PRODUCT WEIGHT	0.2 lb
WARRANTY	3 year
COMPLIANCES	CE Marked
CERTIFICATIONS	UL Recognized cUL Recognized
CATALOG NOTES	Synchronous design requires source and detector to be wired to each other



Powering Business Worldwide

Product specifications

CABLE TYPE	Polyvinyl Chloride (PVC)
ENCLOSURE MATERIAL	Body: structural polyurethane foam Cable jacket: PVC Lens: polycarbonate
OPERATING MODE	Thru-beam
CONNECTION	6.6 ft (2 m) cable
SENSOR TYPE	Through beam
SWITCH TYPE	Photoelectric
INPUT VOLTAGE	20-132 Vac, 15-30 Vdc
LED INDICATOR	Power on: red
CORD LENGTH	79.2 ft
OPERATING TEMPERATURE - MAX	131 °F
OPERATING TEMPERATURE - MIN	-13 °F
ENVIRONMENTAL RATING	NEMA 1, NEMA 3, NEMA 4, NEMA 4X, NEMA 6, NEMA 6P, NEMA 12, NEMA 13

Resources

CATALOGS	Sensing Solutions, Photoelectric Sensor, Volume 8, Tab 5
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - 11155AA14

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

