

Specifications



Photo is representative

Eaton 12155AF07D10

Eaton OEM Prism 18mm tubular photoelectric sensor, Forward Viewing, Sensor distance: 20 Ft., Iso SS Relay, 80 mA at 132 Vac/110 mA at 132Vdc, 10 Ft. (3m) Cable, Current Limited for loads >32V AC/DC, Thru-beam, 7 Ft. (2.1m)

General specifications

PRODUCT NAME	Eaton OEM Prism 18mm tubular photoelectric sensor
CATALOG NUMBER	12155AF07D10
UPC	782114023686
PRODUCT LENGTH/DEPTH	0.47 in
PRODUCT HEIGHT	2.6 in
PRODUCT WIDTH	0.71 in
PRODUCT WEIGHT	0.2875 lb
WARRANTY	3 year
COMPLIANCES	Contact Manufacturer



Powering Business Worldwide

Product specifications

CONTACT RATING	80 mA at 132 Vac / 110 mA at 132Vdc
CABLE TYPE	Polyvinyl Chloride (PVC)
ENCLOSURE MATERIAL	Cable jacket: PVC Lens: polycarbonate Body: structural polyurethane foam
OPERATING MODE	Thru-beam
CONNECTION	10 ft (3 m) cable
CONTACT CONFIGURATION	Isolated solid state relay
SENSOR TYPE	Through beam
SWITCH TYPE	Photoelectric
LED INDICATOR	Output status: red
PROTECTION	Current limited for loads less than 32 Vac/dc
CORD LENGTH	84 ft
MAXIMUM AC CURRENT	80 mA
MAXIMUM DC CURRENT	110 mA
OPERATING TEMPERATURE - MAX	131 °F
OPERATING TEMPERATURE - MIN	-13 °F
ENVIRONMENTAL RATING	NEMA 1, NEMA 3, NEMA 4, NEMA 4X, NEMA 6, NEMA 6P, NEMA 12, NEMA 13

Resources

SPECIFICATIONS AND DATASHEETS [Eaton Specification Sheet - 12155AF07D10](#)

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

